


**RADFORD UNIVERSITY
ALLEN BUILDING ELECTRICAL REPLACEMENT
PROJECT NUMBER 217-B5217-004**

**ADDEDNUM NO. 3
DECEMBER 10, 2025**



General:

1. Bids are due **prior to 2:00pm on January 6, 2026**, at the Facilities Planning & Construction Office, Armstrong Complex, 501 Stockton Street, Radford, VA 24142
2. Bids will be publicly opened and read aloud starting at **2:00pm on January 7, 2026**, at the same location.

Plan Sheets:

1. **REPLACEMENT:** Replace plan sheet T1.01 "Cover Sheet" with the attached T1.01 "Cover Sheet."
2. **REPLACEMENT:** Replace plan sheet A2.02 "Elevations, Details, Partition Types" with the attached A2.02 "Elevations, Details, Partition Types."
3. **REPLACEMENT:** Replace plan sheet C0.01 "General Notes" with the attached C0.01 "General Notes."
4. **REPLACEMENT:** Replace plan sheet C2.01 "Erosion & Sediment Control & Demolition Plan" with the attached C2.01 "Erosion & Sediment Control & Demolition Plan."
5. **REPLACEMENT:** Replace plan sheet C3.01 "Site Plan" with the attached C3.01 "Site Plan."
6. **REPLACEMENT:** Replace plan sheet C5.01 "Details" with the attached C5.01 "Details."
7. **REPLACEMENT:** Replace plan sheet M0.01 "Mechanical Symbols & Abbreviations" with the attached M0.01 "Mechanical Symbols & Abbreviations."
8. **REPLACEMENT:** Replace plan sheet M0.02 "Mechanical Notes" with the attached M0.02 "Mechanical Notes."
9. **REPLACEMENT:** Replace plan sheet M0.03 "Mechanical Notes" with the attached M0.03 "Mechanical Notes."
10. **REPLACEMENT:** Replace plan sheet MD1.11 "Ground Floor Mechanical Demolition Plan" with the attached MD1.11 "Ground Floor Mechanical Demolition Plan."
11. **REPLACEMENT:** Replace plan sheet MD1.21 "First Floor Mechanical Demolition Plan" with the attached MD1.21 "First Floor Mechanical Demolition Plan."
12. **REPLACEMENT:** Replace plan sheet MD1.31 "Roof Mechanical Demolition Plan" with the attached MD1.31 "Roof Mechanical Demolition Plan."
13. **REPLACEMENT:** Replace plan sheet M1.11 "Ground Floor Mechanical Plan" with the attached M1.11 "Ground Floor Mechanical Plan."
14. **REPLACEMENT:** Replace plan sheet M1.12 "Ground Floor Mechanical Plan" with the attached M1.12 "Ground Floor Mechanical Plan."
15. **REPLACEMENT:** Replace plan sheet M1.21 "First Floor Mechanical Plan" with the attached M1.21 "First Floor Mechanical Plan."
16. **REPLACEMENT:** Replace plan sheet M1.31 "Roof Mechanical Plan" with the attached M1.31 "Roof Mechanical Plan."
17. **REPLACEMENT:** Replace plan sheet M5.05 "Details" with the attached M5.05 "Details."
18. **DELETION:** Delete plan sheet M5.06 "Details."
19. **DELETION:** Delete plan sheet M5.07 "Details."
20. **DELETION:** Delete plan sheet M5.08 "Details."
21. **REPLACEMENT:** Replace plan sheet M7.01 "Mechanical Controls" with the attached M7.01 "Mechanical Controls."
22. **REPLACEMENT:** Replace plan sheet E0.01 "Electrical Symbols & Abbreviations" with the attached E0.01 "Electrical Symbols & Abbreviations."
23. **REPLACEMENT:** Replace plan sheet E1.11 "Ground Power Plan" with the attached E1.11 "Ground Power Plan."

24. **REPLACEMENT:** Replace plan sheet E1.12 "Ground Lighting Plan" with the attached E1.12 "Ground Lighting Plan."
25. **REPLACEMENT:** Replace plan sheet E1.21 "First Floor Power Plan" with the attached E1.21 "First Floor Power Plan."
26. **REPLACEMENT:** Replace plan sheet E1.22 "First Floor Lighting Plan" with the attached E1.22 "First Floor Lighting Plan."
27. **REPLACEMENT:** Replace plan sheet E4.01 "Ground Floor Electrical Plan" with the attached E4.01 "Ground Floor Electrical Plan."
28. **REPLACEMENT:** Replace plan sheet E4.02 "Ground Floor Electrical Room Plans" with the attached E4.02 "Ground Floor Electrical Room Plans."
29. **REPLACEMENT:** Replace plan sheet E5.01 "Electrical Details" with the attached E5.01 "Electrical Details."
30. **REPLACEMENT:** Replace plan sheet E5.02 "Electrical Details" with the attached E5.02 "Electrical Details."
31. **DELETION:** Delete plan sheet E5.03 "Electrical Details."
32. **REPLACEMENT:** Replace plan sheet E6.01 "Schedules and Diagrams" with the attached E6.01 "Schedules and Diagrams."
33. **REPLACEMENT:** Replace plan sheet E9.01 "Riser Diagrams" with the attached E9.01 "Riser Diagrams."

Specifications:

1. **REPLACEMENT:** Replace specification section 00 01 02 "Table of Contents" with the attached 00 01 02 "Table of Contents."
2. **REPLACEMENT:** Replace the "Invitation for Bids" in the contract documents with the attached "Invitation for Bids".
3. **REPLACEMENT:** Replace specification section 00 01 07 "Seals Page" with the attached 00 01 07 "Seals Page."
4. **DELETION:** Delete specification section 23 05 00 "HVAC Firestopping."
5. **REPLACEMENT:** Replace specification section 23 05 48 "HVAC Seismic, Wind and Vibration Controls" with the attached 23 05 48 "HVAC Seismic, Wind and Vibration Controls."
6. **REPLACEMENT:** Replace specification section 26 05 26 "Grounding and Bonding" with the attached 26 05 26 "Grounding and Bonding."
7. **ADDITION:** Add three (3) UL details (C-AJ-5061, W-L-1164, and W-L-5064) to the project manual.

Pre-Bid Questions:

1. Specification Section 26 27 26, Page 707, Paragraph D – This section says "replace all devices that have been in temporary use during construction or that show signs that they were installed before building finishing operations were complete. Does this only relate to the exit sign and light fixtures or does any material/equipment that appears old or damaged need to be replaced?"

Answer: This specification section is in regards to any temporary items installed by the Contractor to perform the work (i.e. any temp power, temp receptacles to power tools, temp lighting to perform work, etc.). It includes anything the Contractor installs in order to perform the work and that isn't on the plans. This section does not apply to the temporary devices called out on the plans. The Contractor is not expected to replace all old/deteriorated devices or equipment in the building that are outside of the scope of this project.

2. Drawing Sheet E1.21 - Notes 2&4 describe a junction box for a future duct detector for AHU-1. Note 2 has this Junction box on the roof and note 4 has the junction box above the ceiling. Which location requires the j box or does this AHU-1 require 2 boxes, 1 above the ceiling with the other j boxes on the plan, 1 on the roof.

Answer: The junction box shall be installed above the first floor accessible ceiling, just below the roof at the future AHU-1 location. The junction box is not at the rooftop. Note #2 will be modified for clarity in Addendum 3.

3. I would like to know the peak electrical demand on the current electrical service feeding the building now.

Answer: Existing peak 12-month demand load is 46kW according to the information provided by Radford University. This information is located on sheet E6.01, under the "Building Load Summary" table.

4. Is seismic performance and compliance with ASCE/SEI 7 required on this project as listed in 236426 Air Cooled Chillers specification section 1.2.A?

Answer: Seismic performance in compliance with ASCE/SEI 7-22 is required for centrifugal chillers only. However, section 236426 requires a scroll-type chiller, so this requirement does not apply unless a manufacturer were to submit a substitution request for a centrifugal-style chiller.

Robert S. Notte, PE, LEED AP
Project Manager | Vice President
Dewberry Engineers Inc.

Attachments: T1.01 "Cover Sheet" (1 Page)
A2.02 "Elevations, Details, Partition Types" (1 Page)
C0.01 "General Notes" (1 Page)
C2.01 "Erosion & Sediment Control & Demolition Plan" (1 Page)
C3.01 "Site Plan" (1 Page)
C5.01 "Details" (1 Page)
M0.01 "Mechanical Symbols & Abbreviations" (1 Page)
M0.02 "Mechanical Notes" (1 Page)
M0.03 "Mechanical Notes" (1 Page)
MD1.11 "Ground Floor Mechanical Demolition Plan" (1 Page)
MD1.21 "First Floor Mechanical Demolition Plan" (1 Page)
MD1.31 "Roof Mechanical Demolition Plan" (1 Page)
M1.11 "Ground Floor Mechanical Plan" (1 Page)
M1.12 "Ground Floor Mechanical Plan" (1 Page)
M1.21 "First Floor Mechanical Plan" (1 Page)
M1.31 "Roof Mechanical Plan" (1 Page)
M5.05 "Details" (1 Page)
M7.01 "Mechanical Controls" (1 Page)
E0.01 "Electrical Symbols & Abbreviations" (1 Page)
E1.11 "Ground Power Plan" (1 Page)
E1.12 "Ground Lighting Plan" (1 Page)
E1.21 "First Floor Power Plan" (1 Page)
E1.22 "First Floor Lighting Plan" (1 Page)
E4.01 "Ground Floor Electrical Plan" (1 Page)
E4.02 "Ground Floor Electrical Room Plans" (1 Page)
E5.01 "Electrical Details" (1 Page)
E5.02 "Electrical Details" (1 Page)
E6.01 "Schedules and Diagrams" (1 Page)
E9.01 "Riser Diagrams" (1 Page)
00 01 02 "Table of Contents" (4 Pages)
00100 "Invitation for Bids" (1 Page)
00 01 07 "Seals Page" (4 Pages)
23 05 48 "HVAC Seismic, Wind and Vibration Controls." (11 Pages)
26 05 26 "Grounding and Bonding" (4 Pages)
UL details (C-AJ-5061, W-L-1164, and W-L-5064) (6 Pages)

P:\50158550\Constr\Constr Contract\Electrical Bid\Electrical Addendum 3\2025.12.10_Addendum 3_FINAL.docx

END OF ADDENDUM 3

DRAWING INDEX

GENERAL

11.01

COVER SHEET

11.01

FIRE RATING PLANS

11.02

EGRESS PLAN

ARCHITECTURAL

AD1.11

GROUND FLOOR DEMOLITION PLAN

AD1.13

GROUND FLOOR DEMOLITION RCP

A1.11

GROUND FLOOR ANNOTATION & DIMENSION PLAN

A1.13

GROUND FLOOR REFLECTED CEILING PLAN

A2.02

ELEVATIONS, DETAILS, PARTITION TYPES

CIVIL

C0.01

GENERAL NOTES

C1.01

EXISTING CONDITIONS

C2.01

EROSION & SEDIMENT CONTROL & DEMOLITION PLAN

C3.01

SITE PLAN

C4.01

PROFILES

C5.01

DETAILS

MECHANICAL

M0.01

MECHANICAL SYMBOLS & ABBREVIATIONS

M0.02

MECHANICAL NOTES

M0.03

MECHANICAL NOTES

MD1.11

GROUND FLOOR MECHANICAL DEMOLITION PLAN

MD1.21

FIRST FLOOR MECHANICAL DEMOLITION PLAN

MD1.31

ROOF MECHANICAL DEMOLITION PLAN

M1.11

GROUND FLOOR MECHANICAL PLAN

M1.12

GROUND FLOOR MECHANICAL PLAN

M1.21

FIRST FLOOR MECHANICAL PLAN

M1.31

ROOF MECHANICAL PLAN

M5.01

DETAILS

M5.02

DETAILS

M5.03

DETAILS

M5.04

DETAILS

M5.05

DETAILS

ELECTRICAL

E0.01

ELECTRICAL SYMBOLS & ABBREVIATIONS

ED1.11

GROUND ELECTRICAL DEMOLITION PLAN

ED1.12

GROUND LIGHTING DEMOLITION PLAN

ED1.21

FIRST FLOOR ELECTRICAL DEMOLITION PLAN

E1.11

GROUND POWER PLAN

E1.12

GROUND LIGHTING PLAN

E1.21

FIRST FLOOR POWER PLAN

E1.22

FIRST FLOOR LIGHTING PLAN

E3.01

GROUND LIGHTING EMERGENCY LIGHTING CALCS

E4.01

GROUND FLOOR ELECTRICAL PLAN

E4.02

GROUND FLOOR ELECTRICAL ROOM PLANS

E5.01

ELECTRICAL DETAILS

E5.02

ELECTRICAL DETAILS

STRUCTURAL

S0.01

STRUCTURAL GENERAL NOTES, ABBREVIATIONS, AND SCHEDULES

S5.01

STRUCTURAL DETAILS

LIGHTNING PROTECTION SYSTEM (LPS) RISK FACTORS

Nd = .260
Nc = .0003
Nd > Nc – LPS RISK ASSESSMENT IS RECOMMENDED PER NFPA 780. HOWEVER, OWNER HAS CHOSEN NOT TO INSTALL AN LPS ON THE EXISTING BUILDING DUE TO CURRENT BUDGET AND SCOPE OF PROJECT.

NOTES:

AN ASBESTOS INSPECTION WAS PERFORMED AND NO ACM WAS FOUND. THE ASBESTOS INSPECTION REPORT IS INCLUDED AS AN APPENDIX TO THE PROJECT SPECIFICATIONS.

AN INSPECTION TO IDENTIFY LEAD CONTAINING OR COATED BUILDING COMPONENTS HAS BEEN CONDUCTED AND CAN BE FOUND IN THE PROJECT SPECIFICATIONS. THIS REPORT IS PROVIDED FOR THE CONTRACTOR'S USE AND MAY NOT BE ALL INCLUSIVE. IT IS THE CONTRACTOR'S RESPONSIBILITY TO COMPLY WITH ALL VIRGINIA OCCUPATIONAL SAFETY AND HEALTH (VOSH) REGULATIONS AS THEY PERTAIN TO EMPLOYEE EXPOSURES TO LEAD. ALL LEAD AND LEAD-COATED BUILDING COMPONENTS SHALL BE RECYCLED TO THE EXTENT POSSIBLE.

CONTACT VIRGINIA 811 AT 811, 1-800-552-7001, OR [HTTPS://WWW.VA811.COM](https://www.va811.com) NO LESS THAN 72 HOURS PRIOR TO EXCAVATION AND DO NOT DISTURB THE SOIL UNTIL DIG TICKET HAS BEEN PROCESSED.

PROJECT / BUILDING INFORMATION:

SCOPE OF WORK:	ELECTRICAL IMPROVEMENTS	NATURE OF OCCUPANCY:	POLICE STATION
OCCUPANT LOAD:	85	SEPARATED MIXED USE:	N/A
CONSTRUCTION TYPE:	IIIB	GROSS BUILDING AREA:	12,998 SF
FLOOR AREA:	6,721 SF	WORK AREA:	6,835 SF
FIRE SUPPRESSION:	N/A	FIRE ALARMS:	EXISTING
BUILDING OCCUPANCY USE GROUP:	2 STORY, BUSINESS	WORK TO BE PERFORMED:	LEVEL 2 ALTERATION

CODE REFERENCES

VIRGINIA UNIFORM STATEWIDE BUILDING CODE (VUSBC) – 2021
2021 VIRGINIA EXISTING BUILDING CODE (VEBC) – VUSBC PART II – ALTERATION LEVEL 2
RADFORD UNIVERSITY DESIGN AND CONSTRUCTION STANDARDS – 2019
RADFORD UNIVERSITY ANNUAL STANDARDS AND SPECIFICATIONS FOR EROSION AND SEDIMENT CONTROL AND STORMWATER MANAGEMENT – REVISION 6 – FEBRUARY 16, 2021
MINIMUM DESIGN LOADS FOR BUILDINGS AND OTHER STRUCTURES (ASCE 7-22)
BUILDING CODE REQUIREMENTS FOR STRUCTURAL CONCRETE (ACI 318-19)
VIRGINIA DEPARTMENT OF ENVIRONMENTAL QUALITY – EROSION AND SEDIMENT CONTROL REGULATIONS
VIRGINIA DEPARTMENT OF ENVIRONMENTAL QUALITY – STORMWATER MANAGEMENT REGULATIONS
TITLE II, AMERICANS WITH DISABILITIES ACT OF 1990
CONSTRUCTION AND PROFESSIONAL SERVICES MANUAL, 2025 CPSM, REV. 0, ISSUED 03/17/25
VIRGINIA DEPARTMENT OF TRANSPORTATION ROAD & BRIDGE SPECIFICATIONS – 2020
2020 NATIONAL ELECTRICAL CODE



ALLEN BUILDING
ELECTRICAL REPLACEMENT

100% CONSTRUCTION DOCUMENTS
RADFORD, VIRGINIA

RADFORD UNIVERSITY PROJECT NUMBER 217-B5217-004

ENERGY COMPLIANCE STATEMENTS

HBCA COMPLIANCE STATEMENT: IN ACCORD WITH THE HIGH-PERFORMANCE BUILDINGS ACT, THE BUILDING IS EXEMPT FROM COMPLIANCE BECAUSE OF THE COST OF THE RENOVATIONS DOES NOT EXCEED 50% OF THE VALUE OF THE BUILDING.


VECC COMPLIANCE STATEMENT: IN ACCORD WITH THE VIRGINIA ENERGY CONSERVATION CODE (VECC), THE BUILDING SHALL COMPLY WITH VECC SECTIONS C402 THROUGH C405 AND C408.

DELEGATED DESIGN LIST

AVAILABLE FAULT CURRENT STUDY (PER SPECIFICATION 260571)
DESIGN OF EXCAVATION SUPPORT AND PROTECTIVE SYSTEMS (PER SPECIFICATION 230300)
DESIGN OF TRAPEZE PIPE HANGERS AND EQUIPMENT SUPPORTS (PER SPECIFICATION 230529)
SEISMIC BRACING DESIGN (PER SPECIFICATION 230548)
WIND RESTRAINT DESIGN (PER SPECIFICATION 230548)
FLUSHING AND TESTING PLAN (PER SPECIFICATION 230555)
HYDRONIC PIPING EXPANSION ANCHOR DESIGN (PER SPECIFICATION 232113)
DUCT CONSTRUCTION AND SUPPORT DESIGN (PER SPECIFICATION 230548)

LOCATION MAP

SCALE: NTS




CONTACTS

OWNER: Radford University W. L. Ferguson Project Manager 501 Stockton Street Radford, Virginia 24142 PH. (540) 831-7781 wlferguso@radford.edu	ENGINEER: Dewberry Engineers Inc. Robert S. Notte, P.E., LEED AP 9300 Harris Corners Pkwy, Suite 220 Charlotte, NC 28269 PH. (704) 625-5088 FAX (704) 509-9937 snotte@dewberry.com
--	---

SUBMITTAL	SET NUMBER
<input type="checkbox"/> PRELIMINARY	<input type="checkbox"/> CONSTRUCTION
<input checked="" type="checkbox"/> APPROVAL	<input type="checkbox"/> REVISION
<input type="checkbox"/> BIDDING	<input type="checkbox"/> RECORD

VICINITY MAP






STATE BUILDING OFFICIAL




Dewberry Engineers Inc.
9300 Harris Corners Pkwy - Suite 220
Charlotte, NC 28269
Phone: 704.509.9918
Fax: 704.509.9937
www.dewberry.com

DEB APPROVAL




SCALE: 1" = 100'

Radford UNIVERSITY
ALLEN BUILDING
ELECTRICAL
REPLACEMENT
100% CONSTRUCTION
DOCUMENTS
RADFORD, VIRGINIA



12/5/2025 CIVIL



12/5/2025 STRUCTURAL

REVISIONS			
No.	DATE	BY	Description
2	12/05/2025	RAL	DEB CMTS/ADD 3
1	10/24/2025	RAL	DEB COMMENTS

DRAWN BY: RAL
APPROVED BY: RSN
CHECKED BY: RSN
DATE: JULY 25, 2025
TITLE:

COVER SHEET

DEI PROJECT NO: 50188025
RADFORD UNIVERSITY PROJECT NO: 217-B5217-004

SHEET NO.

T1.01

DEB APPROVAL



SEAL Signed by: *Larry W. Hasson, Jr.*
43F4BFE44B6446...
Larry W. Hasson, Jr.
Lic No. 010298

12/5/2025

KEY PLAN

SCALE:

REVISIONS

2	12/05/25		DEB CMTS/ADD 3	
1	10/24/25		DEB COMMENTS	
NO.	DATE	BY	DESCRIPTION	

DRAWN BY JP

APPROVED BY PR

CHECKED BY BK

DATE JULY 25, 2025

TITLE

ELEVATIONS, DETAILS, PARTITION TYPES

DEI PROJECT NO: 50188025
RADFORD UNIVERSITY PROJECT NO: 217-B5217-004

SHEET NO.

A2.02

S_11-(f) MODIFIER REFER TO DIMENSION PLANS

HEAD

COMPLETELY FILL VOID AT STC RATED WALLS - REFER TO G-200s

FIRE RATED JOINT SYSTEM (UL HW-D-0016) or (UL HW-D-0264)

UNDERSIDE OF STRUCTURE

CEILING SYSTEM - REFER TO REFLECTED CEILING PLAN FOR MATERIAL AND HEIGHT

PLAN

ONE LAYER OF TYPE "X" 5/8" GYPSUM BOARD - EACH SIDE

METAL STUDS AT 16" O.C.

FIBERGLASS INSULATION, COMPLETELY FILL STUD CAVITY

WIDTH REFER BELOW

BASE

REFER TO A-100s FOR FINISHES

FIRE RATED JOINT SYSTEM (UL BW-S-0068)

[illegible]

METAL STUD

S411-S

— TAG LEADER

— WALL MATERIAL IDENTIFIER

— WALL WIDTH

— # OF LAYERS (GWB, CEMENT BOARD, WOOD) ON SIDE 1

— OTHER MODIFIERS

— WALL HEIGHT IDENTIFIER

— # OF LAYERS (GWB, CEMENT BOARD, WOOD) ON SIDE 2

S = METAL STUD C = C-H STUD

SHOWS A ROUNDED VALUE FOR THE WIDTH OF THE STRUCTURAL PORTION OF THE WALL.

OF GYP. WALL BD. LAYERS ON SIDE 1 & 2:
(METAL STUD WALL ONLY)

SHOWS A VALUE FOR THE NUMBER OF LAYERS OF GWB ON EACH SIDE OF THE STUD. A '0' INDICATES ZERO LAYERS OF GWB. WHERE A WALL ONLY HAS GWB ON ONE SIDE, IT IS ALWAYS ON THE EXPOSED SIDE.

WALL HEIGHT IDENTIFIER:

- (DASH) = TO STRUCTURE
A = TO 6" ABOVE CEILING OR ONE FULL COURSE ABOVE CEILING (CMU)

OTHER MODIFIERS:

F = FIRE RATED WALL (COORDINATE WITH CODE COMPLIANCE PLAN FOR RATING AND UL DESIGNATION)

GENERAL NOTES:

1. ALL METAL STUD & FURRED PARTITIONS TO RECEIVE SOUND ATTENUATION BLANKET FULL WIDTH OF STUD AND FULL HEIGHT OF WALL TO UNDERSIDE OF STRUCTURE/DECK, U.N.O. IN FIRE-RATED PARTITIONS, USE SOUND ATTENUATION FIRE BLANKET.
2. SEE PLANS AND DETAIL PLANS FOR CHASE DIMENSIONS. WITHIN CHASE WALLS, USE 4" C-H STUDS MIN.
3. INTERIOR DIMENSIONS ARE TO FACE OF METAL STUD, U.N.O.
4. REFER TO DETAIL DRAWINGS AND SPECIFICATION FOR LOCATIONS AND INFORMATION ON THE VARIOUS TYPES OF GYPSUM BOARD.
5. FINAL WALL PREP REQUIREMENTS BASED ON FINISH SHOWN IN THE ROOM FINISH SCHEDULE AND WITH THE SPECIFICATIONS.
6. REFER TO DETAIL PLANS AND SECTIONS FOR FURTHER DESCRIPTION OF INTERIOR PARTITIONS.
7. REFER TO FINISH DRAWINGS AND SCHEDULES FOR WALL MATERIAL AND FINISHES.
8. LABEL ALL NEW FIRE RATED WALLS IN ACCORDANCE WITH VCC SECTION 703.7.
9. REFER TO **ME.01 AND ES.01** LIFE-SAFETY PENETRATION SCHEDULES **AND SPEC SEC. 078413** FOR FIRE STOPPING SYSTEMS.

42 GROUND FLOOR WALL DETAIL

A2 Scale: 1" = 1'-0"

GROUND FLOOR WALL DETAIL

A3 Scale: 1" = 1'-0"

GROUND FLOOR WALL DETAIL



A4 Scale: 1" = 1'-0"

C3 DOOR AND FRAME TYPES

Scale: 1/4" = 1'-0"

C4 DOOR HEAD AND JAMB



C4 Scale: 1 1/2" = 1'-0"







Dewberry®

DEB APPROVAL



KEY PLAN:



DRAWN BY JP

APPROVED BY PR _____

— CHECKED BY BK

DATE JULY 25, 2025

TITLE


DEI PROJECT NO: 50188025
RADFORD UNIVERSITY PROJECT NO: 217-B5217-004

SHEET NO.

C2.01

- [illegible]

LEE HIGHWAY (HIGHWAY 11)



- NOTES:
1. CONTRACTOR SHALL MAINTAIN ACCESS TO THE POLICE STATION AND ADJACENT AREAS THROUGHOUT CONSTRUCTION.
 2. CONTRACTOR SHALL PROTECT ALL EXISTING UTILITIES THROUGHOUT CONSTRUCTION.
 3. REFER TO MECHANICAL FOR PROPANE PIPING REQUIREMENTS.
 4. FUEL STORAGE AREA TO INCLUDE TWO (2) 1,000-GALLON PROPANE STORAGE TANKS. REFER TO MECHANICAL FOR FUEL STORAGE TANK SIZING CALCULATIONS. TANKS SHALL BE INSTALLED TO MAINTAIN MINIMUM SEPARATION DISTANCES IN ACCORDANCE WITH IFC TABLE 6104.3 AND NFPA 58-2017 TABLE 6.4.1.1:
 - *BUILDINGS: 25 FT
 - *PUBLIC WAYS: 5 FT
 - *PROPERTY LINES: 25 FT
 - *BETWEEN TANKS: 3 FT
 - *FROM VERTICAL PLANE OF OVERHEAD POWER LINES >600 VOLTS: 6 FT

PROPANE TANKS AND ASSOCIATED MANIFOLD PIPING UP TO AND INCLUDING FIRST STAGE PRESSURE REGULATORS ARE BY OWNER'S PROPANE SUPPLIER. CONTRACTOR TO PROVIDE ALL PIPING FROM OUTLET OF SUPPLIER'S FIRST STAGE PRESSURE REGULATOR. CONTRACTOR IS RESPONSIBLE FOR COORDINATING WITH OWNER'S SUPPLIER FOR INSTALLATION OF ALL EQUIPMENT AND ASSOCIATED APPURTENANCES.

PROPOSED 8" CONCRETE PAD
(PAD ELEVATION = 1775.5')
(SEE STRUCTURAL & MECHANICAL SHEETS)

CONTRACTOR TO GRADE SITE TO DRAIN
AWAY FROM PROPOSED CONCRETE PAD

PROPOSED 3" SLEEVE (TYP-2)
(SEE STRUCTURAL, MECHANICAL, & ELECTRICAL SHEETS)

PROPOSED 1" PROPANE
SERVICE LINE

CONTRACTOR SHALL RESTRIPE
EXISTING PARKING SPACES IF
IMPACTED BY CONSTRUCTION

PROPOSED 1" PROPANE
SERVICE LINE -
SEE PROFILE SHEET C4.01

PROPOSED 40 SY OF
ASPHALT PAVEMENT -
SEE DETAIL SHEET C5.01

CONTRACTOR SHALL PHASE WORK
TO MAINTAIN A MINIMUM 15' WIDE
DRIVE AISLE AT ALL TIMES

SMH
TOP=1773.24
INV=1771.55
INV=1764.12
INV=1764.03

N 3580720.60
E 10886095.17
N 3580718.44
E 10886098.14

EMH
TOP=1777.07

CONC. LOADING
DOCK

CONC. PAD

CONC. PAD

CONC. PAD

CONC. PAD

CONC. PAD

CONC. PAD

CONC. PAD

CONC. PAD

CONC. PAD

CONC. PAD

CONC. PAD

CONC. PAD

CONC. PAD

CONC. PAD

CONC. PAD

CONC. PAD

CONC. PAD

CONC. PAD

CONC. PAD

CONC. PAD

CONC. PAD

CONC. PAD

CONC. PAD

POLICE STATION
1 STORY WITH BASEMENT
PARTIALLY SKETCHED

STUB PROPOSED PROPANE SERVICE LINE AND
UNDERGROUND CONDUITS (TYP - 2) 6" ABOVE GRADE.
(SEE MECHANICAL & ELECTRICAL SHEETS FOR CONTINUATION)

APPROXIMATE LOCATION OF
ELECTRICAL LINE FROM
CHILLER TO BUILDING
(SEE ELECTRICAL SHEETS)

CONTRACTOR TO GRADE SITE TO
DRAIN AWAY FROM PROPOSED
CONCRETE PAD

CONTRACTOR SHALL EXTEND EXISTING
CONCRETE PAD (PAD ELEVATION = 1779.85')
(SEE STRUCTURAL & MECHANICAL SHEETS)



MAX SLOPE = 1.9:1

DEWBERRY NAIL #700
N: 3,580,593.35'
E: 10,886,201.02'
ELEV: 1,778.64'




Dewberry Engineers Inc.
9300 Harris Corners Pkwy - Suite 220
Charlotte, NC 28269
Phone: 704.509.9918
Fax: 704.509.9937
www.dewberry.com

DEB APPROVAL



SCALE: 1" = 10'



REVISIONS				
NO.	DATE	BY	DESCRIPTION	
2	12/05/2025	RAL	DEB CMTS/ADD 3	
1	10/24/2025	RAL	DEB COMMENTS	

DRAWN BY: JP
APPROVED BY: PR
CHECKED BY: BK
DATE: JULY 25, 2025
TITLE: SITE PLAN

DEI PROJECT NO: 50188025
RADFORD UNIVERSITY PROJECT NO: 217-B5217-004
SHEET NO.

C3.01

E

D

C

B

A

1992		3.33
TABLE 3.33-A TYPE OF SOD AVAILABLE IN VIRGINIA AND RECOMMENDED USES		
Kentucky Bluegrass: Adapted to the Northern Piedmont and Mountain Regions. Individual varieties selected must make up not less than 10%, nor more than 35% of the total mixture on a weight basis. All varieties must be certified. Selections can be made from Category I alone or various combinations of Categories I, II and III, as noted.		
Category I - Recommended Kentucky Bluegrass Varieties		
65%- 100% A-34, Abbey, Aspen, Asset, Baron, Blackburg, Brink, Chert, Chertan, Classic, Cventry, Georgetown, Glade, Hage, Julia, Liberty, Lori's 1757, Merit, Midnight, Monopoly, Plush, Princeton 104, Rugby, Suffolk, Vicia		
Category II - Special use varieties. If used, must contain at least 65% Category I varieties		
Shade Tolerant		
10-35% Bristol, Columbia, Georgetown, Glade, Midnight		
Low-Maintenance Tolerant		
10-35% Columbia, Georgetown, Monopoly, Ram I, Touchdown, Vicia		
Category III - Promising Kentucky Bluegrass - Limited performance data or seed availability		
10-35% Dawn, Estate, Freedom, Kelly		
(continued)		

III - 337


SO

1992		3.33
TABLE 3.33-A (CONTINUED) TYPE OF SOD AVAILABLE IN VIRGINIA AND RECOMMENDED USES		
Tall Fescue: Adapted to the entire state.		
Recommended Tall Fescue Varieties:		
90-100% Aringo, Apache, Bonanza, Chiefain, Finelawn SGI, Mesa, Rebel II, Shenandoah, Tribute		
Promising Tall Fescues		
Certified Arriba, Austin, Avanti, Atee, Cochise, Crossfire, Eldorado, Hubbard 87, Jaguar II, Maverick II, Monarch, Olympic II, Phoenix, Safari, Shortstop, Sundance, Taurus, Thoroughbred, Titan, Tradition, Vegas, Winchester, Wrangler		
0-10% Kentucky bluegrass: Baron, Chert, Columbia, Monopoly, Nassau, Ram I, Vicia		
Bermudagrass: Tufcote is adapted to the Richmond-Danville-Newport News triangle. Midiron may be used east of Roanoke and south of Charlottesville. Tilgreen and Tilway may be used to the east and south of Richmond. Vamont may be used east of Roanoke and at lower elevations in southwestern Virginia.		
Certified Midiron, Tilgreen [®] , Tilway, Tilway II, Tufcote and Vamont		
Zoysiagrass: This sod performs best in southeastern Virginia.		
Meyer, Emerald [®]		
Note: Common Bermudagrass is not recommended for sod production.		
[®] Only recommended in southeastern Virginia.		

Source: 1991 Virginia Turfgrass Variety Recommendations, Virginia Crop Improvement Association

III - 338

SO




Source: Va. DSWC

Plate 3.33-1

III - 339

SO



TYPICAL PAVEMENT SECTION
N.T.S.

SEED		
APPLICATION DATES	SPECIES	APPLICATION RATES
SEPT. 1 - FEB. 15	50/50 MIX OF ANNUAL RYEGRASS (LOLIUM MULTI-FLORUM) & CEREAL (WINTER) RYE (SECALE CEREALE)	50-100 (lbs./acre)
FEB. 16 - APR. 30	ANNUAL RYEGRASS (LOLIUM MULTI-FLORUM)	60-100 (lbs./acre)
MAY 1 - AUG. 31	GERMAN MILLET	50 (lbs./acre)

FERTILIZER & LIME	
• APPLY 10-10-10 FERTILIZER AT A RATE OF 450 lbs./acre (OR 10 lbs./1,000 sq. ft.)	
• APPLY PULVERIZED AGRICULTURAL LIMESTONE AT A RATE OF 2 TONS/ACRE (OR 90 LBS./1,000 SQ. FT.)	

NOTE:
1. A SOIL TEST IS NECESSARY TO DETERMINE THE ACTUAL AMOUNT OF LIME REQUIRED TO ADJUST THE SOIL pH OF SITE.
2. INCORPORATE THE LIME AND FERTILIZER INTO THE TOP 4-6 INCHES OF THE SOIL BY DISKING OR BY OTHER MEANS.
3. WHEN APPLYING SLOWLY AVAILABLE NITROGEN USE RATES AVAILABLE IN EROSION & SEDIMENT CONTROL TECHNICAL BULLETIN #4, 2003 NUTRIENT MANAGEMENT FOR DEVELOPMENT SITES AT: <http://www.dcr.state.va.us/sw/e&s.htm#pubs>

TEMPORARY SEEDING SPECIFICATIONS QUICK REFERENCE FOR ALL REGIONS

TABLE 3.31-B
(REVISED JUNE 2003)


TS

MULCHES	RATES		NOTES
	PER ACRE	PER 1,000 sq. ft.	
STRAW	2.5 TONS	2 BALES	• CLEAN OAT OR WHEAT STRAW WELL SEASONED BEFORE BAILING. • FREE FROM MATURE SEED-BEARING STALKS OR PROHIBITED NOXIOUS WEEDS.

NOTES:
1. STRAW SHALL BE PLACED ON SEEDING AREAS WITHIN 24 HOURS OF SEEDING.
2. PLACE STRAW MULCH UNIFORMLY IN A CONTINUOUS BLANKET (CONTRACTOR WILL BE ASKED TO REMOVE ANY STRAW CLUMPS LEFT ON THE SEEDING AREA).
3. A MECHANICAL BLOWER MAY BE USED FOR STRAW MULCH APPLICATION WHEN ACCEPTABLE TO THE OWNER'S REPRESENTATIVE.
4. STRAW MULCH SHALL BE TACKED DOWN BY APPLYING A LIGHT COATING OF HYDROMULCH.

ORGANIC MULCH MATERIALS AND APPLICATION RATES


MU



SILT FENCE N.T.S.

CONSTRUCTION OF A SILT FENCE

PAIN SHALL MATCH
RADFORD UNIVERSITY
CAMPUS STANDARDS




STEEL BOLLARD
N.T.S.

* GRAVEL SHALL BE VDOT #3, #357 OR #5 COARSE AGGREGATE.

INLET PROTECTION

THIS METHOD OF INLET PROTECTION IS APPLICABLE WHERE HEAVY CONCENTRATED FLOWS ARE EXPECTED BUT NOT WHERE PONDING AROUND THE STRUCTURE MIGHT CAUSE EXCESSIVE INCONVENIENCE OR DAMAGE TO ADJACENT STRUCTURES AND UNPROTECTED AREAS.


IF STONE FILTER BECOMES CLOGGED, CONTRACTOR SHALL PULL AWAY STONES FROM THE INLET CLEAN THEM AND/OR REPLACE THEM PER VESCH REQUIREMENTS.



SPECIFIC APPLICATION
N.T.S.


CONSTRUCTION FENCE

N.T.S.



CONSTRUCTION FENCE
N.T.S.


TEMPORARY CONSTRUCTION SAFETY FENCING



NOTES :
1. ALL BACKFILL IN TRENCHES WHICH ARE LOCATED WITHIN PAVED STREETS & ROADS, SHALL BE VDOT NO. 21-A STONE FROM SPRING LINE TO BOTTOM OF PAVEMENT.
2. INSTALL UNDERGROUND UTILITY MARKER PER SPECIFICATIONS.

PIPE LAYING CONDITION

N.T.S.



STATE BUILDING OFFICIAL

Dewberry

Dewberry Engineers Inc.
9300 Harris Corners Pkwy - Suite 220
Charlotte, NC 28269
Phone: 704.509.9918
Fax: 704.509.9937
www.dewberry.com

DEB APPROVAL

Radford UNIVERSITY
ALLEN BUILDING
ELECTRICAL
REPLACEMENT
100% CONSTRUCTION
DOCUMENTS
RADFORD, VIRGINIA

SEAL
STATE OF VIRGINIA
ROBERT S. NOTTE
Lic. No. 036367
PROFESSIONAL ENGINEER

12/5/2025

KEY PLAN:

SCALE: 1" = 10'

0' 10' 20'

REVISIONS

NO.	DATE	BY	DESCRIPTION
2	12/05/2025	RAL	DEB CMTS/ADD 3
1	10/24/2025	RAL	DEB COMMENTS

DRAWN BY: JP
APPROVED BY: PR
CHECKED BY: BK
DATE: JULY 25, 2025
TITLE:

DETAILS

DEI PROJECT NO: 50188025
RADFORD UNIVERSITY PROJECT NO: 217-B5217-004
SHEET NO.

C5.01

E


D

C

B

A














STANDARD DETAILING SYMBOLS



HVAC SYMBOLS

SYMBOL		DESCRIPTION
GRILLES		
CEILING MTD	WALL MTD	
		SUPPLY AIR DEVICE
		RETURN AIR DEVICE
		EXHAUST AIR DEVICE
X 500		AIR DEVICE TAG "TYPE" / "CFM" (SEE SCHEDULE)
		ECCENTRIC TRANSITION
		CONCENTRIC TRANSITION
		RADIUS OFFSET (IN THE VERTICAL)
		MITERED OFFSET (IN THE VERTICAL)
		RADIUS ELBOW
		MITERED ELBOW WITH TURNING VANES
RISE	DROP	SUPPLY DUCT
RISE	DROP	RETURN AIR DUCT
RISE	DROP	EXHAUST AIR DUCT
		FLEX DUCT
		DEMOLITION DUCTWORK OR EQUIPMENT.
		EXISTING DUCTWORK OR EQUIPMENT.
		NEW OR FUTURE DUCTWORK OR EQUIPMENT
		ROUND DUCT RISE/DROP
		RECTANGULAR TAKE-OFF
		ROUND TAKE-OFF
BOTTOM 	TOP 	ACCESS DOORS

HVAC SYMBOLS CONTINUED

SYMBOL	DESCRIPTION		
DAMPERS			
	DAMPER	<u>ABBREVIATIONS</u> "AD" = AUTOMATIC/MOTORIZED "FD" = FIRE	
	FIRE DAMPER		
	MANUAL DAMPER		
	GRAVITY BACKDRAFT DAMPER		
	MOTORIZED PARALLEL BLADE DAMPER		
	MOTORIZED OPPOSED BLADE DAMPER		
CONTROLS			
	TEMPERATURE SENSOR		
	HUMIDITY SENSOR		
	CARBON MONOXIDE SENSOR		
	CARBON DIOXIDE SENSOR		
	DUCT MOUNTED SMOKE DETECTOR		
	EMERGENCY POWER OFF SWITCH (E-STOP)		
	MANUAL MOTOR STARTER, FRACTIONAL HORSEPOWER		

MECHANICAL PIPING SYMBOLS

SYMBOL	DESCRIPTION	
	BALL VALVE	
	STOP VALVE (HANDLE OPTIONAL)	
	3-WAY VALVE	
	BALANCING VALVE AUTOMATIC	
	BALANCING VALVE MANUAL	
	BUTTERFLY VALVE	
	CHECK VALVE	
	CONTROL VALVE	
	3-WAY CONTROL VALVE	
	GATE VALVE	
	GLOBE VALVE	
	REDUCED PRESSURE ZONE	
	PRESSURE REGULATING VALVE	
	PIPE TURN UP	
	PIPE TURN DOWN	
	PIPE BOTTOM TAKE OFF	
	PIPE TOP TAKE OFF	
	PIPE CAP OR PLUG	
	PIPE UNION	
	WYE STRAINER	
	PIPE ANCHOR	
	PIPE ALIGNMENT GUIDE	

MECHANICAL PIPING SYSTEMS

SYMBOL	DESCRIPTION	
	CONDENSATE DRAIN	
	CHILLED WATER RETURN	
	CHILLED WATER SUPPLY	
	DRAIN	
	HIGH PRESSURE CONDENSATE	
	HIGH PRESSURE STEAM	
	HEATING WATER RETURN	
	HEATING WATER SUPPLY	
	LOW PRESSURE CONDENSATE	
	LOW PRESSURE STEAM	
	MAKEUP WATER	
	PROPANE GAS	
	REFRIGERANT	

STATE BUILDING OFFICIAL




Dewberry Engineers Inc.
9300 Harris Corners Parkway
Suite 220
Charlotte, NC 28269-3797
704.500.5815
NC License No. F-0929

DEB APPROVAL



SEAL



12/5/2025

KEY PLAN:

SCALE:

REVISIONS

NO.	DATE	BY	DESCRIPTION
2	12/05/25	SWD	DEB CMNTS/ADD 3
1	10/24/25	SWD	DEB COMMENTS

DRAWN BY _____ SMF

APPROVED BY _____ SWD

CHECKED BY _____ JMT

DATE _____ JULY 25, 2025

TITLE

MECHANICAL
SYMBOLS &
ABBREVIATIONS

DEI PROJECT NO: 50188025

RADFORD PROJECT NO: 217-B5217-004

SHEET NO.

M0.01

DRAWING LIST - MECHANICAL

M0.01	MECHANICAL SYMBOLS & ABBREVIATIONS
M0.02	MECHANICAL NOTES
M0.03	MECHANICAL NOTES
MD1.11	GROUND FLOOR MECHANICAL DEMOLITION PLAN
MD1.21	FIRST FLOOR MECHANICAL DEMOLITION PLAN
MD1.31	ROOF MECHANICAL DEMOLITION PLAN
M1.11	GROUND FLOOR MECHANICAL PLAN
M1.12	GROUND FLOOR MECHANICAL PLAN
M1.21	FIRST FLOOR MECHANICAL PLAN
M1.31	ROOF MECHANICAL PLAN
M5.01	DETAILS
M5.02	DETAILS
M5.03	DETAILS
M5.04	DETAILS
M5.05	DETAILS
M6.01	MECHANICAL SCHEDULES
M6.02	MECHANICAL SCHEDULES
M7.01	MECHANICAL CONTROLS
M7.02	MECHANICAL CONTROLS
M7.03	MECHANICAL CONTROLS
M9.01	ISOMETRICS, PERSPECTIVES
TOTAL: 21	

E

D

C

B

A

MECHANICAL GENERAL NEW
WORK NOTES

- ALL WORK SHALL BE PERFORMED IN ACCORDANCE WITH APPLICABLE STATE CODES AND REGULATIONS. MECHANICAL EQUIPMENT SHALL BE SELECTED TO MEET OR EXCEED THE REQUIREMENTS OF THE STATE ENERGY CONSERVATION CODE. MECHANICAL WORK SHALL COMPLY WITH PROJECT SPECIFICATIONS.
- FURNISH AND INSTALL ALL INCIDENTAL ACCESSORIES REQUIRED TO MAKE THE MECHANICAL WORK COMPLETE AND OPERATIONAL.
- CONTRACTOR SHALL BE RESPONSIBLE FOR INSPECTING, TESTING AND VERIFYING CONTROL SEQUENCES, LINE BY LINE, AND VERIFYING OPERATION OF THE EQUIPMENT. ALL EQUIPMENT, VALVES, DAMPERS ACTUATORS, ETC. SHALL BE FUNCTIONAL PRIOR TO FINAL COMMISSIONING. COORDINATE WITH ELECTRICAL AND TAB CONTRACTORS. REFER TO SECTION 239000 FOR MORE DETAIL.
- THESE DRAWINGS ARE DIAGRAMMATIC. EXACT EQUIPMENT LOCATIONS AND DUCT AND PIPING ROUTING SHALL BE COORDINATED WITH THE BUILDING AND SITE CONDITIONS. THE ACTUAL EQUIPMENT AND MINIMUM CLEARANCE DIMENSIONS SHALL BE VERIFIED WITH THE SUPPLIERS. FITTINGS NOT SHOWN ON THE DRAWINGS MIGHT BE REQUIRED.
- EQUIPMENT, DUCTWORK, PIPING AND CONDUIT LAYOUT SHALL BE COORDINATED WITH BUILDING COMPONENTS AND OTHER TRADES PRIOR TO INSTALLATION. THE SYSTEM SHALL BE NEATLY ARRANGED TO MAXIMIZE SPACE ABOVE CEILINGS AND WITHIN CHASES. MAINTAIN MINIMUM EQUIPMENT AND DEVICE MAINTENANCE CLEARANCES. DEVICES SHALL BE READILY MAINTAINABLE. METERS AND GAGES SHALL BE ORIENTED FOR BEST VIEW. INSTALLED MATERIALS NOT COORDINATED SHALL BE REMOVED AND REINSTALLED AT NO ADDITIONAL COST.
- DUCT OFFSETS SHALL BE MADE AT 15 OR 30-DEGREE ANGLES WHERE POSSIBLE BUT AT NEVER MORE THAN 45-DEGREES.
- WALL-MOUNTED CONTROL SENSORS SHALL BE INSTALLED AT 48-INCHES ABOVE THE FLOOR TO THE TOP OF SENSOR. COORDINATE EXACT LOCATIONS WITH LIGHT SWITCHES. WHEN BOTH ARE INDICATED ADJACENT TO A DOOR, LOCATE THE SWITCH CLOSEST TO THE DOOR AND THE SENSOR WITHIN 12-INCHES OF THE SWITCH.
- CONTROL AND ALARM DEVICES SHALL BE INSTALLED IN BACK-BOXES WITHIN NEW AND EXISTING WALLS. SURFACE-MOUNTED CONDUIT AND RACEWAY WILL NOT BE ACCEPTED EXCEPT FOR EXISTING SOLID CONCRETE WALLS. DEVICE BACK-BOXES IN FIRE-RATED WALLS SHALL HAVE FIRESTOP PUTTY PADS OR EQUIVALENT UL-LISTED INSTALLATION.
- PROVIDE APPROVED UL-LISTED FIRESTOP SYSTEMS AT PENETRATIONS OF LIFE-SAFETY RATED ASSEMBLIES AS REQUIRED FOR THE WORK. REFERENCE SECTION 078413 "THROUGH PENETRATION FIRESTOP SYSTEMS" FOR REQUIREMENTS AND THE UL DESIGN APPENDIX IN THE PROJECT MANUAL FOR FIRESTOP SYSTEM DETAILS.
- INSTALL LIFE-SAFETY (FIRE, SMOKE AND COMBINATION FIRE AND SMOKE) DAMPERS IN RATED ASSEMBLIES PER UL-LISTED DETAIL IN ACCORDANCE WITH THE BUILDING CODE AND MANUFACTURER'S LISTING REQUIREMENTS.
- PROVIDE A DUCT ACCESS DOOR FOR EACH DUCT-MOUNTED DEVICE REQUIRING MAINTENANCE OR INSPECTION. REFER TO SECTION 23 33 00 FOR DOOR SIZING REQUIREMENTS. COORDINATE CEILING AND WALL ACCESS DOORS WITH DUCT ACCESS DOORS.
- HVAC PIPING SHALL BE NO LESS THAN 3/4-INCH, EXCEPT REFRIGERANT PIPING.
- ALL MOTORIZED EQUIPMENT SHALL BE CONNECTED TO DUCTWORK OR PIPING WITH FLEXIBLE CONNECTIONS.
- ROOF MODIFICATIONS AND REPAIRS SHALL MEET THE REQUIREMENTS OF THE ROOF WARRANTY.
- EXTEND POWER CONDUIT AND WIRING FROM DEDICATED POWER SOURCES TO CONTROL EQUIPMENT AND DEVICES. COORDINATE POWER SOURCES WITH ELECTRICAL CONTRACTOR.
- PIPING BRANCHES FROM MAINS TO HEATING AND COOLING COILS SHALL MATCH SCHEDULED SIZES UNLESS OTHERWISE NOTED.
- MAINTAIN MINIMUM 36-INCH CLEARANCE FOR 120/208V POWER OR 42-INCH CLEARANCE FOR 277/480V POWER AS REQUIRED BY THE NATIONAL ELECTRIC CODE FOR ELECTRICAL EQUIPMENT AND TO PROVIDE MAINTENANCE ACCESS.
- FIELD VERIFY EXACT PIPING SIZES AND FLOW DIRECTIONS PRIOR TO CONNECTING TO PIPING SYSTEM.
- EXPOSED DUCT, PIPING AND CONDUIT SHALL BE PRIMED AND PAINTED TO MATCH ADJACENT SURFACES. REFER TO SPECIFICATIONS FOR DETAILED REQUIREMENTS.
- SCHEDULE ALL SERVICE DISRUPTIONS AND SHUTDOWNS WITH THE OWNER NO LESS THAN 2 WEEKS PRIOR.
- AIR HANDLING UNIT INTAKES SHALL BE SEPARATED BY MINIMUM 10 FEET FROM EXHAUST FANS, EXHAUST VENTS, FLUES, PLUMBING VENTS, ETC.
- EXISTING DUCTWORK AND PIPING SHOWN ARE BASED ON AS-BUILT DRAWINGS AND EXISTING CONDITIONS NOTED TO THE BEST OF ENGINEER'S ABILITY DURING DESIGN. CONTRACTOR SHALL BE RESPONSIBLE FOR FIELD-VERIFYING ALL EXISTING MECHANICAL ITEMS SHOWN PRIOR TO COMMENCING WORK.

2

MECHANICAL GENERAL DEMOLITION
WORK NOTES

- VERIFY PROJECT SITE EXISTING CONDITIONS PRIOR TO BID. EXISTING CONDITIONS INDICATED IN THESE DOCUMENTS ARE APPROXIMATE AND DO NOT INCLUDE EVERY COMPONENT.
- RECORD EXISTING CONDITIONS PRIOR TO THE START OF WORK. REPAIR DAMAGES RESULTING FROM PROJECT WORK.
- COORDINATE MATERIALS TO BE RETAINED BY THE OWNER PRIOR TO THE START OF DEMOLITION WORK. RETAINED MATERIALS SHALL BE DELIVERED TO A POINT DESIGNATED BY THE OWNER WITHIN A 10-MILE RADIUS OF THE PROJECT SITE. PROPERLY DISPOSE OF ALL REMAINING DEMOLITION MATERIALS. COMPLY WITH MATERIAL RECYCLING REQUIREMENTS. DO NOT ABANDON IN PLACE ANY ITEMS IDENTIFIED TO BE REMOVED UNLESS OTHERWISE NOTED.
- THE SCOPE OF DEMOLITION FOR ITEMS TO BE REMOVED INCLUDES ASSOCIATED SUPPORTS, POWER CONNECTIONS, CONTROLS, CONDUIT, ETC.
- PERFORM ALL DEMOLITION INDICATED INCLUDING THAT REQUIRED TO INSTALL NEW WORK. REMOVE AND REINSTALL MATERIALS TO REMAIN AS NEEDED WHERE REQUIRED TO PERFORM DEMOLITION OR TO INSTALL NEW WORK. REPAIR DAMAGED SURFACES TO MATCH EXISTING ADJACENT SURFACES.
- REMOVE DUCT, PIPING AND CONDUIT BACK TO POINTS INDICATED. PREPARE OPEN ENDS FOR CONNECTION TO NEW WORK INDICATED OR CAP.
- REPAIR DAMAGE TO ANY OPENINGS IN LIFE-SAFETY RATED ASSEMBLIES CREATED BY THE DEMOLITION WORK PER APPROVED UL-LISTED DETAIL IN ACCORDANCE WITH THE BUILDING CODE.
- PIPING AND CONDUIT TO BE REMOVED THAT IS LOCATED BELOW CONCRETE SLAB-ON-GRADE FLOORS OR WITHIN CONCRETE SOLID OR BLOCK WALLS MAY BE ABANDONED IN PLACE UNLESS NECESSARY TO INSTALL NEW WORK OR NOTED OTHERWISE. WHEN ABANDONING CUT PIPING OR CONDUIT BACK AT LEAST 1-INCH BEHIND THE SURFACE, PLUG THE ENDS AND PATCH THE SURFACE WITH SIMILAR MATERIAL.
- CAPTURE AND RECYCLE REFRIGERANT FROM HVAC EQUIPMENT. COMPLY WITH THE EPA REFRIGERANT RECYCLING REQUIREMENTS.
- REMOVE AND REINSTALL LAY-IN CEILING TILES AND GRID AS NEEDED TO PERFORM CONTRACT WORK. STORE CEILING MATERIALS IN A CLEAN DRY PLACE. REPLACE DAMAGED TILES WITH NEW TO MATCH. SELECT ONE ROOM TO INSTALL ALL NEW TILE AND GRID TO PROVIDE THE TILES NEEDED TO REPLACE DAMAGED TILES IN OTHER SPACES.
- DURING RENOVATION, MAINTAIN OPERATION OF EXISTING CONTROL SYSTEMS AND COMPONENTS OUTLINED ON CONTROLS DRAWINGS AND IN THE SEQUENCE OF CONSTRUCTION NOTES ON THIS DRAWING. AT EACH PHASE RE-VERIFY OPERATION OF REMAINING CONTROLLED DEVICES AFTER REMOVAL WORK IS COMPLETE.
- EXISTING SYSTEMS SERVING AREAS OCCUPIED DURING CONSTRUCTION AND SYSTEMS EXPLICITLY INDICATED SHALL BE KEPT IN OPERATION BY TEMPORARY MEANS. TEMPORARY MEANS INCLUDES TEMPORARY BYPASSES OR CONNECTIONS TO BUILDING SYSTEMS AND / OR CONNECTIONS TO TEMPORARY EQUIPMENT. ALL TEMPORARY MEANS, MATERIALS AND EQUIPMENT SHALL BE INCLUDED IN THE CONTRACT UNLESS OTHERWISE NOTED.
- CONTRACTOR SHALL PERFORM PRE-READ TAB AND SUBMIT TAB REPORT TO ENGINEER PRIOR TO COMMENCING DEMOLITION. THIS IS A CRITICAL, NON-NEGOTIABLE STEP OF THE WORK SCOPE THAT SHALL NOT BE OVERLOOKED. REFER TO TEST AND BALANCE (TAB) DESCRIPTION ON M0.03 AND SECTION 230593 "TESTING ADJUSTING AND BALANCING".

HAZARDOUS MATERIAL NOTES

- HAZARDOUS MATERIALS WARNING:** HAZARDOUS MATERIALS ARE ANTICIPATED TO BE ON SITE. REFER TO THE HAZARDOUS MATERIALS TESTING REPORT PROVIDED BY THE OWNER PRIOR TO THE START OF WORK. IF UNCOVERED MATERIALS ARE SUSPECTED OF CONTAINING ASBESTOS, LEAD-BASED PAINT, PCB'S OR ANY OTHER HAZARDOUS MATERIAL, STOP WORK IN THAT AREA AND REPORT THE CONCERN TO THE CONSTRUCTION MANAGER, OWNER, ARCHITECT AND ENGINEER IMMEDIATELY.

STATE BUILDING OFFICIAL




Dewberry Engineers Inc.
9300 Harris Corners Parkway
Suite 220
Charlotte, NC 28269-3797
704.500.6915
NC License No. F-0929

DEB APPROVAL



SEAL



12/5/2025

KEY PLAN:

SCALE:

REVISIONS

NO.	DATE	BY	DESCRIPTION
2	12/05/25	SWD	DEB CMNTS/ADD 3
1	10/24/25	SWD	DEB COMMENTS

DRAWN BY _____ SMF
APPROVED BY _____ SWD
CHECKED BY _____ JMT
DATE _____ JULY 25, 2025

TITLE
MECHANICAL
NOTES

DEI PROJECT NO: 50188025
RADFORD PROJECT NO: 217-B5217-004
SHEET NO.

M0.02

Docusign Envelope ID: 6A42090F-FC13-49FC-A63C-8D42CD4A1846

E

D

C

B

A

12/3/2025 4:25:17 PM

GENERAL PROJECT INFORMATION AND CRITICAL SYSTEMS REQUIREMENTS

GENERAL

RADFORD UNIVERSITY PLANS TO FULLY RENOVATE THE ALLEN BUILDING HVAC SYSTEMS. THIS WORK WILL BE PERFORMED IN TWO CONSECUTIVE PROJECT PHASES UNDER SEPARATE CONTRACTS. THIS PROJECT, THE 'ALLEN BUILDING ELECTRICAL IMPROVEMENTS' IS THE FIRST PROJECT PHASE AND CONSISTS OF UPGRADES TO THE BUILDING ELECTRICAL SYSTEMS TO SUPPORT THE HVAC RENOVATION, AND THE DEMOLITION AND REPLACEMENT OF THE CENTRAL CHILLED WATER AND HEATING HOT WATER SYSTEMS AND ASSOCIATED EQUIPMENT AND CONTROLS. PHASE 1 PROJECT SCOPE IS GENERALLY LOCATED IN GROUND FLOOR MECHANICAL ROOM 002 AND ON THE BUILDING EXTERIOR.

THE SECOND PHASE RENOVATION PROJECT WILL BE PERFORMED BY OTHERS IN THE FUTURE. UNDER A SEPARATE CONTRACT. FUTURE PHASE 2 PROJECT SCOPE WILL INCLUDE DEMOLITION AND REPLACEMENT OF THE REMAINING BUILDING HVAC SYSTEMS NOT INCLUDED UNDER THIS PHASE 1 PROJECT.

CRITICAL SYSTEMS REQUIREMENTS

THE ALLEN BUILDING IS A FULL-SERVICE EMERGENCY FIRST-RESPONSE POLICE DEPARTMENT SERVING THE RADFORD UNIVERSITY COMMUNITY. AS SUCH, PORTIONS OF THE BUILDING AND ASSOCIATED SYSTEMS MUST REMAIN OPERATIONAL AT ALL TIMES. THIS INCLUDES THE FOLLOWING:

1. **EMERGENCY COMMUNICATIONS ROOM 132:** THIS DISPATCH ROOM WILL BE OCCUPIED AT ALL TIMES DURING CONSTRUCTION. ROOM CONTAINS CRITICAL EMERGENCY COMMUNICATION, FIRE, DATA, AND SECURITY EQUIPMENT WHICH REQUIRES CONTINUOUS POWER AND HVAC. CONTINUOUS HVAC TO THE ROOM SHALL BE MAINTAINED VIA EXISTING FAN COIL UNIT FC2215 AND DUCTLESS MINI-SPLIT SYSTEM DMSS-2(E)/CU-2(E).
2. **RADIO ROOM 018:** RADIO ROOM CONTAINS CRITICAL EMERGENCY COMMUNICATION, FIRE, DATA, AND SECURITY EQUIPMENT WHICH REQUIRES CONTINUOUS POWER AND HVAC. CONTINUOUS HVAC TO THE ROOM SHALL BE MAINTAINED BY EXISTING DUCTLESS MINI-SPLIT SYSTEM, DMSS-1(E)/CU-1(E).
3. **BUILDING AUTOMATION SYSTEM (BAS):** EXISTING BAS FUNCTIONALITY FOR CONTROL AND MONITORING OF EQUIPMENT AND DEVICES UNRELATED TO THE HVAC REPLACEMENT WORK SCOPE SHALL BE KEPT IN CONTINUOUS OPERATION BY TEMPORARY MEANS. ALL TEMPORARY MEANS, MATERIALS AND EQUIPMENT SHALL BE INCLUDED IN THE CONTRACT UNLESS OTHERWISE NOTED.
4. **BAS CONNECTION TO CAMPUS SERVER:** THE EXISTING NETWORK INTERFACE BETWEEN THE BUILDING AUTOMATION SYSTEM AND THE CAMPUS SUPERVISORY SERVER SYSTEM SHALL BE MAINTAINED TO SUPPORT CRITICAL COMMUNICATIONS UNTIL WORK IS COMPLETE AND ALL COMMUNICATIONS HAVE BEEN RELOCATED TO THE NEW BUILDING AUTOMATION SYSTEM/HEAD END. REFER TO KEYNOTE 4 ON THIS DRAWING FOR EXISTING SUPERVISORY NETWORK INTERFACE LOCATION IN MECHANICAL ROOM 002.
5. **EMERGENCY OUTDOOR AIR ISOLATION SWITCH:** BAS INTERFACE AND FUNCTIONALITY OF THE CAMPUS-WIDE EMERGENCY OUTDOOR AIR INTAKE ISOLATION SWITCH LOCATED IN EMERGENCY COMMUNICATIONS 132 SHALL BE MAINTAINED THROUGHOUT CONSTRUCTION. REFER TO KEYNOTE 2 ON M1.21 FOR OA SHUTDOWN SWITCH LOCATION.
6. **CAMPUS ELECTRIC METER INTERFACE:** THE CAMPUS-WIDE ELECTRIC SERVICE UTILITY METER IS LOCATED IN THE RADFORD CITY ELECTRIC SUBSTATION, DIRECTLY ADJACENT TO THE ALLEN BUILDING. EXISTING ELECTRIC METER CONNECTIONS TO THE SUBSTATION MUST BE MAINTAINED. THIS IS WHAT CONTROLS THE ENERGY SAVINGS/DEMAND LIMITING CONTROLS ON CAMPUS. THE EXISTING CONNECTION TO THE DEMAND RESPONSE VENDOR (CURRENTLY VOLTUS ENERGY) MUST ALSO BE MAINTAINED. THIS IS HOW RADFORD UNIVERSITY PROVIDES DATA FOR DEMAND RESPONSE PARTICIPATION IN THE VIRGINIA ENERGY DEPARTMENT PROGRAM. REFER TO KEYNOTES 3 AND 10 ON THIS SHEET FOR ADDITIONAL INFORMATION.
7. **BUILDING ELECTRIC METER INTERFACE:** ALLEN BUILDING ELECTRIC METER INTERFACE FROM PANEL MDP TO BAS MUST BE MAINTAINED. REFER TO KEYNOTE 12 ON THIS SHEET.
8. **OWNER COORDINATION:** CONTRACTOR SHALL COORDINATE THE SEQUENCE OF ALL WORK WITH THE OWNER/OCCUPANTS TO MINIMIZE DISRUPTION. REFER TO GENERAL MECHANICAL NOTES ON M0.02 FOR ADDITIONAL REQUIREMENTS.

PIPING SYSTEM FLUSHING NOTES

THE MECHANICAL CONTRACTOR SHALL BE RESPONSIBLE FOR CHILLED WATER AND HOT WATER HYDRONIC PIPING SYSTEMS FLUSHING AND TESTING, SUBJECT TO THE CRITERIA OUTLINED HEREIN AND THE REQUIREMENTS OF SECTION *230555 - HVAC PIPING SYSTEMS FLUSHING AND TESTING.*

EACH BUILDING HYDRONIC SYSTEM LOOP PIPING SHALL BE CLEANED AND FLUSHED PRIOR TO STARTING WORK ON THE RESPECTIVE SYSTEM. REFER TO SEQUENCE OF CONSTRUCTION NOTES ON THIS DRAWING FOR FLUSHING PROCEDURE. CONSTRUCTION SEQUENCE. CONTRACTOR SHALL SUBMIT A DELEGATED-DESIGN SUBMITTAL WITH DETAILED FLUSHING AND TESTING PLAN FOR REVIEW AND APPROVAL OF THE ENGINEER AND OWNER.

GENERAL PROCEDURES FOR PRELIMINARY AND FINAL FLUSHING SHALL INCLUDE AN INITIAL SYSTEM CLEANING PERIOD, OPERATING THE SYSTEM PUMPS WITH A PRE-CLEANING CHEMICAL AGENT TO REMOVE SYSTEM DEPOSITS, AND CONCURRENT BLOWDOWN OF ALL SYSTEM AND EQUIPMENT STRAINERS. FOLLOWING CLEANING AND BLOWDOWN, THE SYSTEM SHALL BE DRAINED, REFILLED, AND RE-FLUSHED UNTIL WATER IS WITHIN TOLERANCES SPECIFIED IN SECTION 230555.

THE FOLLOWING CRITERIA SHALL APPLY:

1. THE PROCESS OF CLEANING SHALL BE PERFORMED AND MONITORED BY A QUALIFIED COMMERCIAL WATER TREATMENT COMPANY. A FULL REPORT OF CLEANING WITH ANALYSIS SHALL BE SUBMITTED.
2. EXISTING BASE MOUNTED CONSTANT VOLUME PUMPS SERVING THE HYDRONIC SYSTEMS MAY BE USED FOR CLEANING AND FLUSHING.
3. STRAINER BLOW-DOWN PROCESS SHALL INCLUDE STRAINERS AT ALL FAN COIL UNITS, OUTDOOR AIR UNIT OAU-1, SYSTEM PUMPS, CHILLER, AND HW HEAT EXCHANGER. FINE MESH STRAINERS SHALL BE INSTALLED AT THE SYSTEM PUMP SUCTION DIFFUSERS FOR THE DURATION OF THE FLUSHING PROCESS.
4. ALL EXISTING EQUIPMENT COILS ARE EQUIPPED WITH A 3-WAY CONTROL VALVE. CONTROL VALVES SHALL BE MODULATED TO FULLY BYPASS THE COIL FOR THE DURATION OF THE FLUSHING PROCESS.
5. ALL SYSTEM WATER AND CHEMICAL CLEANSERS SHALL BE DRAINED TO THE SANITARY SEWER SYSTEM.
6. ALL CHEMICALS SHALL BE APPROVED BY THE OWNER IN WRITING PRIOR TO USE AND SHALL BE COMPATIBLE WITH OWNERS PRESENT PROGRAM AND WITH EXISTING SYSTEM PIPING, EQUIPMENT, SENSORS, AND OTHER COMPONENTS.
7. NO HAZARDOUS CHEMICALS SHALL BE USED. MSDS FOR ALL CHEMICALS TO BE USED SHALL BE SUBMITTED FOR REVIEW AND APPROVAL, PRIOR TO DELIVERY OF CHEMICALS TO SITE.
8. ALL EMPTY CHEMICAL DRUMS, TEMPORARY EQUIPMENT, AND ASSOCIATED DEBRIS SHALL BE REMOVED AT COMPLETION OF JOB.

CENTRAL PLANT REPLACEMENT - SEQUENCE OF CONSTRUCTION

THE ALLEN BUILDING WILL REMAIN OCCUPIED DURING CONSTRUCTION. THE BUILDING'S CENTRAL HEATING AND COOLING SYSTEMS WILL BE CONSECUTIVELY REPLACED IN THE RESPECTIVE SUMMER AND WINTER PERIODS WHEN EACH SYSTEM IS NOT REQUIRED FOR OCCUPANT COMFORT.

PLEASE NOTE THAT THE FOLLOWING SEQUENCE IS NOT MEANT TO SERVE AS STEP-BY-STEP INSTRUCTIONS FOR THE CONTRACTOR. INSTEAD, IT IS MEANT TO SERVE AS A GENERAL GUIDE FOR THE CONTRACTOR'S USE IN MAINTAINING CONTINUOUS HEATING AND COOLING TO THE BUILDING AS SEASONALLY REQUIRED THROUGHOUT THE DURATION OF THE CONSTRUCTION PROCESS.

CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING THE MECHANICAL WORK WITH THE ELECTRICAL WORK. ANY REQUIRED SHUTDOWN WORK SHALL BE COORDINATED WITH THE OWNER A MINIMUM OF 2-WEEKS PRIOR TO THE PLANNED SHUTDOWN.

HEATING PLANT REPLACEMENT – SUMMER 2026

1. PERFORM AIR AND WATER SYSTEM PRE-TAB OF EXISTING HEATING WATER SYSTEM EQUIPMENT AND COILS TO ESTABLISH BASELINE PERFORMANCE OF EXISTING HW SYSTEMS PRIOR TO START OF WORK.
2. ENLARGE MECHANICAL ROOM 002 SPACE INTO SAFETY STORAGE ROOM 001 AS INDICATED ON ARCHITECTURAL DRAWINGS. DEMOLISH EXISTING PARTITION WALL AND INSTALL NEW FIRE-RATED PARTITION WALL. UPGRADE EXISTING MECHANICAL ROOM 002 WALLS TO FIRE-RATED CONSTRUCTION.
3. IN THE SPRING, WHEN BUILDING HEATING IS NO LONGER REQUIRED:
 - A. FLUSH EXISTING BUILDING HW PIPING SYSTEMS. REFER TO PIPING SYSTEMS FLUSHING NOTES ON THIS DRAWING AND SPECIFICATION SECTION *230555 - HVAC SYSTEMS FLUSHING AND TESTING* FOR REQUIREMENTS.
 - B. TAKE STEAM AND HEATING WATER SYSTEMS OFFLINE. DISCONNECT BUILDING HW PIPING SERVICE MAINS AT MECHANICAL ROOM 002 WALL AND DEMOLISH ALL HOT WATER PIPING AND ASSOCIATED EQUIPMENT IN MECHANICAL ROOM 002 UP TO THE POINTS OF DISCONNECTION AT THE ROOM WALL.
 - C. DISCONNECT BUILDING STEAM AND STEAM CONDENSATE SERVICE PIPING AT ISOLATION VALVES LOCATED AT THE CENTRAL PLANT, AND DEMOLISH ALL ABOVE GROUND STEAM AND STEAM CONDENSATE SYSTEMS THROUGHOUT THE ALLEN BUILDING. COMPLETE WITH STEAM TO HW EXCHANGER, HOT WATER PUMPS, CONDENSATE PUMPS, UNIT HEATERS, MAKEUP AIR UNIT STEAM COIL, AND ALL ASSOCIATED PIPING AND CONTROLS. RETURN STEAM PRV AND STEAM METER TO OWNER FOR REUSE.
 - D. INFILL BELOW GROUND CONDENSATE BASIN IN MECH RM 002 AS INDICATED ON STRUCTURAL DRAWINGS.
4. INSTALL TEMPORARY ELECTRIC HEATERS (UH-A TO UH-E AND RHC-1) TO REPLACE DEMOLISHED STEAM HEATERS. TEMPORARY HEATERS TO REMAIN IN SERVICE UNTIL CONSTRUCTION OF FUTURE PHASE 2 PROJECT (BY OTHERS).
5. INSTALL NEW HW PLANT, COMPLETE WITH BOILER(S), PROPANE STORAGE AND SUPPLY PIPING, PRIMARY AND SECONDARY PUMPS, EXPANSION TANK, PIPING, UNIT HEATERS, AND CONTROLS. CONNECT PLANT PIPING TO EXISTING BUILDING HW SERVICE MAINS. FLUSH NEW PIPING, START PLANT, AND TAB NEW AND EXISTING SYSTEM EQUIPMENT AND COILS.

COOLING PLANT REPLACEMENT- WINTER '26-'27

1. PERFORM AIR AND WATER SYSTEMS PRE-TAB OF EXISTING CHILLED WATER SYSTEM EQUIPMENT AND COILS TO ESTABLISH BASELINE PERFORMANCE OF EXISTING CHW SYSTEMS PRIOR TO START OF WORK.
2. IN THE FALL, WHEN BUILDING COOLING IS NO LONGER REQUIRED:
 - A. FLUSH EXISTING BUILDING CHW PIPING SYSTEMS. REFER TO PIPING SYSTEMS FLUSHING NOTES ON THIS DRAWING AND SPECIFICATION SECTION *230555 - HVAC SYSTEMS FLUSHING AND TESTING* FOR REQUIREMENTS.
 - B. TAKE CHILLED WATER PLANT OFFLINE, DISCONNECT BUILDING CHW PIPING SERVICE MAINS AT MECHANICAL ROOM 002 WALL AND DEMOLISH ALL CHILLED WATER PIPING AND ASSOCIATED EQUIPMENT AND CONTROLS IN MECHANICAL ROOM 002 AND OUTSIDE, UP TO THE POINTS OF DISCONNECTION AT THE MECHANICAL ROOM WALL.
3. INSTALL NEW CHW PLANT, COMPLETE WITH CHILLER, PUMPS, BUFFER TANK, PIPING, AND CONTROLS. CONNECT PLANT PIPING TO BUILDING CHW SERVICE MAINS, FLUSH NEW PIPING, START PLANT, AND TAB NEW AND EXISTING EQUIPMENT AND COILS.

TEST AND BALANCE (TAB) DESCRIPTION

PRE-CONSTRUCTION TAB:

- PRE-READ TAB OF THE EXISTING CHILLED WATER AND HOT WATER SYSTEMS SHALL BE PERFORMED PRIOR TO THE START OF CONSTRUCTION TO ESTABLISH BASELINE PERFORMANCE. THIS INCLUDES READING CHW AND HW FLOWRATES AT ALL EXISTING FAN COIL UNITS, AIR HANDLING UNITS, OUTDOOR AIR UNIT OAU-1, HW/CHW PUMPS, HW HEAT EXCHANGER, AND CHILLER.
- PRE-READ TAB OF ALL EXISTING AIR SYSTEMS SHALL BE PERFORMED PRIOR TO START OF CONSTRUCTION TO ESTABLISH BASELINE PERFORMANCE. THIS INCLUDES READING OUTLET AND EQUIPMENT AIRFLOWS AT ALL EXISTING FAN COIL UNITS, AIR HANDLING UNITS, EXHAUST FANS, AND OUTDOOR AIR UNIT OAU-1.
- CONTRACTOR SHALL SUBMIT PRE-READ TAB REPORTS FOR ENGINEER APPROVAL PRIOR TO COMMENCING DEMOLITION.

FINAL TAB OF ALL HYDRONIC AND AIR SYSTEMS SHALL BE PERFORMED AT THE END OF CONSTRUCTION TO CONFIRM CENTRAL PLANT PERFORMANCE AND TO VERIFY BASELINE PERFORMANCE HAS BEEN RESTORED TO THE EXISTING SYSTEMS AND EQUIPMENT.

REFER TO SECTION 230593 "TESTING ADJUSTING AND BALANCING" FOR DETAILED REQUIREMENTS.

BUILDING STEAM SERVICE DISCONNECTION SCOPE

ALL EXISTING STEAM AND CONDENSATE SYSTEM EQUIPMENT, PIPING AND COMPONENTS IN THE ALLEN BUILDING WILL BE DEMOLISHED. BUILDING STEAM SERVICE PIPING AND AND STEAM TUNNEL BETWEEN THE CAMPUS BOILER PLANT AND ALLEN BUILDING WILL BE ABANDONED IN PLACE.

ALLEN BUILDING STEAM AND PUMPED CONDENSATE RETURN SERVICE PIPING IS ROUTED IN A BELOW-GROUND STEAM TUNNEL WITH CRAWL ACCESS FROM THE CAMPUS BOILER PLANT TO THE ALLEN BUILDING. THE BOILER PLANT IS LOCATED APPROXIMATELY 350 FEET WEST OF THE ALLEN BUILDING AT THE WEST END OF EAST MAIN STREET ACCESS ROAD. THE STEAM TUNNEL IS ROUTED BELOW THE ACCESS ROAD FROM THE BOILER PLANT TO THE ALLEN BUILDING SERVICE ENTRANCE LOCATED IN SAFETY STORAGE ROOM 001. EACH SERVICE LINE IS EQUIPPED WITH AN ISOLATION VALVE AT THE STEAM TUNNEL ENTRANCE IN THE BOILER HOUSE.


PRIOR TO DEMOLITION OF THE ALLEN BUILDING STEAM SYSTEMS, THE EXISTING HIGH PRESSURE STEAM AND PUMPED CONDENSATE RETURN SERVICE LINES SHALL BE DISCONNECTED FROM THE PLANT MAINS AT THEIR RESPECTIVE BRANCH ISOLATION VALVES AT THE BOILER PLANT SERVICE TUNNEL ENTRANCE. CONTRACTOR SHALL PERMANENTLY CAP EACH ISOLATION VALVE AFTER DISCONNECTING THE BUILDING SERVICE LINES.

CONTRACTOR IS ADVISED THAT ACCESS TO THE ISOLATION VALVES IN THE PLANT TUNNEL ENTRANCE IS LIMITED AND WORK SCOPE ASSOCIATED WITH DISCONNECTION AND CAPPING OF THE BUILDING BRANCH LINES REQUIRES CONFINED SPACE WORK. ALL PERSONNEL SHALL BE PROPERLY TRAINED FOR CONFINED SPACE WORK AND CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING A "CONFINED SPACE ENTRY PERMIT" FROM THE UNIVERSITY PRIOR TO COMMENCING THE WORK.


FOLLOWING SERVICE LINE ISOLATION AND CAPPING AT THE BOILER HOUSE, CONTRACTOR SHALL DISCONNECT AND CAP THE LINES IN THE STEAM TUNNEL BELOW THE EXTERIOR MANHOLE AT THE NORTH-WEST CORNER OF THE ALLEN BUILDING WHERE INDICATED ON DRAWING B/M1.12. ALL STEAM AND STEAM CONDENSATE PIPING FROM THE MANHOLE TO THE BUILDING AND WITHIN THE BUILDING SHALL THEN BE DEMOLISHED TO THE POINTS OF DISCONNECTION AS INDICATED ON THE DRAWINGS.



1 CRITICAL COMPONENTS IN MECHANICAL ROOM 002
Scale: N.T.S.



2 FIRST FLOOR CRITICAL SYSTEMS
Scale: 3/32" = 1'-0"



3 GROUND FLOOR CRITICAL SYSTEMS
Scale: 3/32" = 1'-0"

KEY NOTES

1. EXISTING BAS PANELS TO REMAIN. CONTRACTOR TO PROTECT PANEL AND MAINTAIN POWER AND CRITICAL DATA CONNECTIONS THROUGHOUT CONSTRUCTION.
2. EXISTING BAS UPS PANEL TO BE RELOCATED. CONTRACTOR TO PROTECT PANEL AND MAINTAIN POWER AND DATA CONNECTIONS THROUGHOUT CONSTRUCTION. EXTEND CONDUIT AND WIRING AND MOUNT UPS PANEL ON WALL BELOW EXISTING BAS PANEL. NOTED IN KEYNOTE #1 ON THIS SHEET. CONTRACTOR TO TEST UPS BATTERY AND REPLACE OR UPGRADE UPS AS REQUIRED TO MAINTAIN POWER TO BAS EQUIPMENT FOR A POWER LOSS DURATION OF 30 MINUTES OR GREATER.
3. EXISTING CAMPUS-WIDE ELECTRIC UTILITY DEMAND RESPONSE CONTROL PANEL TO REMAIN ("VOLTUS" IS THE CURRENT CAMPUS DEMAND RESPONSE VENDOR). CONTRACTOR TO PROTECT PANEL AND MAINTAIN POWER AND DATA CONNECTIONS THROUGHOUT CONSTRUCTION. FIELD-VERIFY DATA CABLE ROUTING PRIOR TO START OF CONSTRUCTION. REFER TO "CRITICAL SYSTEMS REQUIREMENTS" NOTES ON THIS SHEET FOR ADDITIONAL INFORMATION.
4. EXISTING SSI NETWORK INTERFACE PANEL TO CAMPUS SUPERVISORY SERVER. CONTRACTOR TO PROTECT PANEL AND MAINTAIN POWER AND DATA CONNECTIONS THROUGHOUT CONSTRUCTION. DISCONNECT POWER AND DEMOLISH FOLLOWING INSTALLATION AND FINAL COMMISSIONING OF NEW BUILDING AUTOMATION SYSTEM AND NETWORK INTERFACE TO CAMPUS SUPERVISORY SERVER. COORDINATE DEMOLITION WITH WORK SEQUENCE.
5. EXISTING EXTERIOR LIGHTING RELAY PANEL 'FC' TO REMAIN. CONTRACTOR TO PROTECT PANEL AND MAINTAIN POWER AND CONTROL CONNECTIONS THROUGHOUT CONSTRUCTION. COORDINATE RECONNECTION OF EXISTING CONTROL POINTS TO NEW BAS WITH CONSTRUCTION SEQUENCE. REFER TO M7.03.
6. THIS ROOM TO REMAIN FULLY OPERATIONAL AT ALL TIMES DURING CONSTRUCTION. REFER TO "CRITICAL SYSTEMS REQUIREMENTS" NOTES ON THIS SHEET FOR ADDITIONAL INFORMATION.
7. REFER TO PHOTOGRAPH 1 ON THIS SHEET FOR EXISTING CRITICAL COMPONENTS IN THIS CORNER OF MECHANICAL ROOM 002 THAT REQUIRE PROTECTION AND CONTINUOUS POWER AND DATA CONNECTIONS THROUGHOUT CONSTRUCTION.
8. EXISTING BAS PANEL.
9. NEW BAS PANEL.
10. APPROXIMATE ROUTING OF EXISTING ELECTRIC METER CONNECTION TO THE RADFORD CITY ELECTRIC SUBSTATION. CONTRACTOR TO VERIFY EXACT LOCATION WITH OWNER PRIOR TO STARTING DEMOLITION AND PROTECT ROUTING AND CONNECTIVITY THROUGHOUT CONSTRUCTION. REFER TO "CRITICAL SYSTEMS REQUIREMENTS" NOTES ON THIS SHEET FOR ADDITIONAL INFORMATION.
11. CAMPUS OA INTAKE EMERGENCY CLOSURE/RESET SWITCH. CONTRACTOR TO PROTECT SWITCH PRIOR TO STARTING DEMOLITION AND MAINTAIN SWITCH ACCESS, FUNCTIONALITY AND BAS INTERFACE THROUGHOUT CONSTRUCTION.
12. ALLEN BUILDING ELECTRIC METER IN EXISTING PANEL MDP.

WALL RATING LEGEND			
—1—1—	1-HR FIRE RATED WALL		
—2—2—	2-HR FIRE WALL		
—SB—SB—	SMOKE PARTITIONS		

STATE BUILDING OFFICIAL




Dewberry Engineers Inc.
9300 Harris Corners Parkway
Suite 220
Charlotte, NC 28269-3797
704.509.6918
NC License No. F-0929

DEB APPROVAL



SEAL



12/5/2025

KEY PLAN:

SCALE:

REVISIONS

NO.	DATE	BY	DESCRIPTION
2	12/05/25	SWD	DEB CMNTS/ADD 3
1	10/24/25	SWD	DEB COMMENTS

DRAWN BY SMF
APPROVED BY SWD
CHECKED BY JMT
DATE JULY 25, 2025

TITLE
MECHANICAL NOTES

DEI PROJECT NO: 50188025
RADFORD PROJECT NO: 217-B5217-004
SHEET NO.

M0.03




Dewberry Engineers Inc.
9300 Harris Corners Parkway
Suite 220
Charlotte, NC 28269-3797
704.500.9919
NC License No. F-0929

DEB APROVAL

Radford
UNIVERSITY
ALLEN BUILDING
ELECTRICAL
REPLACEMENT
100% CONSTRUCTION
DOCUMENTS
RADFORD, VIRGINIA

SEAL



KEY PLAN:

SCALE:

REVISIONS

NO.	DATE	BY	DESCRIPTION
2	12/05/25	SWD	DEB CMNTS/ADD 3
1	10/24/25	SWD	DEB COMMENTS


DRAWN BY _____ SMF
APPROVED BY _____ SWD
CHECKED BY _____ JMT
DATE _____ JULY 25, 2025

TITLE
**GROUND FLOOR
MECHANICAL
DEMOLITION
PLAN**

DEI PROJECT NO: 50188025
RADFORD PROJECT NO: 217-B5217-004

SHEET NO.

MD1.11



1 GROUND MECHANICAL DEMOLITION PLAN

Scale: 1/4" = 1'-0"



GENERAL NOTES:

- REFER TO M0.02 FOR GENERAL MECHANICAL DEMOLITION AND NEW WORK NOTES.

KEY NOTES

- EXISTING AIR HANDLING UNIT TO REMAIN.
- DEMOLISH STEAM UNIT HEATER / CONVECTOR / RADIATOR COMPLETE WITH ALL ASSOCIATED SUPPORTS AND ACCESSORIES. DISCONNECT POWER, AND DEMOLISH CONTROL WIRING AND CONDUIT BACK TO CONTROL PANEL.
- EXHAUST FAN TO REMAIN.
- BAS PANEL TO REMAIN.
- CONTRACTOR SHALL PRE-READ SUPPLY AIR OUTLET CFM PRIOR TO COMMENCING DEMOLITION. TYPICAL OF ALL EXISTING SUPPLY AIR SYSTEM OUTLETS IN THE BUILDING.
- CONTRACTOR SHALL PRE-READ RETURN AIR OUTLET CFM PRIOR TO COMMENCING DEMOLITION. TYPICAL OF ALL EXISTING RETURN AIR SYSTEM OUTLETS IN THE BUILDING.
- CONTRACTOR SHALL PRE-READ EXHAUST AIR OUTLET CFM PRIOR TO COMMENCING DEMOLITION. TYPICAL OF ALL EXISTING EXHAUST AIR SYSTEM OUTLETS IN THE BUILDING.
- CONTRACTOR SHALL PRE-READ AHU-1 HW AND CHW COIL PERFORMANCE AND GPM PRIOR TO COMMENCING DEMOLITION.
- EXISTING HUMIDIFIER TO REMAIN.
- EQUIPMENT LPC PIPING NOT SHOWN. CONTRACTOR TO FIELD-VERIFY EXACT ROUTING AND DEMOLISH FROM EQUIPMENT BACK TO CONDENSATE RECEIVER.
- DEMOLISH LPS PIPING FROM LOCATION INDICATED BACK TO HEATER(S) SHOWN.
- DEMOLISH LPS/LPC PIPING FROM LOCATION INDICATED BACK TO MECHANICAL ROOM 002 AS SHOWN.
- DEMOLISH LPC PIPING FROM LOCATION INDICATED AT ROOM WALL BACK TO HEATER SHOWN.
- EXISTING LPC MAIN DOWN BELOW GROUND CONTINUING TO CONDENSATE RECIEVER IN MECHANICAL 002.
- DEMOLISH LPS/LPC PIPING AS INDICATED. DISCONNECT LPS 2" BELOW FLOOR AND DEMOLISH BACK TO HEATER AS SHOWN. PATCH FLOOR AT POINT OF DISCONNECTION.
-

GENERAL NOTES:

1. REFER TO M0.02 FOR GENERAL MECHANICAL DEMOLITION AND NEW WORK NOTES.

KEY NOTES

1. CAMPUS OA INTAKE EMERGENCY CLOSURE/RESET SWITCH TO REMAIN FUNCTIONAL WITH BAS INTERFACE AT ALL TIMES. REFER TO CONTROLS. COORDINATE WITH OWNER.
2. REFER TO ROOF PLAN FOR EA DUCT CONNECTION TO FAN. BAS PANEL TO REMAIN.
3. DEMOLISH SECTION OF SA DUCT IN PREPARATION FOR INSTALLATION OF ELECTRIC HEAT COIL.
4. DISCONNECT LPS AND LPC PIPING FROM UNIT AND DEMOLISH PIPING BACK TO POINT OF DISCONNECTION INDICATED. PREPARE FOR CAPPING.
5. CONTRACTOR SHALL PRE-READ OAU-1 CHW COIL PERFORMANCE AND GPM PRIOR TO COMMENCING DEMOLITION.
6. CONTRACTOR SHALL PRE-READ FAN COIL UNIT HW AND CHW COIL PERFORMANCE AND GPM PRIOR TO COMMENCING DEMOLITION. TYPICAL AT ALL FAN COIL UNITS IN THE BUILDING.
7. CAREFULLY REMOVE DISCHARGE AIR TEMPERATURE SENSOR, PATCH DUCT, AND PREPARE SENSOR FOR RELOCATION SHOWN ON NEW WORK PLAN.




Dewberry Engineers Inc.
9300 Harris Corners Parkway
Suite 220
Charlotte, NC 28269-3797
704.500.5915
NC License No. F-0929

DEB APPROVAL



SEAL



12/5/2025

KEY PLAN:

SCALE:

REVISIONS

NO.	DATE	BY	DESCRIPTION
2	12/05/25	SWD	DEB CMNTS/ADD 3
1	10/24/25	SWD	DEB COMMENTS


DRAWN BY _____ SMF
APPROVED BY _____ SWD
CHECKED BY _____ JMT
DATE _____ JULY 25, 2025

TITLE
FIRST FLOOR
MECHANICAL
DEMOLITION
PLAN


DEI PROJECT NO: 50188025
RADFORD PROJECT NO: 217-B5217-004

SHEET NO.

MD1.21



1 FIRST FLOOR MECHANICAL DEMOLITION PLAN
Scale: 1/4" = 1'-0"



GENERAL NOTES:

1. REFER TO M0.02 FOR GENERAL MECHANICAL DEMOLITION AND NEW WORK NOTES.




Dewberry Engineers Inc.
9300 Harris Corners Parkway
Suite 220
Charlotte, NC 28269-3797
704.500.5815
NC License No. F-0929

DEB APPROVAL



SEAL



12/5/2025

KEY PLAN:

SCALE:

REVISIONS

NO.	DATE	BY	DESCRIPTION
2	12/05/25	SWD	DEB CMNTS/ADD 3
1	10/24/25	SWD	DEB COMMENTS

DRAWN BY _____ SMF
APPROVED BY _____ SWD
CHECKED BY _____ JMT
DATE _____ JULY 25, 2025

TITLE

ROOF
MECHANICAL
DEMOLITION
PLAN

DEI PROJECT NO: 50188025
RADFORD PROJECT NO: 217-B5217-004
SHEET NO.

MD1.31

WALL RATING LEGEND

- 1—1— 1-HR FIRE RATED WALL
—2—2— 2-HR FIRE WALL
—SB—SB— SMOKE PARTITIONS

1

ROOF MECHANICAL DEMOLITION PLAN

Scale: 1/4" = 1'-0"



E

D

C

B

A

OUTLINE OF LOW ROOF

OUTLINE OF HIGH ROOF

EF-3(E)

1

LPS

EF-4(E)

ANTENNA 2

(E) 10" TALL DAVIT

(E) VENT

(E) RD

(E) VENT

(E) RD




Dewberry Engineers Inc.
9300 Harris Corners Parkway
Suite 220
Charlotte, NC 28269-3797
704.500.8915
NC License No. F-0929

DEB APROVAL

Radford
UNIVERSITY
ALLEN BUILDING
ELECTRICAL
REPLACEMENT
100% CONSTRUCTION
DOCUMENTS
RADFORD, VIRGINIA

SEAL



12/5/2025

KEY PLAN:

SCALE:

REVISIONS

NO.	DATE	BY	DESCRIPTION
2	12/05/25	SWD	DEB CMNTS/ADD 3
1	10/24/25	SWD	DEB COMMENTS

DRAWN BY _____ SMF
APPROVED BY _____ SWD
CHECKED BY _____ JMT
DATE _____ JULY 25, 2025

TITLE
**GROUND FLOOR
MECHANICAL
PLAN**

DEI PROJECT NO: 50188025
RADFORD PROJECT NO: 217-B5217-004
SHEET NO.

M1.11

WALL RATING LEGEND

—1—1— 1-HR FIRE RATED WALL
—2—2— 2-HR FIRE WALL
—SB—SB— SMOKE PARTITIONS


GENERAL NOTES:

- REFER TO M0.02 FOR GENERAL MECHANICAL DEMOLITION AND NEW WORK NOTES.
- REFER TO UNIT HEATER SCHEDULE FOR HOT WATER BRANCH PIPE SIZING.
- REFER TO DETAILS FOR PROPANE PIPE SIZING AND ISOMETRIC VIEW.

KEY NOTES

- INSTALL ELECTRIC UNIT HEATER IN SAME LOCATION AS FORMER STEAM UNIT HEATER.
- HANG ELECTRIC UNIT HEATER ABOVE STAIR LANDING.
- EXISTING CHWS/R AND HWS/R BRANCH PIPING UP TO FIRST FLOOR. (TYPICAL)
- EXISTING CHWS/R AND HWS/R MAINS UP TO FIRST FLOOR FAN COILS.
- CONTRACTOR SHALL BALANCE SUPPLY AIR OUTLET CFM TO THE AIRFLOW MEASURED DURING PRE-READ TAB. TYPICAL OF ALL EXISTING SUPPLY AIR SYSTEM OUTLETS IN THE BUILDING.
- CONTRACTOR SHALL BALANCE RETURN AIR OUTLET CFM TO THE AIRFLOW MEASURED DURING PRE-READ TAB. TYPICAL OF ALL EXISTING RETURN AIR SYSTEM OUTLETS IN THE BUILDING.
- CONTRACTOR SHALL BALANCE EXHAUST AIR OUTLET CFM TO THE AIRFLOW MEASURED DURING PRE-READ TAB. TYPICAL OF ALL EXISTING EXHAUST AIR SYSTEM OUTLETS IN THE BUILDING.
- CONTRACTOR SHALL BALANCE AHU-1 HW AND CHW COIL FLOWRATES TO GPM MEASURED DURING PRE-READ TAB.
- CAP LPS.
- CAP LPC.
- LPC THROUGH WALL TO BELOW GROUND UNDER STAIR, CONTINUING TO CONDENSATE RECEIVER IN MECH 002. ABANDON BELOW GROUND PIPING AND INSTALL CAP AT WALL.

1 GROUND MECHANICAL PLAN
Scale: 1/4" = 1'-0"



GENERAL NOTES:

- REFER TO M0.02 FOR GENERAL MECHANICAL DEMOLITION AND NEW WORK NOTES, AND SEQUENCE OF CONSTRUCTION REQUIREMENTS.
- REFER TO DETAILS FOR PROPANE PIPE SIZING AND ISOMETRIC VIEW.

KEY NOTES

- DEMOLISH CHILLER COMPLETE WITH ALL ASSOCIATED PIPING AND ACCESSORIES. DISCONNECT POWER, AND DEMOLISH CONTROL WIRING AND CONDUIT BACK TO CONTROL PANEL. PREPARE CONCRETE PAD FOR EXPANSION AS SHOWN ON NEW WORK PLAN ON THIS DRAWING.
- EXISTING CONDENSING UNIT TO REMAIN.
- DEMOLISH HW AND CHW PUMPS. DISCONNECT ALL ASSOCIATED PIPING AND ACCESSORIES. DISCONNECT POWER, AND DEMOLISH CONTROL WIRING AND CONDUIT BACK TO CONTROL PANEL.
- DEMOLISH HEAT EXCHANGER. DISCONNECT ALL ASSOCIATED PIPING AND ACCESSORIES. DISCONNECT POWER, AND DEMOLISH CONTROL WIRING AND CONDUIT BACK TO CONTROL PANEL.
- DEMOLISH CHEMICAL POT FEEDER COMPLETE WITH ALL PIPING AND SUPPORTS.
- 2" HWS/R AND 3" CHWS/R VALVED AND CAPPED PIPING STUBS. LOCATE WHERE SHOWN FOR FUTURE CONNECTION.
- DEMOLISH EXPANSION TANK COMPLETE WITH ALL ASSOCIATED PIPING SUPPORTS AND ACCESSORIES.
- DEMOLISH CONDENSATE PUMP COMPLETE WITH ALL ASSOCIATED PIPING AND ACCESSORIES. DISCONNECT POWER AND DEMOLISH CONTROL WIRING AND CONDUIT BACK TO CONTROL PANEL.
- DEMOLISH STEAM UNIT HEATER / CONVECTOR / RADIATOR COMPLETE WITH ALL ASSOCIATED PIPING, SUPPORTS AND ACCESSORIES. DISCONNECT POWER, AND DEMOLISH CONTROL WIRING AND CONDUIT BACK TO CONTROL PANEL.
- CHWS/R AND HWS/R PIPING UP TO FLOOR ABOVE TO REMAIN.
- CONNECT TO EXISTING LOUVER. FIELD VERIFY EXACT SIZE (APPROXIMATELY 20X20). PROVIDE MOTORIZED ISOLATION DAMPER IN INTAKE DUCT AND INTERLOCK WITH EF-1 OPERATION. REFER TO CONTROLS.
- PROVIDE 14X14 OPENING IN WALL. LOCATE EDGE OF OPENING 16-INCHES FROM DOOR AS INDICATED. LOCATE TOP OF OPENING 2-INCHES BELOW BOTTOM OF 1ST FLR SLAB. COORDINATE EXACT DUCT ROUTING WITH EXISTING CONDUIT IN ROOM.
- 3/4" PROPANE GAS BUILDING SERVICE LINE DN BELOW GRADE WITH BUILDING ISOLATION VALVE. REFER TO MECHANICAL DETAILS AND CIVIL DRAWINGS FOR CONTINUATION.
- INSTALL EMERGENCY SHUTOFF VALVE IN PROPANE GAS SUPPLY MAIN AND WIRE TO EPO SWITCH IN BOILER ROOM. REFER TO CONTROL DRAWINGS.
- INSTALL EMERGENCY SHUT OFF SWITCH HARD-WIRED TO FUEL SHUT OFF VALVE AND BOILER, B-1 AND B-2 SHUTDOWN. REFER TO CONTROL DRAWINGS.
- CLEAN ALL BELOW GROUND MECHANICAL ROOM DRAIN PIPING FROM FLOOR DRAINS TO BUILDING SERVICE MAIN WITH WATER JET AND AUGER AS REQUIRED TO RESTORE FLOW.
- APPROXIMATE LOCATION OF EXISTING BUILDING DOMESTIC WATER METER. RECONNECT TO NEW BAS. REFER TO CONTROL DRAWINGS.
- 2" HPS & 2" HPC BUILDING STEAM SERVICE PIPING IN STEAM TUNNEL BELOW GROUND. DISCONNECT AND CAP SERVICE LINES AT POINT INDICATED BELOW EXTERIOR MANHOLE. ABANDON SERVICE PIPING IN TUNNEL. DEMOLISH ALL STEAM AND STEAM CONDENSATE PIPING FROM THE MANHOLE TO THE BUILDING AND WITHIN THE BUILDING TO THE POINTS OF DISCONNECTION AS INDICATED. REFER TO "BUILDING STEAM SERVICE DISCONNECTION SCOPE" ON DRAWING M0.03 FOR ADDITIONAL INFORMATION.
- EXTEND CHILLER PAD AS SHOWN. REFER TO STRUCTURAL AND CIVIL DRAWINGS.
- SECOND STAGE BUILDING PRESSURE REGULATOR. PIPE RELIEF TO SAFE LOCATION AT BUILDING EXTERIOR. REFER TO MECHANICAL DETAILS.
- DEMOLISH EXHAUST FAN WITH DUCTWORK AND SUPPORTS. DISCONNECT POWER, AND DEMOLISH CONTROL WIRING AND CONDUIT BACK TO CONTROL PANEL. PREPARE WALL OPENING FOR NEW FAN.
- PROVIDE CARBON MONOXIDE DETECTOR WITH AUDIBLE/VISUAL ALARM. REFER TO CONTROLS DRAWINGS.
- CAREFULLY REMOVE BUILDING STEAM SERVICE FLOW METER AND PRV AND RETURN TO OWNER FOR REUSE.
- DEMOLISH CONDENSATE BASIN ACCESSORIES, INFILL HOLE, AND PATCH SLAB. REFER TO STRUCTURAL.
- DEMOLISH EXISTING PUMP MOTOR STARTERS.
- EXISTING BAS PANEL TO REMAIN. REFER TO M0.02 FOR ADDITIONAL INFORMATION.
- PROVIDE PIPE SUPPORT STAND. REFER TO STRUCTURAL DETAIL ON S5.01.
- 4" DIAMETER COMBUSTION INTAKE.
- 4" DIAMETER STAINLESS STEEL VENT.
- TERMINATE COMBUSTION AIR INTAKE AND STAINLESS STEEL VENT WITH CONCENTRIC VENT TERMINAL IN ACCORDANCE WITH BOILER MANUFACTURER'S INSTRUCTIONS. DO NOT TERMINATE VENT VERTICALLY ABOVE ELECTRICAL EQUIPMENT. COORDINATE EXACT LOCATION WITH DIV 26 CONTRACTOR.
- RPZ TO REMAIN. DISCONNECT MAKEUP WATER PIPING FROM RPZ OUTLET & DEMOLISH BACK TO HW & CHW SYSTEMS INCLUDING PRVS.
- CONNECT 3/4" MU TO RPZ OUTLET AND EXTEND TO HW AND CHW SYSTEMS AS SHOWN. PROVIDE SEPARATE PRV FOR EACH SYSTEM. REFER TO AIR SEPARATOR/EXPANSION TANK DETAIL FOR MU PIPING REQUIREMENTS.
- EXISTING EXTERIOR LIGHTING RELAY PANEL 'FC' TO REMAIN. CONTRACTOR TO PROTECT PANEL AND MAINTAIN POWER AND CONTROL CONNECTIONS THROUGHOUT CONSTRUCTION. COORDINATE RECONNECTION OF EXISTING CONTROL POINTS TO NEW BAS WITH CONSTRUCTION SEQUENCE. REFER TO 1/M0.03 AND M7.01.
- CONNECT 3" CHWS/R TO EXISTING 2-1/2" CHWS/R. PATCH INSULATION AND JACKET.
- CONNECT 2" HWS/R TO EXISTING 2" HWS/R. PATCH INSULATION AND JACKET.
- PROVIDE UNISTRUT SUPPORT RACK. REFER TO DETAIL 1/M5.05.
- DISCONNECT DCW & DHW AT WATER HEATER AND PREPARE WH FOR RELOCATION.
- RELOCATE ELECTRIC WATER HEATER TO NEW LOCATION SHOWN ON EXISTING SUPPORTS AND RECONNECT TO DCW AND DHW SERVICE LINES. INSULATE NEW PIPING FROM WH TO POINTS OF CONNECTION. COORDINATE BRANCH CIRCUIT WIRE/CONDUIT EXTENSION REQUIREMENTS WITH ELECTRICAL CONTRACTOR.
- CAP LPS.

WALL RATING LEGEND			
—1—1—	1-HR FIRE RATED WALL		
—2—2—	2-HR FIRE WALL		
—SB—SB—	SMOKE PARTITIONS		




Dewberry Engineers Inc.
9300 Harris Corners Parkway
Suite 220
Charlotte, NC 28269-3797
704.500.8915
NC License No. F-0929

DEB APPROVAL



SEAL



12/5/2025

KEY PLAN:

SCALE:

REVISIONS

NO.	DATE	BY	DESCRIPTION
2	12/05/25	SWD	DEB CMNTS/ADD 3
1	10/24/25	SWD	DEB COMMENTS

DRAWN BY _____ SMF
APPROVED BY _____ SWD
CHECKED BY _____ JMT
DATE _____ JULY 25, 2025

TITLE
GROUND FLOOR
MECHANICAL
PLAN

DEI PROJECT NO: 50188025
RADFORD PROJECT NO: 217-B5217-004


SHEET NO.

M1.12


GROUND FLOOR MECHANICAL DEMOLITION PLAN
AT CHILLER / BOILER AREA



Scale: 1/4" = 1'-0"



GROUND FLOOR MECHANICAL PLAN
AT CHILLER / BOILER AREA



Scale: 1/4" = 1'-0"



GENERAL NOTES:

1. REFER TO M0.02 FOR GENERAL MECHANICAL DEMOLITION AND NEW WORK NOTES.




Dewberry Engineers Inc.
9300 Harris Corners Parkway
Suite 220
Charlotte, NC 28269-3797
704.509.5815
NC License No. F-0929

DEB APPROVAL



SEAL



KEY PLAN:

SCALE:

REVISIONS

NO.	DATE	BY	DESCRIPTION
2	12/05/25	SWD	DEB CMNTS/ADD 3
1	10/24/25	SWD	DEB COMMENTS

DRAWN BY _____ SMF
APPROVED BY _____ SWD
CHECKED BY _____ JMT
DATE _____ JULY 25, 2025

TITLE

ROOF MECHANICAL PLAN

DEI PROJECT NO: 50188025
RADFORD PROJECT NO: 217-B5217-004
SHEET NO.


M1.31

WALL RATING LEGEND	
—1—1—	1-HR FIRE RATED WALL
—2—2—	2-HR FIRE WALL
—SB—SB—	SMOKE PARTITIONS

1

ROOF MECHANICAL PLAN

Scale: 1/4" = 1'-0"



E

D

C

B

A

OUTLINE OF LOW ROOF

OUTLINE OF HIGH ROOF

EF-3(E)

(E) ELEVATOR
OVERRUN TO
REMAIN

(E) VENT

(E) RD

EF-4(E)

(E) 10" TALL DAVIT

(E) VENT

(E) RD

KEY NOTES

1. REFER TO M1.21 FOR EA DUCT CONTINUATION.
2. EXISTING COMMUNICATION ANTENNA.
3. CAP LPS ABOVE ROOF.

E

D

C

B

A

NOTES:


1. CHANNEL CONNECTIONS, NUTS, AND HARDWARE SHALL BE MADE BY CHANNEL MANUFACTURER.

DISCONNECT ENCLOSURE, REFER TO SECTION 230511 AND DIV 26 FOR REQUIREMENTS AND NEMA TYPE.

TYPICAL VERTICAL SUPPORT
MINIMUM OF TWO PER RACK
1-5/8" X 3-1/4" STAINLESS
STEEL CHANNEL

TYPICAL HORIZONTAL SUPPORT,
MINIMUM OF TWO PER RACK SPACED
AS REQUIRED BY EQUIPMENT
MOUNTING HOLES 1-5/8" SQ. SLOTTED
STAINLESS STEEL CHANNEL

CONCRETE BASE (TYP)
PROVIDE WITH 1"
CHAMFERED EDGE
3000 PSI AT 28 DAYS



1 CHILLER DISCONNECT SUPPORT RACK
Scale: N.T.S.




Dewberry Engineers Inc.
9300 Harris Corners Parkway
Suite 220
Charlotte, NC 28269-3797
704.500.5815
NC License No. F-0929

DEB APPROVAL



SEAL



12/5/2025

KEY PLAN:

SCALE:

REVISIONS

NO.	DATE	BY	DESCRIPTION
2	12/05/25	SWD	DEB CMNTS/ADD 3
1	10/24/25	SWD	DEB COMMENTS

DRAWN BY _____ SMF
APPROVED BY _____ SWD
CHECKED BY _____ JMT
DATE _____ JULY 25, 2025

TITLE
DETAILS

DEI PROJECT NO: 50188025
RADFORD PROJECT NO: 217-B5217-004
SHEET NO.

M5.05

CONTROLS LEGEND

- AI

=

ANALOG INPUT
- AO

=

ANALOG OUTPUT
- DI

=

DIGITAL INPUT
- DO

=

DIGITAL OUTPUT
- N

=

NETWORK CONNECTION
- AC

=

ACTUATOR CONTROL
- AF

=

AIR FLOW SWITCH
- CO

=

CARBON MONOXIDE SENSOR
- CO2

=

CARBON DIOXIDE SENSOR
- CS

=

CURRENT SENSING RELAY
- DP

=

DIFFERENTIAL PRESSURE SENSOR
- EM

=

ENERGY METER
- FM

=

FLOW METER
- FS

=

FLOAT SWITCH OR FLOW SWITCH
- HL

=

HUMIDITY HIGH LIMIT SWITCH
- HS

=

HUMIDITY SENSOR
- OS

=

OCCUPANCY SENSOR
- PS

=

PRESSURE SENSOR
- R

=

RELAY
- ES

=

END SWITCH
- SD

=

DUCT SMOKE DETECTOR
- SCR

=

SILICON CONTROLLED RECTIFIER
- STR

=

STARTER
- TS

=

TEMPERATURE SENSOR
- VF

=

VARIABLE FLOW VALVE OR DAMPER
- VS

=

VELOCITY SENSOR
- VFD

=

VARIABLE SPEED DRIVE
- S

=

OVERRIDE SWITCH
- FA

=

FIRE ALARM CONTACT
- FO

=

FAIL OPEN
- FC

=

FAIL CLOSED
- =

THREE WAY CONTROL VALVE
- =

TWO WAY CONTROL VALVE
- M

=

MOTOR
- AFMS

=

AIR FLOW MONITORING STATION
- =

DAMPER
- =

COOLING OR HEATING COIL
- =

FREEZE STAT
- =

FILTER
- =

FAN
- =

FAN
- =

PUMP

CONTROLS SCOPE:

1. GENERAL PROJECT DESCRIPTION:
- A. THIS PROJECT CONSISTS OF A FULL REPLACEMENT OF THE ALLEN BUILDING CENTRAL HEATING AND COOLING PLANT LOCATED IN AND DIRECTLY OUTSIDE OF MECHANICAL ROOM 002 LOCATED ON THE GROUND FLOOR OF THE BUILDING. EXISTING HOT WATER AND CHILLED WATER PIPING MAINS FROM THE PLANT WILL BE DISCONNECTED FROM BUILDING DISTRIBUTION MAINS AT MECHANICAL ROOM 002 WALL. HEATING AND COOLING SYSTEM EQUIPMENT AND PIPING WITHIN MECHANICAL ROOM 002 WILL BE FULLY DEMOLISHED, INCLUDING STEAM TO HOT WATER EXCHANGER, DUPLEX STEAM CONDENSATE PUMP, CHILLED AND HOT WATER PUMPS, ASSOCIATED PIPING ACCESSORIES, AND AIR-COOLED CHILLER LOCATED OUTSIDE.

B. EXISTING STEAM AND STEAM CONDENSATE SYSTEMS WILL BE DEMOLISHED THROUGHOUT THE ENTIRE BUILDING, COMPLETE WITH ASSOCIATED EQUIPMENT, PIPING AND ACCESSORIES.

C. ALL EXISTING HVAC SYSTEMS IN THE BUILDING THAT ARE LOCATED OUTSIDE OF MECHANICAL ROOM 002 WILL REMAIN FOR CONTINUED SERVICE WITH THE EXCEPTION OF THE EXISTING STEAM SYSTEMS AND ITEMS SPECIFICALLY NOTED ON THE DEMOLITION DRAWINGS.

D. NEW CHILLED WATER AND HEATING HOT WATER EQUIPMENT AND RELATED COMPONENTS WILL BE INSTALLED IN AND DIRECTLY OUTSIDE OF MECHANICAL ROOM 002. THE NEW CHW PLANT WILL CONSIST OF ONE AIR-COOLED CHILLER, TWO CHILLED WATER PUMPS, PIPING, ACCESSORIES, AND CONTROLS. THE NEW HW PLANT WILL CONSIST OF TWO GAS-FIRED BOILERS, PROPANE STORAGE SYSTEM WITH FUEL SUPPLY PIPING, TWO PRIMARY AND TWO SECONDARY PUMPS, PIPING, HYDRONIC ACCESSORIES, THREE HW UNIT HEATERS, AND HEATING SYSTEM CONTROLS. SUPPLY AND RETURN PIPING FROM THE NEW HOT AND CHILLED WATER SYSTEMS WILL BE CONNECTED TO THE EXISTING BUILDING CHILLED AND HOT WATER DISTRIBUTION MAINS IN THE CORRIDOR DIRECTLY OUTSIDE MECHANICAL ROOM 002.

E. STEAM SYSTEM HEATING EQUIPMENT THAT WAS DEMOLISHED WILL BE REPLACED WITH TEMPORARY ELECTRIC HEATERS. THIS INCLUDES FIVE UNIT HEATERS AND ONE HEATING COIL LOCATED IN EXISTING OUTDOOR AIR UNIT, OAU-1. ELECTRIC HEATERS WILL BE REPLACED BY OTHERS AS PART OF THE FUTURE, PHASE 2 BUILDING RENOVATION PROJECT.
2. EXISTING BUILDING CONTROLS CONSIST OF OLDER GENERATION JCI METASYS COMPONENTS. FIELD LEVEL CONTROLLERS ARE LOCATED THROUGHOUT THE BUILDING, INCLUDING THE FOLLOWING:
- MECHANICAL ROOM 002 (METASYS DX-9100; SERVES CENTRAL PLANT)
P.D. STORAGE 006 (METASYS DX-9100; SERVES EXISTING AHU-1), AND
MECH RM 108 (METASYS FEC-2611; SERVES EXISTING OAU-1).

EXISTING FIELD CONTROLLERS ARE INTEGRATED WITH THE CENTRAL CAMPUS JCI SYSTEM VIA A SUPERVISORY CONTROLLER (METASYS SNE10501) LOCATED IN MECHANICAL ROOM 002.
3. CONTROLS SERVING EXISTING-TO-REMAIN EQUIPMENT AND SYSTEMS SHALL REMAIN IN SERVICE. REFER TO M0.03 FOR CRITICAL SYSTEMS AND COMPONENTS REQUIRING CONTINUOUS OPERATION AT ALL TIMES.
4. A NEW BAS SYSTEM COMPLYING WITH SECTION 239000 REQUIREMENTS SHALL BE PROVIDED TO SERVE THE NEW CENTRAL PLANT SYSTEMS AND EQUIPMENT. THE NEW SYSTEM SHALL INCLUDE A NEW SUPERVISORY LEVEL NETWORK CONTROLLER TO REPLACE THE EXISTING SNE10501 CONTROLLER. ALL EXISTING BUILDING CONTROLS, INCLUDING FIELD CONTROLLERS, DEVICES, AND SENSORS SHALL BE RECONNECTED AND FULLY INTEGRATED WITH THE EXISTING CAMPUS NETWORK. THE BAS SHALL INCLUDE ALL REQUIRED SENSORS, DEVICES, FIELD CONTROLLERS AND PANELS, NETWORK CONTROLLERS AND SERVERS, INTEGRATION WITH ALL EXISTING BUILDING SENSORS, DEVICES, AND FIELD CONTROLLERS, INTEGRATION WITH THE CAMPUS FRONT END OPERATOR INTERFACE, SOFTWARE AND ANY OTHER HARDWARE OR SOFTWARE COMPONENTS FOR A FULLY FUNCTIONING BAS SYSTEM.
5. ALL COMMISSIONING AND FUNCTIONAL TESTING WITH THE UNIVERSITY COMMISSIONING TEAM SHALL BE INCLUDED IN THIS CONTRACT AND CONSIST OF ALL PROCEDURES OUTLINED IN THE COMMISSIONING PROCEDURES.

BAS CONTROL SYSTEM GENERAL NOTES

DESCRIPTION: OPEN ARCHITECTURE SYSTEM SHALL VIEW, MONITOR AND CONTROL BACNET PROTOCOL DEVICES OVER ETHERNET OR IP. REFER TO SECTION 239000 SPECIFICATIONS FOR DETAILED INFORMATION.

SET POINTS: ALL SET POINTS AND NUMERIC VALUES SHALL BE ADJUSTABLE.

TIME DELAYS: TIME DELAYS NOTED IN THE SEQUENCES OF OPERATION ARE INTENDED TO ALLOW FOR OTHER DEVICES TO ACT IN ADVANCE. FOR EXAMPLE, A FAN NOTED TO START ON A TIME DELAY IS WAITING FOR AN ASSOCIATED DAMPER TO OPEN. TIME DELAY DURATIONS SHALL BE DETERMINED WITH THE ENGINEER ONCE THE ACTUATORS HAVE BEEN SELECTED.

VARIABLE SPEED DRIVE OPERATION: WHEN A FAN OR PUMP IS STARTED, THE VARIABLE FREQUENCY DRIVE SHALL START AT MINIMUM SPEED AND SLOWLY INCREASE UNTIL REACHING THE REQUIRED SPEED TO SATISFY THE REFERENCE SIGNAL. STARTING AT FULL SPEED AND SLOWING TO MEET SET POINT IS NOT ACCEPTABLE.

EQUIPMENT WITH PACKAGED CONTROLS: HVAC EQUIPMENT THAT COMES EQUIPPED WITH FACTORY-INSTALLED PACKAGED CONTROLS SHALL COME WITH BACNET INTERFACE CARDS THAT ALLOW FULL VISIBILITY OF INTERNAL CONTROL AND MONITORING POINTS. THIS REQUIREMENT SHALL INCLUDE CHILLERS AND BOILERS. ELECTRICAL OR INDUSTRIAL EQUIPMENT THAT IS NOT AVAILABLE WITH A DIRECT BACNET INTERFACE SHALL BE MODBUS.

REGAIN POWER CONTROL: ENABLE CHILLER AND BOILER AUTOMATIC RESTART 5 MINUTES (ADJ.) AFTER RESUMPTION OF POWER FROM AN OUTAGE. AUTOMATICALLY RESTART ALL OTHER EQUIPMENT BASED ON THE OCCUPANCY SCHEDULE.

POWER SUPPLY: POWER TO THE BAS SYSTEM SHALL BE MAINTAINED BY UPS FOR A POWER LOSS DURATION OF UP TO 30 MINUTES.

SCHEDULING FUNCTIONS: PROVIDE A REAL TIME CLOCK AND SCHEDULE CONTROLLER WITH SUFFICIENT SCHEDULING CAPABILITY TO SCHEDULE ALL REQUIRED CONTROLLERS AND SEQUENCES. SET UP INITIAL OCCUPANCY AND SYSTEM CONTROL SCHEDULES IN COORDINATION WITH THE OWNER.

OCCUPANCY SCHEDULE: EACH TEMPERATURE CONTROL ZONE SHALL REFERENCE A USER-DEFINED AND USER-ADJUSTABLE SCHEDULE. MINIMUM OF 10 SCHEDULES SHALL BE AVAILABLE FOR CURRENT AND FUTURE USE. UNLESS OTHERWISE DIRECTED BY THE OWNER / ENGINEER, USE THE FOLLOWING PRELIMINARY SCHEDULE:

OCCUPIED:
MON. – SUN. 12:00 AM – 12:00 AM

SPACE SENSORS: ALL SPACE SENSORS SHALL BE COMBINATION TEMPERATURE / HUMIDITY SENSORS. ALL SPACE SENSORS SHALL BE EQUIPPED WITH SETPOINT ADJUSTMENT AND OVERRIDE PUSH BUTTON (ASSOCIATED SYSTEM SHALL OPERATE FOR 90 MINUTE PERIOD (ADJ.)). REFER TO PLANS FOR LOCATIONS OF STAINLESS STEEL FLAT PLATE SENSORS AND FLAT PLATE SENSORS WITH OVERRIDE.

MISCELLANEOUS CONTROL POINTS

OA TEMPERATURE, HUMIDITY & CARBON DIOXIDE: PROVIDE BUILDING OUTDOOR AMBIENT REFERENCE SENSORS FOR TEMPERATURE, HUMIDITY AND CARBON DIOXIDE TO BE USED BY ALL HVAC BUILDING CONTROLLERS TO DETERMINE OUTSIDE AIR TEMPERATURE, HUMIDITY AND CARBON DIOXIDE LEVEL. COORDINATE SENSOR LOCATION WITH OWNER.

LIGHTING CONTROLS: RECONNECT ANY EXISTING LIGHTING CONTROL ZONES AND RELAYS. REFER TO 1/M0.03 FOR REQUIREMENTS FOR EXTERIOR LIGHTING RELAY PANEL 'EC'. CONFIRM DETAILED REQUIREMENTS WITH OWNER.

FIRE ALARM SYSTEM: BAS SHALL SEND THE APPROPRIATE HVAC SHUTDOWN SIGNALS IN THE EVENT THE FIRE ALARM PANEL IS IN ALARM.

PROPANE STORAGE TANK FILL LEVEL: PROVIDE PROPANE STORAGE TANK LEVEL SENSOR AT A MINIMUM OF ONE PROPANE TANK. COORDINATE INSTALLTION WITH OWNERS TANK SUPPLIER. MONITOR FILL LEVEL ON 15 MIN. (ADJ.) INTERVALS AND ALARM BAS WHEN WHEN TANK LEVEL FALLS BELOW 25%. REFER TO CIVIL DRAWINGS FOR TANK FARM LOCATION.

EXISTING DOMESTIC WATER METER: RECONNECT EXISTING DOMESTIC WATER METER IN MECHANICAL ROOM 002 TO THE BAS. REFER TO B/M1.12 FOR APPROXIMATE METER LOCATION.

EXISTING ELECTRIC METER DEMAND & CONSUMPTION: CONNECTIONS TO THE EXISTING ELECTRIC METER MUST BE MAINTAINED DURING CONSTRUCTION AND TRANSFERRED TO THE NEW BAS PRIOR TO PROJECT COMPLETION. THIS INCLUDES MONITORING AND CONTROL CONNECTIONS TO RADFORD CITY ELECTRIC SUBSTATION AS REQUIRED FOR THE ENERGY SAVINGS/DEMAND LIMITING CONTROLS ON CAMPUS. THE EXISTING CONNECTION TO THE DEMAND RESPONSE VENDOR (VOLTUS ENERGY) MUST ALSO BE MAINTAINED. THIS IS USED TO PROVIDE RADFORD UNIVERSITY DATA FOR DEMAND RESPONSE PARTICIPATION IN THE VIRGINIA ENERGY DEPARTMENT PROGRAM. FIELD VERIFY CONNECTION REQUIREMENTS SHOWN WITH OWNER. REFER TO CRITICAL SYSTEM NOTES AND PHOTOGRAPH ON DRAWING M0.03 FOR ADDITIONAL INFORMATION.

HEAT TRACE CONTROLS: BAS SHALL ALARM ON HEAT TRACE SYSTEM FAULT OR WHEN SYSTEM POWER IS TURNED OFF AND OUTSIDE AIR TEMPERATURE FALLS BELOW 45 DEF. F. HEAT TRACE OPERATION SHALL BE LOCKED OUT WHEN OUTDOOR AIR TEMPERATURE RISES ABOVE 40°F. REFER TO MECHANICAL DETAILS AND HEAT TRACING SPECIFICATION 230533.

CAMPUS OA INTAKE EMERGENCY CLOSURE/RESET SWITCH: BAS INTERFACE AND FUNCTIONALITY OF THE EMERGENCY OUTDOOR AIR INTAKE SHUTDOWN SWITCH LOCATED IN EMERGENCY COMMUNICATIONS 132 SHALL BE MAINTAINED DURING CONSTRUCTION AND TRANSFERRED TO THE NEW BAS PRIOR TO PROJECT COMPLETION. FIELD VERIFY CONNECTION REQUIREMENTS SHOWN WITH OWNER. REFER TO CRITICAL SYSTEMS REQUIREMENTS ON M0.03 FOR ADDITIONAL INFORMATION.

TREND LOGS: PROVIDE TREND LOGS FOR BOILER OPERATION, CHILLER OPERATION, PUMP OPERATION, AIR HANDLING UNIT OPERATION AND ENERGY RECOVERY UNIT OPERATION AT OWNER'S DISCRETION. COORDINATE WITH OWNER FOR EXACT REQUIREMENTS OF TREND LOG REQUIREMENTS.

EXHAUST FAN CONTROL DIAGRAM

EXHAUST FAN CONTROL

THERMOSTAT FAN CONTROL: OPEN MOTOR-OPERATED INTAKE DAMPER (WHERE APPLICABLE) AND START FAN (TIME DELAY) BASED ON A RISE IN SPACE TEMPERATURE ABOVE THE SPACE TEMPERATURE SET POINT. STOP FAN AND CLOSE MOTOR-OPERATED INTAKE DAMPER (WHERE APPLICABLE) (TIME DELAY) WHEN SPACE TEMPERATURE DROPS 1F BELOW SET POINT.

SPACE SET POINTS:
MECHANICAL/ELECTRICAL ROOMS = 85F


HW UNIT HEATER CONTROL

GENERAL: PROVIDE UNIT-MOUNTED ADJUSTABLE THERMOSTAT. CYCLE FAN ON AND OPEN HW CONTROL VALVE TO MAINTAIN SETPOINT AS TEMPERATURE DROPS BELOW THERMOSTAT SETPOINT. PROVIDE AQUASTAT TO PREVENT FAN OPERATION IF HOT WATER SUPPLY DROPS BELOW 90F. DEENERGIZE FAN AND CLOSE HW VALVE WHEN OUTSIDE AIR TEMP RISES ABOVE 60F ADJUSTABLE

SPACE SET POINTS:
MECHANICAL/ELECTRICAL ROOMS = 60F
STAIRWELLS = 60F
STORAGE ROOMS = 60F

MONITOR AND TREND: SPACE TEMPERATURE (15 MINUTE INTERVALS)

ALARM BAS: SPACE TEMPERATURE FALLS 10F (ADJ.) BELOW SETPOINT.



STATE BUILDING OFFICIAL




Dewberry Engineers Inc.
9300 Harris Corners Parkway
Suite 220
Charlotte, NC 28269-3797
704.500.5815
NC License No. F-0929

DEB APPROVAL



SEAL



12/5/2025

KEY PLAN:

SCALE:

REVISIONS

NO.	DATE	BY	DESCRIPTION
2	12/05/25	SWD	DEB CMNTS/ADD 3
1	10/24/25	SWD	DEB COMMENTS

DRAWN BY _____ SMF
APPROVED BY _____ SWD
CHECKED BY _____ JMT
DATE _____ JULY 25, 2025


TITLE
MECHANICAL
CONTROLS

DEI PROJECT NO: 50188025
RADFORD PROJECT NO: 217-B5217-004
SHEET NO.

M7.01



—1—1— 1-HR FIRE RATED WALL
—2—2— 2-HR FIRE WALL
—SB—SB— SMOKE PARTITIONS



GENERAL NOTES:

- REFER TO E0.01 FOR ADDITIONAL NOTES.
- REFER TO FIXTURE SCHEDULE FOR FURTHER INFORMATION.
- PROVIDE LISTED FIRESTOP SYSTEMS AT PENETRATIONS FOR LIFE-SAFETY RATED ASSEMBLIES REQUIRED FOR THE WORK. REFERENCE SECTION 078413 "THROUGH PENETRATION FIRESTOP SYSTEMS" FOR REQUIREMENTS AND THE UL DESIGN APPENDIX IN THE PROJECT MANUAL FOR FIRESTOP SYSTEM DETAILS.

1 GROUND LIGHTING PLAN
Scale: 1/4" = 1'-0"

KEY NOTES

- CONTRACTOR SHALL PROVIDE NEW FIXTURE AS SHOWN. MODIFY AND EXTEND SWITCHED CIRCUIT RETAINED DURING DEMOLITION TO NEW FIXTURE. CONNECT TO EXISTING BRANCH CIRCUIT SERVING THIS AREA.
- CONTRACTOR SHALL REINSTALL DEVICE RETAINED DURING DEMOLITION. MODIFY AND EXTEND CIRCUIT AS REQUIRED FOR NEW LOCATION. PRIOR TO RE-INSTALLATION, CONTRACTOR SHALL WIPE DOWN AND CLEAN DEVICE.
- FIXTURE TO BE WIRED AS NIGHT LIGHT. CONTRACTOR SHALL CONNECT FIXTURE AHEAD OF SWITCHED LEG.
- CONTRACTOR SHALL PROVIDE OCCUPANCY SENSOR AS SHOWN. OCCUPANCY SENSOR SHALL CONTROL NIGHT LIGHT FIXTURES IN THIS SPACE. FIXTURES SHALL TURN OFF IF SPACE IS EMPTY AND NO MOTION IS DETECTED AFTER A PERIOD OF 30 MINUTES. UPON DETECTION OF MOTION OCCUPANCY SENSOR SHALL BRING NIGHT LIGHT FIXTURE TO FULL BRIGHTNESS.

WALL RATING LEGEND	
—1—1—	1-HR FIRE RATED WALL
—2—2—	2-HR FIRE WALL
—SB—SB—	SMOKE PARTITIONS




Dewberry Engineers Inc.
9300 Harris Corners Parkway
Suite 220
Charlotte, NC 28269-3797
704.509.9918
NC License No. F-0929

DEB APPROVAL



SEAL



KEY PLAN:

SCALE:

REVISIONS

NO.	DATE	BY	DESCRIPTION
2	12/05/25		DEB CMNTS/ADD 3
1	10/24/25		DEB COMMENTS

DRAWN BY _____ TLW
APPROVED BY _____ TLW
CHECKED BY _____ POA
DATE _____ JULY 25, 2025

TITLE
GROUND LIGHTING PLAN

DEI PROJECT NO: 50188025
RADFORD PROJECT NO: 217-B5217-004

SHEET NO.

E1.12

DEB APPROVAL



Radford
UNIVERSITY

**ALLEN BUILDING
ELECTRICAL
REPLACEMENT**

**100% CONSTRUCTION
DOCUMENTS**

SEAL

KEY PLAN:

SCALE:

REVISIONS

[illegible]

DRAWN BY TLW

APPROVED BY TLW

CHECKED BY _____ POA _____

DATE	JULY 25, 2025
------	---------------

TITLE

FIRST FLOOR POWER PLAN

DEI PROJECT NO: 50188025

RADFORD PROJECT NO: 217-B5217-004

SHEET NO.

E1.21

WALL RATING LEGEND	
—1—1—	1-HR FIRE RATED WALL
—2—2—	2-HR FIRE WALL
—SB—SB—	SMOKE PARTITIONS

GENERAL NOTES:

1. REFER TO E0.01 FOR ADDITIONAL NOTES.
2. COORDINATE CONNECTION OF ALL MECHANICAL EQUIPMENT WITH DIVISION 23 CONTRACTOR.
3. PROVIDE LISTED FIRESTOP SYSTEMS AT PENETRATIONS FOR LIFE-SAFETY RATED ASSEMBLIES REQUIRED FOR THE WORK. REFERENCE SECTION 078413 "THROUGH PENETRATIONS" FOR REQUIREMENTS AND THE UL DESIGN APPENDIX IN THE PROJECT MANUAL FOR FIRESTOP SYSTEM DETAILS.

KEY NOTES

- 1 CONTRACTOR SHALL COORDINATE RHC-1 ELECTRICAL CONNECTION WITH DIVISION 23 CONTRACTOR. REFER TO PANEL SCHEDULE FOR FURTHER INFORMATION. REFER TO MECHANICAL FIRST FLOOR NEW WORK PLAN AND MECHANICAL SCHEDULE FOR FURTHER INFORMATION.
- 2 CONTRACTOR SHALL PROVIDE JUNCTION BOX ABOVE CEILING ADJACENT TO FACP FOR FUTURE AHU-1 DUCT DETECTOR CONNECTION.
- 3 CONTRACTOR SHALL PROVIDE JUNCTION BOX ABOVE CEILING TO STUB FUTURE AHU-1 FACP TO CONDUIT FROM DETECTOR. PROVIDE JUNCTION BOXES FOR FUTURE AHU-1 USE. REFER TO RISER DIAGRAM FOR FURTHER DETAILS.
- 4 CONTRACTOR SHALL PROVIDE NEW FIRE ALARM WIRING AND CONDUIT FROM NEW JUNCTION BOX ADJACENT TO EXISTING FACP TO NEW JUNCTION BOX ABOVE CEILING FOR FUTURE AHU-2 DETECTOR. FACP IS LOCATED IN FIRST FLOOR ROOM 132. CIRCULARLY LABEL JUNCTION BOX AS FUTURE AHU-1 FIRE ALARM.

1 FIRST FLOOR POWER PLAN

Scale: 1/4" = 1'-0"




E

D

C

B

A



GENERAL NOTES:

1. REFER TO E-001 FOR ADDITIONAL NOTES.
2. REFER TO FIXTURE SCHEDULE FOR FURTHER INFORMATION.
3. PROVIDE LISTED FIRESTOP SYSTEMS AT PENETRATIONS FOR LIFE-SAFETY RATED ASSEMBLIES REQUIRED FOR THE WORK. REFERENCE SECTION 078413 "THROUGH PENETRATION FIRESTOP SYSTEMS" FOR REQUIREMENTS AND THE UL DESIGN APPENDIX IN THE PROJECT MANUAL FOR FIRESTOP SYSTEM DETAILS.

KEY NOTES

1. CONTRACTOR SHALL PROVIDE NEW FIXTURE AS SHOWN. MODIFY AND EXTEND SWITCHED CIRCUIT RETAINED DURING DEMOLITION TO NEW FIXTURE. CONNECT TO EXISTING BRANCH CIRCUIT SERVING THIS AREA.
2. CONTRACTOR SHALL PROVIDE NEW EXIT SIGN AS SHOWN. MODIFY AND EXTEND BRANCH CIRCUIT WIRING AND CONDUIT RETAINED DURING DEMOLITION TO NEW EXIT SIGN.
3. FIXTURE TO BE WIRED AS NIGHT LIGHT. CONTRACTOR SHALL CONNECT FIXTURE AHEAD OF SWITCHED LEG.
4. CONTRACTOR SHALL PROVIDE OCCUPANCY SENSOR AS SHOWN. OCCUPANCY SENSOR SHALL CONTROL NIGHT LIGHT FIXTURES IN THIS SPACE. FIXTURES SHALL TURN OFF IF SPACE IS EMPTY AND NO MOTION IS DETECTED AFTER A PERIOD OF 30 MINUTES. UPON DETECTION OF MOTION OCCUPANCY SENSOR SHALL BRING NIGHT LIGHT FIXTURE TO FULL BRIGHTNESS.




Dewberry Engineers Inc.
9300 Harris Corners Parkway
Suite 220
Charlotte, NC 28269-3797
704.509.9918
NC License No. F-0929

DEB APPROVAL



SEAL



KEY PLAN:

SCALE:

REVISIONS

NO.	DATE	BY	DESCRIPTION
2	12/05/25		DEB CMNTS/ADD 3
1	10/24/25		DEB COMMENTS

DRAWN BY _____ TLW
APPROVED BY _____ TLW
CHECKED BY _____ POA
DATE _____ JULY 25, 2025

TITLE
FIRST FLOOR LIGHTING PLAN

DEI PROJECT NO: 50188025
RADFORD PROJECT NO: 217-B5217-004
SHEET NO.

WALL RATING LEGEND	
—1—1—	1-HR FIRE RATED WALL
—2—2—	2-HR FIRE WALL
—SB—SB—	SMOKE PARTITIONS

E1.22


E

D


C

B

A




A ELECTRICAL DEMOLITION PLAN AT CHILLER AREA
Scale: 1/4" = 1'-0"



B ELECTRICAL PLAN AT CHILLER AREA
Scale: 1/4" = 1'-0"

KEY NOTES

- 1 CONTRACTOR SHALL PROVIDE NEW 600A SE RATED, NEMA 3R, HD, FUSED DISCONNECT AS SHOWN. REFER TO RISER DIAGRAM FOR FURTHER DETAILS.
- 2 CONTRACTOR SHALL PROVIDE (2) NEW SERVICE WEATHERHEADS FOR NEW ELECTRICAL SERVICE. NEW WEATHERHEADS SHALL BE MINIMUM 12' AFG AND MAXIMUM 22' AFG. COORDINATE FINAL MOUNTING HEIGHT WITH UTILITY COMPANY PRIOR TO ROUGH IN.
- 4 CONTRACTOR SHALL STUB CHILLER FEEDER CONDUIT DOWN AT BUILDING EXTERIOR AND ROUTE TO BELOW GRADE TO NEW DISCONNECT MOUNTED ON NEW UNISTRUT FRAME. NEW UNISTRUT FRAME SHALL BE PROVIDED BY DIVISION 23 CONTRACTOR. PROVIDE A NEMA 3R RATED JUNCTION BOX AT EXTERIOR OF BUILDING TO MAKE TRANSITION.



C ELECTRICAL SERVICE EQUIPMENT ELEVATION VIEW
Scale: 1/4" = 1'-0"




Dewberry Engineers Inc.
9300 Harris Corners Parkway
Suite 220
Charlotte, NC 28269-3797
704.509.9918
NC License No. F-0929

DEB APPROVAL



SEAL



KEY PLAN:

SCALE:

REVISIONS

NO.	DATE	BY	DESCRIPTION
2	12/05/25		DEB CMNTS/ADD 3
1	10/24/25		DEB COMMENTS

DRAWN BY _____ TLW
APPROVED BY _____ TLW
CHECKED BY _____ POA
DATE _____ JULY 25, 2025

TITLE
**GROUND FLOOR
ELECTRICAL
PLAN**

DEI PROJECT NO: 50188025
RADFORD PROJECT NO: 217-B5217-004
SHEET NO.

E4.01



Dewberry Engineers Inc.
9300 Harris Corners Parkway
Suite 220
Charlotte, NC 28269-3797
704.509.9918
NC License No. F-0929

DEB APPROVAL



SEAL



12/5/2025

KEY PLAN:

SCALE:

REVISIONS

NO.	DATE	BY	DESCRIPTION
2	12/05/25		DEB CMNTS/ADD 3
1	10/24/25		DEB COMMENTS



DRAWN BY _____ TLW
APPROVED BY _____ TLW
CHECKED BY _____ POA
DATE _____ JULY 25, 2025

TITLE
**GROUND FLOOR
ELECTRICAL
ROOM PLANS**

DEI PROJECT NO: 50188025
RADFORD PROJECT NO: 217-B5217-004

SHEET NO.

E4.02



KEY NOTES

- CONTRACTOR SHALL REMOVE AND RETAIN EXISTING DEVICE FOR RELOCATION DURING NEW WORK. PULL BACK AND RETAIN CIRCUIT TO NEAREST UPSTREAM JUNCTION BOX.
- CONTRACTOR SHALL DISCONNECT WATER HEATER BRANCH CIRCUIT IN PREPARATION FOR WATER HEATER RELOCATION. COORDINATE RELOCATION WITH DIVISION 23 CONTRACTOR.
- CONTRACTOR SHALL REMOVE FIRE ALARM DEVICE AND RETAIN FOR RE-INSTALLATION DURING NEW WORK. MAINTAIN CONTINUITY OF SLC CIRCUIT DURING WALL DEMOLITION.
- CONTRACTOR SHALL CAP AND SEAL EXISTING KNOCKOUT ON EXISTING BAS UPS ENCLOSURE. BAS UPS AND ENCLOSURE SHALL BE RELOCATED BY DIVISION 23 CONTRACTOR. MODIFY AND EXTEND EXISTING BRANCH CIRCUIT TO NEW LOCATION BELOW EXISTING BAS PANEL. COORDINATE RELOCATION WITH DIVISION 23 CONTRACTOR.

KEY NOTES

- CONTRACTOR SHALL REINSTALL FIRE ALARM DEVICE RETAINED DURING DEMOLITION. RECONNECT DEVICE TO EXISTING SLC LOOP.
- CONTRACTOR SHALL REINSTALL DEVICE RETAINED DURING DEMOLITION. MODIFY AND EXTEND CIRCUIT AS REQUIRED FOR NEW LOCATION.
- CONTRACTOR SHALL PROVIDE JUNCTION BOX ABOVE PANEL PA FUTURE AHU-1 ANCILLARY CIRCUITS. PROVIDE WIRE AND CONDUIT FROM NEW JUNCTION BOX TO ROOFTOP. CLEARLY LABEL JUNCTION BOX AS FUTURE USE FOR AHU-1 ANCILLARY CIRCUITS. MINIMUM JUNCTION BOX SIZE SHALL BE 4"Dx4"Hx12"W. REFER TO ROOF PLAN AND RISER DIAGRAM FOR FURTHER INFORMATION.
- CONTRACTOR SHALL PROVIDE HEAVY DUTY, NEMA 1, 30AF, NF DISCONNECT FOR WH-1.
- CONTRACTOR SHALL PROVIDE NEW PANELBOARD AS SHOWN. REFER TO RISER DIAGRAM AND PANEL SCHEDULES FOR FURTHER INFORMATION.
- CONTRACTOR SHALL MODIFY AND EXTEND BRANCH CIRCUIT WIRE AND CONDUIT AS REQUIRED TO ACCOMMODATE RELOCATION OF EXISTING WATER HEATER. TERMINATE EXISTING BRANCH CIRCUIT RETAINED DURING DEMOLITION ON NEW DISCONNECT. PROVIDE NEW WIRE AND CONDUIT (2#10 & 1#10G IN 3/4"C) BETWEEN NEW DISCONNECT AND EXISTING WH-1. COORDINATE RELOCATION WITH DIVISION 23 CONTRACTOR.
- CONTRACTOR SHALL PROVIDE (1) 1"C WITH PULLSTRING TO NEW PROPANE TANK FOR PROPANE TANK FILL LEVEL ALARM. REFER TO CIVIL PLANS AND PROFILE FOR EXACT LOCATION, UNDERGROUND ROUTING, AND BURIAL DEPTH. TURN UNDERGROUND CONDUIT UP AT WALL AND STUB INTO MECHANICAL ROOM. ROUTE CONDUITS INTO NEW JUNCTION BOX INSIDE MECHANICAL ROOM. ROUTE INTERIOR CONDUIT FROM NEW JUNCTION BOX TO NEW BAS PANEL LOCATED IN MECHANICAL ROOM 002. COORDINATE TERMINATION AT NEW BAS PANEL WITH DIVISION 23 CONTRACTOR. CLEARLY LABEL JUNCTION BOX TO SHOW CONDUIT IS ROUTED TO NEW PROPANE TANK.
- CONTRACTOR SHALL PROVIDE NEW BRANCH CIRCUIT (2#12 & 1#12G IN 3/4"C) TO NEW BAS PANEL AS SHOWN. COORDINATE CONNECTION WITH DIVISION 23 CONTRACTOR.
- CONTRACTOR SHALL MODIFY AND EXTEND BRANCH CIRCUIT WIRING AND CONDUIT (2#12, 1#12G IN 3/4"C) SERVING THE BAS UPS PANEL TO NEW LOCATION BELOW BAS-1 AS SHOWN. COORDINATE RELOCATION WITH DIVISION 23 CONTRACTOR.
- CONTRACTOR SHALL PROVIDE NEW FIRE ALARM DEVICE AS SHOWN. CONNECT DEVICE TO EXISTING SLC LOOP.


E

D

C

B


A




NOTE: REFER TO DETAIL #3 THIS SHEET FOR FURTHER DUCT BANK DETAILS.

4 DIRECT BURIED DUCT BANK SECTION
Scale: N.T.S.


- NOTE:
1. THE BOTTOM OF THE TRENCH MUST BE FREE OF ROCK, CINDERS OR SHARP OBJECTS.
 2. THE BACKFILLED TRENCH SHALL BE FREE OF PEAT, MARL, HIGHLY PLASTIC CLAY, OR OTHER UNSUITABLE MATERIAL SUCH AS TRASH, DEBRIS, BRUSH, FROZEN MATERIAL OR ICE.
 3. PLACE EMBEDMENT ZONE MATERIAL IN 3 OR MORE LIFTS AS SHOWN AND TAMP TO ELIMINATE VOIDS AND ASSURE FULL CONTACT WITH THE CONDUIT PERIMETER.
 4. PLACE FINAL BACKFILL ZONE MATERIAL IN 6-INCH LIFTS AND COMPACT WITH MULTIPLE PASSES OF A MACHINE TAMPER, ROLLER, OR VIBRATORY EQUIPMENT (FOR USE ON SAND AND GRAVEL ONLY) THAT IS SPECIFICALLY DESIGNED FOR SOIL COMPACTION. COMPACT UNTIL VOIDS ARE ELIMINATED AND THE COMPACTED SURFACE NO LONGER VISIBLY YIELDS BENEATH THE COMPACTION EQUIPMENT.
 5. NUMBER OF CONDUIT VARIES. REFER TO DIRECT BURIED DUCT BANK SECTION DETAIL #4 THIS SHEET.



3 TYPICAL DIRECT BURIED CONDUIT INSTALLATION
Scale: N.T.S.



1 CONDUIT DIRECT BURIED GRS-PVC TRANSITION
Scale: N.T.S.



SEISMIC CATEGORY 'C'
TYPICAL PANELBOARD MOUNTING DETAIL

- NOTES:
1. PROVIDE CERTIFICATION THAT PANELBOARDS, OVERCURRENT PROTECTION DEVICES, ACCESSORIES AND COMPONENTS MEET THE SEISMIC REQUIREMENTS OF VCC 2015, CATEGORY 'C'.
 2. PROVIDE SHAKE TABLE TEST RESULTS CERTIFIED BY A THIRD PARTY TO THE AUTHORITIES HAVING JURISDICTION PRIOR TO INSPECTION.

2 SEISMIC PANELBOARD SUPPORT
Scale: N.T.S.




Dewberry Engineers Inc.
9300 Harris Corners Parkway
Suite 220
Charlotte, NC 28269-3797
704.509.9918
NC License No. F-0929

DEB APPROVAL



SEAL



KEY PLAN:

SCALE:

REVISIONS

NO.	DATE	BY	DESCRIPTION
2	12/05/25		DEB CMNTS/ADD 3
1	10/24/25		DEB COMMENTS

DRAWN BY _____ TLW
APPROVED BY _____ TLW
CHECKED BY _____ POA
DATE _____ JULY 25, 2025

TITLE
**ELECTRICAL
DETAILS**

DEI PROJECT NO: 50188025
RADFORD PROJECT NO: 217-B5217-004
SHEET NO.

E5.01

E

D

C


B

A



NOTE:

- THIS FIGURE ILLUSTRATES THE WORKING SPACE IN FRONT OF THE ELECTRICAL EQUIPMENT REQUIRED BY SECTION 110.26(A) AND 110.26(F) OF THE NATIONAL ELECTRICAL CODE.
- DOORS TO ELECTRICAL ROOMS SHALL BE PROVIDED WITH PERMANENT SIGNAGE READING "NO STORAGE" IN LETTERS NOT LESS THAN THE ROOM IDENTIFICATION OR THE WORKING SPACE AS DEFINED BY NEC SHALL BE MARKED BY A 2 WIDE YELLOW LINE AND STENCILED "NO STORAGE - ELECTRICAL WORKING SPACE" IN 2" HIGH YELLOW LETTERS IN MECHANICAL ROOMS, ELECTRICAL ROOMS, AND SERVICE AREAS.





2" WIDE YELLOW LINES ON FLOOR STENCILED WITH "NO STORAGE - ELECTRICAL WORKING SPACE" IN 2" HIGH YELLOW LETTERS ON THE FLOOR TO DENOTE WORKING SPACE REQUIRED IF NO SIGN ON DOOR PROVIDED. REFER TO NOTE #2 FOR REQUIREMENTS. REFER TO TABLE A FOR EXACT WORKING SPACE CLEAR DISTANCES.

TABLE A - WORKING SPACES				
VOLTAGE TO GROUND NOMINAL	CONDITION:	MINIMUM CLEAR DISTANCE FEET		
		1	2	3
0-150	3	3	3	3
151-600	3	3	3-1/2	4


WHERE THE "CONDITIONS" ARE AS FOLLOWS

- EXPOSED LIVE PARTS ON ONE SIDE AND NO LIVE OR GROUNDED PARTS ON THE OTHER SIDE OF THE WORKING SPACE. OR EXPOSED LIVE PARTS ON BOTH SIDES EFFECTIVELY GUARDED BY SUITABLE WOOD OR OTHER INSULATING MATERIALS. INSULATED WIRE OR INSULATED BUSBARS OPERATING AT NOT OVER 300V TO GROUND SHALL NOT BE CONSIDERED LIVE PARTS.
- EXPOSED LIVE PARTS ON ONE SIDE AND GROUNDED PARTS ON THE OTHER SIDE. (CONCRETE BRICK OR TILE WALLS SHALL BE CONSIDERED AS GROUNDED.)
- EXPOSED LIVE PARTS ON BOTH SIDES OF THE WORK SPACE (NOT GUARDED AS PROVIDED IN CONDITION 1) WITH THE OPERATOR BETWEEN.



DETAIL KEY NOTES:

- EQUIPMENT BY MECHANICAL CONTRACTOR.
- CONDUIT & WIRING BY ELECTRICAL CONTRACTOR.
- DISCONNECT SWITCH FURNISHED BY MECHANICAL CONTRACTOR, INSTALLED BY ELECTRICAL CONTRACTOR.
- A COMBINATION STARTER OR VFD MAY BE USED IN LIEU OF A SEPARATE DISCONNECT SWITCH AND STARTER / VFD. DISCONNECT SWITCH AND STARTER/VFD FURNISHED BY MECHANICAL CONTRACTOR, INSTALLED BY ELECTRICAL CONTRACTOR. LOCATE DISCONNECT SWITCH ADJACENT TO VFD.
- FEEDER CIRCUIT WIRING AND CONDUIT IN ELECTRICAL WORK. SEE PANELBOARD SCHEDULE FOR BREAKER SIZES AND BRANCH OR FEEDER SCHEDULES FOR WIRE/CONDUIT SIZES.
- EQUIPMENT PROVIDED BY MECHANICAL CONTRACTOR, WITH INTEGRAL DISCONNECTING MEANS.
- MECHANICAL CONTRACTOR SUPPLYING THE EQUIPMENT SHALL MAKE FINAL CONNECTIONS, START UP, AND TEST EQUIPMENT.
- IF AN ADDITIONAL DISCONNECT IS REQUIRED BY NEC IT SHALL BE FURNISHED BY MECHANICAL CONTRACTOR AND INSTALLED BY ELECTRICAL CONTRACTOR.



2 ELECTRICAL TO MECHANICAL EQUIPMENT

Scale: N.T.S.

NOTE: DETAIL IS ALSO SHOWN ON MECHANICAL DRAWINGS. DETAIL IS DUPLICATED FOR EASE OF REFERENCE FOR EACH RESPECTIVE CONTRACTOR.

1 WORKING CLEARANCE FOR ELECTRICAL EQUIPMENT

Scale: N.T.S.




Dewberry Engineers Inc.

9300 Harris Corners Parkway
Suite 220
Charlotte, NC 28269-3797
704.509.9918
NC License No. F-0929

DEB APPROVAL



SEAL



KEY PLAN:

SCALE:

REVISIONS

NO.	DATE	BY	DESCRIPTION
2	12/05/25		DEB CMNTS/ADD 3
1	10/24/25		DEB COMMENTS

DRAWN BY _____ TLW
APPROVED BY _____ TLW
CHECKED BY _____ POA
DATE _____ JULY 25, 2025

TITLE
ELECTRICAL
DETAILS

DEI PROJECT NO: 50188025

RADFORD PROJECT NO: 217-B5217-004

SHEET NO.

E5.02

E

D

C

B

A

12/3/2025 4:21:48 PM

EXISTING PANEL: PA										NEW WORK												
LOCATION: MECHANICAL...					VOLTS: 120/208 Wye					MAINS TYPE: MLO												
SUPPLY FROM: MDP					PHASES: 3					BUS RATING: 225 A												
MOUNTING: Surface					WIRES: 4					NEUTRAL RATING: 100.00%												
ENCLOSURE: Type 1					SE RATED: NO					MINIMUM KAIC: 10												
MANUFACTURER/MODEL:					CALCULATED Isc:																	
CKT	LOAD SERVED			CB	P	*	A		B		C		*	P	CB	LOAD SERVED		CKT				
1	PCHWP-1 (3HP) (3#12 & 1#12G IN 3/4"C)			20 A	3	11	1272	0					11	3	20 A	PCHWP-2 (3HP) (3#12 & 1#12G IN 3/4"C)		2				
3									1272	0								4				
5											1272	0							6			
7	SHWP-1 (1.5HP) (3#12 & 1#12G IN 3/4"C)			15 A	3	11	792	0					11	3	15 A	SHWP-2 (1.5HP) (3#12 & 1#12G IN 3/4"C)		8				
9										792	0								10			
11											792	0							12			
13	PHWP-1 (1/3HP)			20 A	1	10	864	0					--	3	20 A	OAU-1		14				
15	PHWP-2 (1/3HP)			20 A	1	10			864	0								16				
17	SPARE			20 A	1	10					0	0	--	1	20 A	REC. EMS DAY RM.		18				
19	EF-1 (1/4HP)			15 A	1	11	696	0										20				
21	EF-3			20 A	1	--			0	0			--	1	20 A	REC. EMS BED RM.		22				
23				20 A	3	--					0	0				AIR COND OUTSIDE				24		
25	KW METER						0	0							2					20 A	26	
27									0	0					--	1	20 A	LTS - AMMO/RECORD RM.				28
29											0	0										1
31	AC UNIT RADIO ROOM			20 A	2	--	0	500					2	20 A	WATER HEATER				32			
33	RECORD ROOM REC			20 A	1	--			0	0									34			
35	AMMO ROOM REC			20 A	1	--					0	500	10	1	20 A	BAS-2				36		
37						0	0					38										
39	FUTURE ELEVATOR			125 A	3	--			0	0			--	3	150 A	SPARE				40		
41									0	0										42		
CONNECTED LOAD:							4124 VA		2928 VA		2564 VA											
CONNECTED AMPS:							35 A		25 A		21 A											
DEMAND AMPS:							35 A		25 A		21 A											
BREAKER NOTES:							PANEL NOTES:															
* INDICATES BREAKER TYPE: 1=GFCI (6mA), 2=GECB (30mA/100mA), 3=SHUNT TRIP, 4=AFCI, 5=SUBFEED BREAKER, 6=LI, 7=LSI, 8=LSIG, 9= LOCKING DEVICE, 10=NEW BREAKER IN EXISTING, 11=EXISTING BREAKER.																						
LOAD CLASSIFICATION				CONNECTED LOAD				Demand Factor				ESTIMATED DEMAND				PANEL TOTALS						
Default				9616 VA				100.00%				9616 VA				TOTAL LOAD: 9616 VA						
																DEMAND FACTOR: 100.00%						
																DEMAND LOAD: 9616 VA						
																DEMAND AMPS: 27 A						

PANEL PA
LOAD REMOVED: 29,780VA
LOAD ADDED: 9,616VA
NET LOAD: -20,164VA

PANEL MDP
LOAD REMOVED: 34,356VA
LOAD ADDED: 11,673VA
NET LOAD: -22,683VA

PANEL PB
LOAD REMOVED: 2,200VA
LOAD ADDED: 2,000VA
NET LOAD: -200VA

PANEL: PB										BRANCH: WORK														
LOCATION: MECHANICAL...					VOLTS: 120/208 Wye					MAINS TYPE: MLO														
SUPPLY FROM: MDP					PHASES: 3					BUS RATING: 125 A														
MOUNTING: Surface					WIRES: 4					NEUTRAL RATING: 100.00%														
ENCLOSURE: Type 1					SE RATED: NO					MINIMUM KAIC: 10														
MANUFACTURER/MODEL:					CALCULATED Isc:																			
CKT	LOAD SERVED				CB	P	*	A		B		C		*	P	CB	LOAD SERVED				CKT			
1	CARD READER				20 A	1	--	0	1000					10.2	1	20 A	CHILLER HEAT TRACE				2			
3	OAU + VALVES				20 A	1	--			0	0						--	1	20 A	FC 2005,2010,2015,2020,2025,2030,2035				4
5	FC 2040,2045,2047,2050,2060,2070,2075,2080				20 A	1	--					0	0	--	1	20 A	FC 2200,2205,2210,2215,2230				6			
7	FC 2245,2255,2260,2265,2270,2275				20 A	1	--	0	1000								11	1	20 A	CHILLER EVAPORATOR HEATER				8
9	NIGHT LIGHTS				20 A	1	--			0	0			--	1	20 A	EMERGENCY LIGHTS				10			
11	EXTERIOR LIGHTS				20 A	1	--					0	25				--	1	20 A	Default MECHANICAL ROOM 002				12
13	COMPUTER INTERFACE				20 A	1	--	0	0					--	1	20 A	TELEPHONE SYSTEM				14			
15	MISC. EMS CIRCUITS				20 A	1	--			0	0						--	1	20 A	MISC. RECEPT. GRD. FLOOR				16
17	CARD READERS				20 A	1	--					0	0	--	2	25 A	DMSS-3A, 3B & CU-3AB				18			
19	A&B EVAP UNITS				15 A	1	--	0	0												20			
21	CARD READER				20 A	1	--			0	0			--	1	20 A	D.C. MARQUE LIGHTS				22			
23	NETWORK SYCS. RECEPT				20 A	1	--					0	0				--	2	20 A	EAST AN WEST MARQUE				24
25	LIGHTS IN GARAGE				20 A	1	--	0	0					--	1	20 A	EXISTING				26			
27	RECEPTS IN GARAGE				20 A	1	--			0	0										--	1	20 A	28
29	GEN. BATT. CHARGER				20 A	1	--					0	0	--	1	20 A	MAIN FIRE ALARM PANEL				30			
CONNECTED LOAD:					2000 VA				0 VA		25 VA													
CONNECTED AMPS:					17 A				0 A		0 A													
DEMAND AMPS:					17 A				0 A		0 A													
BREAKER NOTES:					PANEL NOTES:																			
* INDICATES BREAKER TYPE: 1=GFCI (6mA), 2=GECB (30mA/100mA), 3=SHUNT TRIP, 4=AFCI, 5=SUBFEED BREAKER, 6=LI, 7=LSI, 8=LSIG, 9= LOCKING DEVICE, 10=NEW BREAKER IN EXISTING, 11=EXISTING BREAKER.																								
LOAD CLASSIFICATION					CONNECTED LOAD					Demand Factor					ESTIMATED DEMAND					PANEL TOTALS				
Default					2025 VA					100.00%					2025 VA					TOTAL LOAD: 2025 VA				
																				DEMAND FACTOR: 100.00%				
																				DEMAND LOAD: 2025 VA				
																				DEMAND AMPS: 6 A				


SEQUENCE OF CONSTRUCTION NOTES:

- CONTRACTOR SHALL PROVIDE 150KW, DIESEL RENTAL GENERATOR AND TEMPORARY CABLING FOR THE DURATION OF THE ELECTRICAL INFRASTRUCTURE UPGRADES. IT IS CONTRACTORS RESPONSIBILITY TO INCLUDE RENTAL GENERATOR COSTS IN THEIR BID.
- ANY SHUTDOWN EFFECTING CALL CENTER OPERATION MUST BE SHORTER IN DURATION THAN THE UPS BATTERY RUN TIME (~30MINS) TO ENSURE CALL CENTER FUNCTIONALITY.
- CONTRACTOR SHALL CONFIRM UPS LOADING, UPS CAPACITY, AND UPS RUNTIME FOR CALL CENTER UPS AND BAS PANEL UPS PRIOR TO ANY PLANNED BUILDING OUTAGE. IF IT IS DETERMINED THAT THE PLANNED OUTAGE WILL BE LONGER THAN UPS RUNTIME A TEMPORARY UPS MAY BE REQUIRED. NOTIFY ENGINEER IMMEDIATELY IF IT IS DETERMINED EITHER UPS HAS INSUFFICIENT RUNTIME FOR PLANNED OUTAGE.
- ALL OUTAGES ARE TO OCCUR MONDAY-FRIDAY DURING TYPICAL BUSINESS HOURS.
- CONTRACTOR SHALL PROVIDE ADEQUATE AMOUNT OF FUEL FOR GENERATOR DURING TIMES WHEN BUILDING IS ON GENERATOR POWER ONLY. CONTRACTOR SHALL MONITOR FUEL LEVELS AND REFILL THE FUEL TANK AS REQUIRED. ONCE SEQUENCE IS COMPLETE CONTRACTOR SHALL FILL GENERATOR FUEL TANK TO FULL LEVEL.

ELECTRICAL SERVICE REPLACEMENT – SEQUENCE OF CONSTRUCTION

PLEASE NOTE THAT THE FOLLOWING SEQUENCE IS NOT MEANT TO SERVE AS STEP-BY-STEP INSTRUCTIONS FOR THE CONTRACTOR DURING CONSTRUCTION. INSTEAD, IT IS MEANT TO SERVE AS A GENERAL GUIDE TO AID IN TRANSITIONING FROM DEMOLITION TO NEW WORK AND MINIMIZE DOWNTIME FOR THE BUILDING. CONTRACTOR TO COORDINATE ANY SHUTDOWN WORK WITH THE OWNER A MINIMUM OF 2-WEEKS PRIOR TO PLANNED SHUTDOWN.

- CONTRACTOR SHALL PROVIDE TEMPORARY, ROLL-UP, 150KW, DIESEL GENERATOR WITH ONBOARD BELLY TANK. PROVIDE DLO CABLING TO ROUTE FROM TEMPORARY GENERATOR TO EXISTING ATS INSIDE MECHANICAL ROOM 002. COORDINATE TEMPORARY CABLE ROUTING AND TEMPORARY GENERATOR LOCATION WITH OWNER.
- COORDINATE BUILDING OUTAGE WITH OWNER.** DURING OUTAGE:
 - DISCONNECT NORMAL FEEDERS FROM EXISTING ATS NORMAL LUGS
 - TERMINATE TEMPORARY DLO FEEDERS FROM TEMPORARY GENERATOR ON NORMAL LUGS OF EXISTING ATS
 - START-UP TEMPORARY GENERATOR AND ENSURE PROPER VOLTAGE, PHASE ROTATION, AND FEEDER CONNECTIONS
- BUILDING IS NOW OPERATING ON TEMPORARY GENERATOR AS THE 'NOMRAL' ATS FEED AND THE EXISTING ON-SITE GENERATOR CONTINUING TO OPERATE AS THE EMERGENCY FEED. CONTRACTOR CAN NOW COORDINATE THE NEW UTILITY FEED TO THE BUILDING WITH THE UTILITY COMPANY, DEMOLISH THE NORMAL FEED INTO THE BUILDING, AND INSTALL THE NEW ELECTRICAL INFRASTRUCTURE WHILE THE BUILDING HAS (2) SOURCES OF POWER. REFER TO THE DEMOLITION AND NEW WORK RISER DIAGRAM FOR FURTHER DETAILS.
 - CONTRACTOR SHALL ONLY ROUTE THE FEEDERS FROM NEW PANEL MSB TO THE EXISTING ATS. DO NOT TERMINATE THE FEEDERS ONTO THE ATS UNTIL ALL ELECTRICAL WORK IS COMPLETE. THE PERMANENT FEEDER CONNECTION FROM PANEL MSB TO THE EXISTING ATS NORMAL LUGS SHALL BE THE LAST STEP TO MINIMIZE DOWNTIMES AND OUTAGES.
 - LOTO MSB BREAKER THAT SERVES THE ATS NORMAL LUGS
 - LOTO NEW SE RATED DISCONNECT SWITCH ON EXTERIOR OF BUILDING
- ONCE ALL ELECTRICAL INFRASTRUCTURE IS DEMOLISHED AND NEW ELECTRICAL INFRASTRUCUTRE IS INSTALLED PER THE RISER DIAGRAM WITH THE EXCEPTION OF THE PERMANENT NORMAL FEEDER FROM PANEL MSB TO THE EXISTING ATS:
 - COORDINATE BUILDING OUTAGE WITH OWNER. THIS WILL INVOLVE MANUALLY SHUTTING OFF AND DISENGAGING BOTH GENERATORS ON SITE.**
 - DISCONNECT TEMPORARY DLO FEEDERS FROM ATS NORMAL LUGS
 - TERMINATE PERMANENT FEEDER FROM PANEL MSB ON ATS NORMAL LUGS
 - LOTO CAN BE REMOVED FROM MSB BREAKER SERVING THE ATS
 - LOTO CAN BE REMOVED FROM THE SE RATED DISCONNECT SWITCH
 - BUILDING IS NOW READY TO BE ENERGIZED VIA THE NEW ELECTRICAL SERVICE
 - RE-ENGAGE EXISTING ON-SITE GENERATOR TO ENSURE PROPER ATS OPERATION
- AT THIS POINT DURING THE SEQUENCE:
 - NEW MSB INSTALLED AND ENERGIZED
 - NEW UTILITY SERVICE ACTIVE AND ENERGIZED
 - ATS NORMAL IS SERVED VIA THE NEW MSB
 - TEMPORARY GENERATOR AND CABLING IS NO LONGER NEEDED
- REMOVE TEMPORARY GENERATOR AND DLO CABLING FROM THE SITE



GENERAL NOTES:

- REFER TO SEQUENCE OF CONSTRUCTION FOR FURTHER DETAILS.
- CONTRACTOR SHALL UTILIZE ALUMINUM (AL) FEEDERS UP TO NEW PANEL MSB. ALL OTHER CIRCUITS SHALL BE COPPER.

DEMOLITION KEYED NOTES:


- CONTRACTOR SHALL REMOVE KW METER FROM EXISTING PANEL MDP. METER WILL BE RELOCATED DURING NEW WORK. METER IS USED TO MONITOR BUILDING DEMAND FOR CAMPUS NETWORK. COORDINATE TIMING OF METER RELOCATION AND RECONNECTION TO THE CAMPUS BAS WITH THE OWNER AND BAS CONTRACTOR. DEMOLISH EXISTING CONTROL WIRING FROM PANEL MDP TO BAS PANEL. CAP AND SEAL CONDUIT ELBOW IN PANEL MDP.

1 ELECTRICAL DEMOLITION POWER RISER DIAGRAM

Scale: N.T.S.

NEW WORK KEYED NOTES:

- CONTRACTOR SHALL COORDINATE WEATHERHEAD LOCATION AND REQUIREMENTS WITH UTILITY PRIOR TO INSTALLATION.
- CONTRACTOR SHALL PROVIDE SPD FOR NEW PANEL MSB. INSTALL SPD PER MANUFACTURER'S GUIDELINES. INSTALL SPD AS NEAR TO MSB AS PRACTICAL.
- CONTRACTOR SHALL INSTALL NEW CT CABINET AND METERBASE. NEW CT CABINET AND METERBASE SHALL BE FURNISHED BY THE UTILITY COMPANY. COORDINATE CT CABINET AND METERBASE INSTALLATION WITH UTILITY COMPANY. UTILITY COMPANY TO PROVIDE SERVICE CONDUCTORS TO LINE SIDE OF CT CABINET. CONTRACTOR SHALL PROVIDE CONDUCTORS FROM LOAD SIDE OF CT CABINET TO SE RATED DISCONNECT.
- CONTRACTOR SHALL PROVIDE 1-1/2" CONTROLS CONDUIT FOR CHILLER. COORDINATE HEAD END LOCATION IN MECHANICAL ROOM 002 WITH DIVISION 23 CONTRACTOR. PROVIDE CONDUIT WITH PULLSTRING.
- CONTRACTOR SHALL INSTALL KW METER RETAINED DURING DEMOLITION IN NEW PANEL MSB. METER SHALL MONITOR AND REPORT BUILDING KW DEMAND. PROVIDE NEW CONTROL WIRING IN 1" C FROM NEW PANEL MSB TO NEW BAS PANEL. COORDINATE TIMING OF METER RELOCATION AND RECONNECTION OT THE CAMPUS BAS WITH THE OWNER AND BAS CONTRACTOR.
- CONTRACTOR SHALL PROVIDE BRANCH CIRCUITS AS SHOWN FROM NEW PANEL MSB TO ROOF FOR FUTURE AHU-1 FANS. TERMINATE FEEDERS ABOVE FIRST FLOOR ACT CEILING IN NEW JUNCTION BOX. CLEARLY LABEL JUNCTION BOXES AS FUTURE USE FOR AHU-1.
- CONTRACTOR SHALL PROVIDE BRANCH CIRCUITS AS SHOWN FROM NEW JUNCTION BOX ADJACENT TO EXISTING PANEL PA TO ABOVE FIRST FLOOR ACT CEILING FOR FUTURE AHU-1 ANCILLARY CIRCUITS. TERMINATE FEEDERS ON ROOF IN NEW JUNCTION BOX. CLEARLY LABEL JUNCTION BOX AS FUTURE USE FOR AHU-1 ANCILLARY CIRCUITS.
- CONTRACTOR SHALL LABEL DISCONNECT, ATS#1, AND MSB WITH ISC AND DATE OF CALCULATION. REFER TO SPECIFICATIONS FOR FURTHER INFORMATION.
- CONTRACTOR SHALL PROVIDE #4/0AL BONDING JUMPER BETWEEN SE GROUND BAR AND SE NEUTRAL BAR.



2 ELECTRICAL NEW WORK POWER RISER DIAGRAM

Scale: N.T.S.




Dewberry Engineers Inc.

9300 Harris Corners Parkway
Suite 220
Charlotte, NC 28269-3797
704.509.9918
NC License No. F-0929

DEB APPROVAL



SEAL



12/5/2025

KEY PLAN:

SCALE:

REVISIONS

NO.	DATE	BY	DESCRIPTION
2	12/05/25		DEB CMNTS/ADD 3
1	10/24/25		DEB COMMENTS

DRAWN BY _____ TLW
APPROVED BY _____ TLW
CHECKED BY _____ POA
DATE _____ JULY 25, 2025

TITLE
RISER DIAGRAMS

DEI PROJECT NO: 50188025
RADFORD PROJECT NO: 217-B5217-004

SHEET NO.

E9.01

**RADFORD UNIVERSITY
ALLEN BUILDING ELECTRICAL REPLACEMENT**

100% CONSTRUCTION DOCUMENTS

DATE – JULY 25, 2025

*REVISED OCTOBER 24, 2025**REVISED DECEMBER 5, 2025***PROCUREMENT AND CONTRACT DOCUMENTS**

DGS-30-256	Notice of Invitation for Bids
00 01 07	Seals Page
00 01 15	List of Drawing Sheets
CO-7	Commonwealth of Virginia General Conditions of the Construction Contract
CO-7a	Instructions to Bidders
**DGS-30-364	Submittal Register Format
**DGS-30-384	Vendor eVA Registration Requirements
	eVA Invoice Fee Codes – eVA Fee Schedule
DGS-30-272	Pre-Bid Question Form
DGS-30-220	Bid Form
DGS-30-326	Special Requirements for Low Slope Roofing Membranes
CO-10.2	Standard Bid Bond
**CO-9	Contract Between University and Contractor
**CO-9a	Workers Compensation Insurance Certificate
**CO-10	Standard Performance Bond
**CO-10.1	Standard Labor and Material Payment Bond
**CO-11	Change Order Blank
**GC-1	Change Order Estimate (General Contractors)
**SC-1	Change Order Estimate (Subcontractors)
**SS-1	Change Order Estimate (Sub-Subcontractors)
**CO-12	Schedule of Values and Certificate for Payment
**CO-13	Affidavit of Payment of Claims
**CO-13.1	Certificate of Completion by Architect/Engineer or Project Manager
**CO-13.1a	Architect/Engineer's Certificate of Substantial Completion
**CO-13.b	Final Report of Structural and Special Inspections
**CO-13.1c	Certificate of Partial or Substantial Completion by Agency Project Manager
**CO-13.1d	Final Report of Structural Observations
**CO-13.2	Certificate of Completion by Contractor
**CO-13.2a	Certificate of Partial or Substantial Completion by Contractor
CO-6b	2021 VUSCB Special Inspections & Structural Observations
	Prevailing Wage Determination

** Please see <https://dgs.virginia.gov/search/documents-and-forms/?filter=DEB>

TECHNICAL SPECIFICATIONS**Division 01 – General Conditions**

01 00 00	General Provisions
01 01 10	Summary of Work
01 01 40	Work Restrictions

01 01 80	Project Utility Sources
01 02 90	Payment Procedures
01 03 10	Project Management and Coordination
01 03 30	Submittal Procedures
01 04 30	Quality Assurance and Control
01 05 00	Temporary Facilities and Controls
01 05 10	Temporary Utilities
01 05 20	Construction Facilities
01 05 50	Vehicular Access and Parking
01 05 60	Temporary Barriers and Enclosures
01 07 00	Contract Closeout
01 07 20	Project Record Documents and Contractors As-builts
01 91 13	General Commissioning Requirements

Division 02 – Existing Conditions

02 41 19	Selective Demolition
----------	----------------------

Division 03 – Concrete

03 30 00	Cast-In-Place Concrete
----------	------------------------

Division 04 – Masonry

04 20 00	Unit Masonry
----------	--------------

Division 06 – Wood and Plastic Products

06 10 53	Miscellaneous Rough Carpentry
----------	-------------------------------

Division 07 – Roofing, Waterproofing, and Insulation

07 21 00	Thermal Insulation
07 53 23	Ethylene-Propylene-Diene-Monomer (EPDM) Roofing
07 62 00	Sheet Metal Flashing and Trim
07 84 13	Through Penetration Firestop Systems
07 84 43	Joint Firestopping
07 92 00	Joint Sealants

Division 08 – Windows and Doors

08 11 13	Hollow Metal Doors and Frames
08 31 13	Access Doors and Frames
08 71 00	Door Hardware

Division 09 – Finishes

09 22 16	Non-Structural Metal Framing
09 29 00	Gypsum Board
09 51 13	Acoustical Panel Ceilings
09 65 13	Resilient Base and Accessories
09 65 19	Resilient Tile Flooring
09 91 23	Interior Painting

Division 23 – Heating, Ventilation, and Air Conditioning

23 01 00	HVAC General Work Requirements
23 02 00	HVAC Systems Owner Training

23 03 00	HVAC Underground Utilities Work Requirements
23 05 11	HVAC Electrical Provisions
23 05 13	HVAC Equipment Motors
23 05 14	Variable Speed Controllers
23 05 16	Expansion Fittings and Loops
23 05 17	Sleeves and Sleeve Seals
23 05 19	Piping Instruments and Gages
23 05 29	Hangers and Supports
23 05 33	Heat Tracing
23 05 48	HVAC Seismic, Wind and Vibration Controls
23 05 53	HVAC Systems Identification
23 05 55	HVAC Piping Systems Flushing and Testing
23 05 93	Testing, Adjusting and Balancing
23 07 13	Duct and Ducted Equipment Insulation
23 07 19	Piping and Piped Equipment Insulation
23 08 00	HVAC Commissioning Requirements
23 11 26	Fuel Gas Piping
23 21 13	Hydronic Piping
23 21 16	Hydronic Piping Specialties
23 21 19	Hydronic Piping Valves
23 21 23	Hydronic Pumps
23 25 00	HVAC Water Treatment
23 31 13	Metal Ducts
23 33 00	Metal Duct Accessories
23 34 00	HVAC Fans
23 37 13	Diffusers, Grilles and Registers
23 51 00	Breechings, Chimneys and Stacks
23 52 16	Condensing Boilers
23 64 26	Air-Cooled Chillers
23 82 16	Air Coils
23 82 39	Unit Heaters
23 90 00	BAS General Requirements
23 90 10	BAS Instrumentation
23 90 20	BAS Field Controllers
23 90 30	BAS Network Level Controls
23 90 40	BAS Front-End Software and Hardware
23 92 10	Energy and Flow Meters

Division 26 – Electrical

26 01 00	Basic Electrical Requirements
26 05 00	Basic Electrical Materials and Methods
26 05 19	Conductors and Cables
26 05 26	Grounding and Bonding
26 05 29	Hangers and Supports
26 05 33	Raceway and Boxes
26 05 53	Identification for Electrical Systems
26 05 71	Power System Study
26 08 00	Electrical Commissioning Requirements
26 24 16	Panelboards
26 27 26	Wiring Devices
26 28 13	Fuses

26 28 16 Enclosed Switches and Circuit Breakers
26 51 00 Lighting

Division 31 – Earthwork

31 10 00 Site Preparation: Clearing and Grubbing
31 20 00 Earth Moving
31 23 19 Dewatering
31 25 00 Erosion and Sediment Control

Division 32 – Exterior Improvements

32 12 16 Asphalt Paving
32 13 13 Concrete Paving

Division 33 – Site Utilities

33 05 00 Earthwork for Utilities
33 05 26 Utility Location and Identification

HDHT Asbestos Inspection Report
HDHT Lead Inspection Report
UL Design

END OF SECTION 00 01 02

**NOTICE OF
INVITATION FOR BIDS (IFB)
Allen Building Electrical Replacement
Project Code 217-B5217-004**

Sealed bids are invited for the construction of **Allen Building Electrical Replacement**, Project Code 217-B5217-004, on the campus of Radford University, Radford, Virginia. The project is generally described as: Electrical improvements to include but not limited to, replacement of electrical service to the building, upgrade of heating system and installation of propane tanks.

Sealed bids will be received at Facilities Planning & Construction Office, Armstrong Complex, 501 Stockton Street, Radford, VA 24142. **The deadline for submitting bids is 2:00 P.M. sharp, as determined by the Bid Officer, on January 6, 2026.** The bids will be opened publicly and read aloud **beginning at 2:00 P.M., on January 7, 2026**, at the same location.

A Bid Bond is required.

eVA Vendor Registration: The bidder or offeror shall be a registered vendor in eVA. See the attached **eVA Vendor Registration Requirements**.

Procedures for submitting a bid, claiming an error, withdrawal of bids and other pertinent information are contained in the Instructions to Bidders, which is part of the Invitation for Bids. Withdrawal due to error in bid shall be permitted in accord with Section 9 of the Instructions to Bidders and § 2.2-4330, Code of Virginia. The Owner reserves the right to reject any or all bids.

A pre-bid conference will be held at the Facilities Planning & Construction Office, Armstrong Complex, 501 Stockton Street, Radford, VA 24142 at 10:00 a.m. on November 14, 2025. Attendance shall be optional for those submitting a bid.

All attendees to the pre-bid conference will be required to comply with Radford University Parking Regulations found at this web address: <https://www.radford.edu/parking/parking-information/index.html>
Attendees requesting Parking validation must email wlferguso@radford.edu 24 hours prior to pre-bid conference.

The contract shall be awarded on a lump sum basis as follows: the Total Base Bid Amount including any properly submitted and received bid modifications, if the Owner in its discretion decides to award in the manner set forth in Paragraph 12 of the Instructions to Bidders. **‘Notice of Award’ or ‘Notice of Intent to Award’ will be posted on eVA, Virginia Department of General Services’ central electronic procurement website, at <https://eva.virginia.gov>.**

Contractor registration is required in accordance with Section 54.1-1103 of the Code of Virginia. See the Invitation for Bids for additional qualification requirements.

All executive branch agencies are directed to advance Executive Order 35, dated July 3, 2019.

The Invitation for Bids for the above project, including the Drawings and the Specifications containing the information necessary for bidding, will be available for download from the eVA website at <https://eva.virginia.gov>.

Copies of the Invitation for Bids documents, including the plans and the specifications, will also be available for inspection at the following locations:

Facilities Planning & Construction Office: 501 Stockton St., Radford, VA 24142

Attachment: eVA Vendor Registration Requirements

SECTION 00 01 07 – SEALS PAGE

1.1 DESIGN PROFESSIONALS OF RECORD


ARCHITECT

Larry W. Hasson, Jr.
Virginia Architect License # 010298




STRUCTURAL
ENGINEER

William James Hamilton
Virginia Professional Engineer License # 0402059615




CIVIL
ENGINEER

Robert S. Notte
Virginia Professional Engineer License # 036367




ELECTRICAL
ENGINEER

Tyler Winokur
Virginia Professional Engineer License # 065927



MECHANICAL
ENGINEER

Scott W. Davis
Virginia Professional Engineer License # 062725



END OF SECTION 00 01 07

SECTION 23 05 48 – HVAC SEISMIC, WIND AND VIBRATION CONTROLS

PART 1 - GENERAL

1.1. SUMMARY

- A. Section includes seismic, wind and vibration control devices and related materials, including isolators, mounts, guides and supports.
- B. Description: Delegated design of all equipment and materials installed under Division 23.
 - 1. Seismic Bracing: Applies to all HVAC equipment and materials based on the seismic criteria defined in this section.
 - 2. Wind Restraints: Applies to all HVAC equipment and materials installed outdoors, above-grade.
 - 3. Vibration Isolation: Applies to all HVAC equipment and materials.

1.2. SUBMITTALS

- A. Delegated-Design Submittals: For each vibration isolation, wind restraint and seismic restraint device:
 - 1. Include design calculations and details for selecting vibration isolators, wind restraints, seismic restraints, and vibration isolation bases complying with performance requirements, design criteria, and analysis data signed and sealed by the qualified professional engineer (registered in the state of the project's location) responsible for their preparation.
 - 2. Design Calculations: Calculate static and dynamic loading due to equipment weight, operation, and seismic and wind forces required to select vibration isolators and seismic and wind restraints and for designing vibration isolation bases.
 - a. Coordinate design calculations with wind load calculations required for equipment mounted outdoors. Comply with requirements in other Sections for equipment mounted outdoors.
 - 3. Riser Supports: Include riser diagrams and calculations showing anticipated expansion and contraction at each support point, initial and final loads on building structure, spring deflection changes, and seismic loads. Include certification that riser system was examined for excessive stress and that none exists.
 - 4. Seismic and Wind Restraint Details:
 - a. Design Analysis: To support selection and arrangement of seismic and wind restraints. Include calculations of combined tensile and shear loads.
 - b. Details: Indicate fabrication and arrangement. Detail attachments of restraints to the restrained items and to the structure. Show attachment locations, methods and spacings. Identify components, list their strengths, and indicate directions and values

of forces transmitted to the structure during seismic events. Indicate association with vibration isolation devices.

- c. Coordinate seismic-restraint and vibration isolation details with wind-restraint details required for equipment mounted outdoors. Comply with requirements in other Sections for equipment mounted outdoors.

B. Product Submittals: For each type of product indicated.

- 1. Include rated load, rated deflection, and overload capacity for each vibration isolation device.
- 2. Illustrate and indicate style, material, strength, fastening provision, and finish for each type and size of vibration isolation, wind restraint and seismic restraint device required.

1.3. QUALITY ASSURANCE

- A. Testing Agency Qualifications: An independent agency, with the experience and capability to conduct the testing indicated, that is an NRTL as defined by OSHA in 29 CFR 1910.7 and that is acceptable to authorities having jurisdiction.
- B. Comply with seismic-restraint requirements in the Virginia Construction Code unless requirements in this Section are more stringent.
- C. Welding Qualifications: Qualify procedures and personnel according to AWS D1.1/D1.1M, "Structural Welding Code - Steel."
- D. Seismic-restraint devices shall have horizontal and vertical load testing and analysis and shall bear anchorage preapproval OPA number from OSHPD, preapproval by an agency acceptable to authorities having jurisdiction, showing maximum seismic-restraint ratings. Ratings based on independent testing are preferred to ratings based on calculations. If preapproved ratings are unavailable, submittals based on independent testing are preferred. Calculations (including combining shear and tensile loads) to support seismic-restraint designs must be signed and sealed by a qualified professional engineer.

PART 2 - PRODUCTS

2.1. MANUFACTURERS

- A. Manufacturers: Subject to compliance with requirements, provide product by one of the following for spring and elastomeric isolators:
 - 1. Mason Industries, Inc.
 - 2. Kinetics Noise Control, Inc.
 - 3. Vibration Eliminator Company, Inc.
 - 4. Vibration Mounting & Controls (VMC) Group, Inc.

2.2. PERFORMANCE REQUIREMENTS

- A. Wind-Restraint Loading:
1. Ultimate Wind Speed: 120 MPH.
 2. Building Risk Category: IV.
 3. Minimum 50 lb/sq. ft. multiplied by maximum area of HVAC component projected on vertical plane normal to wind direction, and 45 degrees either side of normal.
- B. Seismic-Restraint Loading:
1. Site Class as Defined in the State Building Code: D (Assumed).
 2. Seismic Design Category: C.
 3. Assigned Risk Category as Defined in the State Building Code: IV.
 - a. Component Importance Factor of 1.5:
 - 1) Smoke Control Systems including Make-Up Air Systems
 - 2) Life-Safety Dampers
 - 3) Natural Gas, Propane (LP) Gas, and Fuel Oil Piping Systems
 - 4) Carbon Monoxide Detection and Alarm Systems
 - 5) Fuel-Fired Equipment Chimneys and Breechings
 - 6) HVAC Systems in First Responder Facilities (Law Enforcement, EMT, Fire, Rescue and 911 Emergency Call Centers)
 - b. Component Importance Factor of 1.0: All other systems and their components.
 - c. Component Response Modification Factor: Table 13.6-1, ~~ASCE 7-16~~ ASCE/SEI-22 - Chapter 13.
 - d. Component Amplification Factor: Table 13.6-1, ~~ASCE 7-16~~ ASCE/SEI 7-22 - Chapter 13.
 4. Design Spectral Response Acceleration at Short Periods (0.2 Second): 0.258.
 5. Design Spectral Response Acceleration at 1.0-Second Period: 0.113.
 6. Structural Safety Factor: Allowable strength in tension, shear, and pullout force of components shall be at least four times the maximum seismic forces to which they are subjected.
- C. Seismic Performance: HVAC equipment shall withstand the effects of earthquake motions determined according to ~~ASCE/SEI-16~~ ASCE/SEI-22. The term “withstand” means the unit will remain in place without separation of any parts from the device when subjected to the seismic forces specified.
- D. Critical Functions: In addition, the following equipment and systems shall be fully operational after the seismic event:

1. Computer room air-conditioners serving data centers and emergency communications equipment.

2.3. ELASTOMERIC ISOLATION PADS

A. Description: Elastomeric Isolation Pads.

1. Fabrication: Single or multiple layers of sufficient durometer stiffness for uniform loading over pad area.
2. Size: Factory or field cut to match requirements of supported equipment.
3. Pad Material: Oil and water resistant with elastomeric properties.
4. Surface Pattern: Waffle pattern.
5. Infused nonwoven cotton or synthetic fibers.
6. Load-bearing metal plates adhered to pads.
7. Sandwich-Core Material: Resilient and elastomeric.
 - a. Surface Pattern: Waffle pattern.
 - b. Infused nonwoven cotton or synthetic fibers.

2.4. ELASTOMERIC ISOLATION MOUNTS

A. Description: Double-Deflection, Elastomeric Isolation Mounts.

1. Mounting Plates:
 - a. Top Plate: Encapsulated steel load transfer top plates, factory drilled and threaded with threaded studs or bolts.
 - b. Baseplate: Encapsulated steel bottom plates with holes provided for anchoring to support structure.
2. Elastomeric Material: Molded, oil-resistant rubber, neoprene, or other elastomeric material.

2.5. RESTRAINED ELASTOMERIC ISOLATION MOUNTS

- ### A. Description: All-directional isolator with seismic restraints containing two separate and opposing elastomeric elements that prevent central threaded element and attachment hardware from contacting the housing during normal operation.
1. Housing: Cast-ductile iron or welded steel.
 2. Elastomeric Material: Molded, oil-resistant rubber, neoprene, or other elastomeric material.

2.6. OPEN SPRING ISOLATORS

A. Description: Freestanding, Laterally Stable, Open-Spring Isolators.

1. Outside Spring Diameter: Not less than 80 percent of the compressed height of the spring at rated load.
2. Minimum Additional Travel: 50 percent of the required deflection at rated load.
3. Lateral Stiffness: More than 80 percent of rated vertical stiffness.
4. Overload Capacity: Support 200 percent of rated load, fully compressed, without deformation or failure.
5. Baseplates: Factory-drilled steel plate for bolting to structure with an elastomeric isolator pad attached to the underside. Baseplates shall limit floor load to 500 psig.
6. Top Plate and Adjustment Bolt: Threaded top plate with adjustment bolt and cap screw to fasten and level equipment.

2.7. HOUSED SPRING ISOLATORS

- A. Description: Freestanding, Laterally Stable, Open-Spring Isolators in Two-Part Telescoping Housing.
 1. Outside Spring Diameter: Not less than 80 percent of the compressed height of the spring at rated load.
 2. Minimum Additional Travel: 50 percent of the required deflection at rated load.
 3. Lateral Stiffness: More than 80 percent of rated vertical stiffness.
 4. Overload Capacity: Support 200 percent of rated load, fully compressed, without deformation or failure.
 5. Two-Part Telescoping Housing: A steel top and bottom frame separated by an elastomeric material and enclosing the spring isolators.
 - a. Drilled base housing for bolting to structure with an elastomeric isolator pad attached to the underside. Bases shall limit floor load to 500 psig.

2.8. RESTRAINED SPRING ISOLATORS

- A. Description: Freestanding, Laterally Stable, Open-Spring Isolators with Vertical-Limit Stop Restraint.
 1. Housing: Steel housing with vertical-limit stops to prevent spring extension due to weight being removed.
 - a. Base with holes for bolting to structure with an elastomeric isolator pad attached to the underside. Bases shall limit floor load to 500 psig.
 - b. Top plate with threaded mounting holes or elastomeric pad.
 - c. Internal leveling bolt that acts as blocking during installation.
 2. Restraint: Limit stop as required for equipment and authorities having jurisdiction.

3. Outside Spring Diameter: Not less than 80 percent of the compressed height of the spring at rated load.
4. Minimum Additional Travel: 50 percent of the required deflection at rated load.
5. Lateral Stiffness: More than 80 percent of rated vertical stiffness.
6. Overload Capacity: Support 200 percent of rated load, fully compressed, without deformation or failure.

2.9. HOUSED RESTRAINED SPRING ISOLATORS

- A. Description: Freestanding, Steel, Open-Spring Isolators with Vertical-Limit Stop Restraint in Two-Part Telescoping Housing.
 1. Two-Part Telescoping Housing: A steel top and bottom frame separated by an elastomeric material and enclosing the spring isolators. Housings are equipped with adjustable snubbers to limit vertical movement.
 - a. Drilled base housing for bolting to structure with an elastomeric isolator pad attached to the underside. Bases shall limit floor load to 500 psig.
 - b. Threaded top housing with adjustment bolt and cap screw to fasten and level equipment.
 2. Outside Spring Diameter: Not less than 80 percent of the compressed height of the spring at rated load.
 3. Minimum Additional Travel: 50 percent of the required deflection at rated load.
 4. Lateral Stiffness: More than 80 percent of rated vertical stiffness.
 5. Overload Capacity: Support 200 percent of rated load, fully compressed, without deformation or failure.

2.10. PIPE RISER RESILIENT SUPPORTS

- A. Description: All-directional, acoustical pipe anchor consisting of two steel tubes separated by a minimum 1/2-inch thick neoprene.
 1. Vertical-Limit Stops: Steel and neoprene vertical-limit stops arranged to prevent vertical travel in both directions.
 2. Maximum Load Per Support: 500 psig on isolation material providing equal isolation in all directions.

2.11. RESILIENT PIPE GUIDES

- A. Description: Telescopic arrangement of two steel tubes or post and sleeve arrangement separated by a minimum 1/2-inch-thick neoprene.
 1. Factory-Set Height Guide with Shear Pin: Shear pin shall be removable and re-insertable to allow for selection of pipe movement. Guides shall be capable of motion to meet location requirements.

2.12. ELASTOMERIC HANGERS

- A. Description: Elastomeric Mount in a Steel Frame with Upper and Lower Steel Hanger Rods.
 - 1. Frame: Steel, fabricated with a connection for an upper threaded hanger rod and an opening on the underside to allow for a maximum of 30 degrees of angular lower hanger-rod misalignment without binding or reducing isolation efficiency.
 - 2. Dampening Element: Molded, oil-resistant rubber, neoprene, or other elastomeric material with a projecting bushing for the underside opening preventing steel to steel contact.

2.13. SPRING HANGERS

- A. Description: Combination Coil-Spring and Elastomeric-Insert Hanger with Spring and Insert in Compression.
 - 1. Frame: Steel, fabricated for connection to threaded hanger rods and to allow for a maximum of 30 degrees of angular hanger-rod misalignment without binding or reducing isolation efficiency.
 - 2. Outside Spring Diameter: Not less than 80 percent of the compressed height of the spring at rated load.
 - 3. Minimum Additional Travel: 50 percent of the required deflection at rated load.
 - 4. Lateral Stiffness: More than 80 percent of rated vertical stiffness.
 - 5. Overload Capacity: Support 200 percent of rated load, fully compressed, without deformation or failure.
 - 6. Elastomeric Element: Molded, oil-resistant rubber or neoprene. Steel-washer-reinforced cup to support spring and bushing projecting through bottom of frame.
 - 7. Adjustable Vertical Stop: Steel washer with neoprene washer "up-stop" on lower threaded rod.
 - 8. Self-centering hanger-rod cap to ensure concentricity between hanger rod and support spring coil.

2.14. SNUBBERS

- A. Description: Factory fabricated using welded structural-steel shapes and plates, anchor bolts, and replaceable resilient isolation washers and bushings.
 - 1. Anchor bolts for attaching to concrete shall be seismic-rated, drill-in, and stud-wedge or female-wedge type.
 - 2. Resilient Isolation Washers and Bushings: Oil- and water-resistant neoprene.
 - 3. Maximum 1/4-inch air gap, and minimum 1/4-inch-thick resilient cushion.

2.15. RESTRAINT CHANNEL BRACINGS

- A. Description: MFMA-4, shop- or field-fabricated bracing assembly made of slotted steel channels with accessories for attachment to braced component at one end and to building structure at the other end and other matching components and with corrosion-resistant coating; rated in tension, compression, and torsion forces.

2.16. RESTRAINT CABLES

- A. Restraint Cables: ASTM A 492 stainless-steel cables. End connections made of steel assemblies with thimbles, brackets, swivel, and bolts designed for restraining cable service; with a minimum of two clamping bolts for cable engagement.

2.17. SEISMIC RESTRAINT ACCESSORIES

- A. Hanger-Rod Stiffener: Steel tube or steel slotted-support-system sleeve with internally bolted connections to hanger rod.
- B. Hinged and Swivel Brace Attachments: Multifunctional steel connectors for attaching hangers to rigid channel bracings and restraint cables.
- C. Bushings for Floor-Mounted Equipment Anchor Bolts: Neoprene bushings designed for rigid equipment mountings and matched to type and size of anchor bolts and studs.
- D. Bushing Assemblies for Wall-Mounted Equipment Anchorage: Assemblies of neoprene elements and steel sleeves designed for rigid equipment mountings and matched to type and size of attachment devices used.
- E. Resilient Isolation Washers and Bushings: One-piece, molded, oil- and water-resistant neoprene, with a flat washer face.

2.18. MECHANICAL ANCHOR BOLTS

- A. Mechanical Anchor Bolts: Drilled-in and stud-wedge or female-wedge type in zinc-coated steel for interior applications and stainless steel for exterior applications. Select anchor bolts with strength required for anchor and as tested according to ASTM E 488.

2.19. ADHESIVE ANCHOR BOLTS

- A. Adhesive Anchor Bolts: Drilled-in and capsule anchor system containing PVC or urethane methacrylate-based resin and accelerator, or injected polymer or hybrid mortar adhesive. Provide anchor bolts and hardware with zinc-coated steel for interior applications and stainless steel for exterior applications. Select anchor bolts with strength required for anchor and as tested according to ASTM E 488.

PART 3 - EXECUTION

3.1. EXAMINATION

- A. Examine areas and equipment to receive vibration isolation and seismic and wind control devices for compliance with requirements for installation tolerances and other conditions affecting performance of the Work.

- B. Examine roughing-in of reinforcement and cast-in-place anchors to verify actual locations before installation.
- C. Proceed with installation only after unsatisfactory conditions have been corrected.

3.2. APPLICATIONS

- A. Multiple Pipe Supports: Secure pipes to trapeze member with clamps approved for application.
- B. Hanger-Rod Stiffeners: Install hanger-rod stiffeners where indicated or scheduled on Drawings to receive them and where required to prevent buckling of hanger rods due to seismic forces.
- C. Strength of Support and Seismic-Restraint Assemblies: Where not indicated, select sizes of components so strength is adequate to carry present and future static and seismic loads within specified loading limits.
- D. Vibration Isolation: In addition to vibration isolation devices indicated within the project documents, provide isolators per ASHRAE Handbook – “HVAC Applications”, Chapter 49, Table 47 “Selection Guide for Vibration Isolation”.
 - 1. Install vibration isolators on all vibrating equipment.
 - 2. Suspended Piping: Install vibration isolation hangers in all mechanical equipment rooms and on all piping within 50 feet of vibrating equipment connections.
 - a. Three hangers closest to each equipment connection shall be rated for deflection equal to the equipment isolator deflection.
 - b. The remaining hangers shall have a deflection of 3/4-inch.
 - c. Exceptions: Not required at terminal equipment connections where the equipment is isolated, such as terminal units, blower coil units, fan coil units and heaters.

3.3. CONTROL AND RESTRAINT DEVICE INSTALLATION

- A. Coordinate the location of embedded connection hardware with supported equipment attachment and mounting points and with requirements for concrete reinforcement and formwork.
- B. Installation of vibration isolators must not cause any change of position of equipment, piping, or ductwork resulting in stresses or misalignment.
- C. Equipment Restraints:
 - 1. Install seismic snubbers on HVAC equipment mounted on vibration isolators. Locate snubbers as close as possible to vibration isolators and bolt to equipment base and supporting structure.
 - 2. Install resilient bolt isolation washers on equipment anchor bolts where clearance between anchor and adjacent surface exceeds 0.125 inch.
 - 3. Install seismic-restraint devices.

D. Piping Restraints:

1. Comply with requirements in MSS SP-127.
2. Space lateral supports a maximum of 40 feet o.c., and longitudinal supports a maximum of 80 feet o.c.
3. Brace a change of direction longer than 12 feet.

E. Install cables so they do not bend across edges of adjacent equipment or building structure.

F. Install bushing assemblies for anchor bolts for floor-mounted equipment, arranged to provide resilient media between anchor bolt and mounting hole in concrete base.

G. Install bushing assemblies for mounting bolts for wall-mounted equipment, arranged to provide resilient media where equipment or equipment-mounting channels are attached to wall.

H. Attachment to Structure: If specific attachment is not indicated, anchor bracing to structure at flanges of beams, at upper truss chords of bar joists, or at concrete members.

I. Drilled-in Anchors:

1. Identify position of reinforcing steel and other embedded items prior to drilling holes for anchors. Do not damage existing reinforcing or embedded items during coring or drilling. Notify the structural engineer if reinforcing steel or other embedded items are encountered during drilling. Locate and avoid pre-stressed tendons, electrical and telecommunications conduit, and gas lines.
2. Do not drill holes in concrete or masonry until concrete, mortar, or grout has achieved full design strength.
3. Wedge Anchors: Protect threads from damage during anchor installation. Heavy-duty sleeve anchors shall be installed with sleeve fully engaged in the structural element to which anchor is to be fastened.
4. Adhesive Anchors: Clean holes to remove loose material and drilling dust prior to installation of adhesive. Place adhesive in holes proceeding from the bottom of the hole and progressing toward the surface in such a manner as to avoid introduction of air pockets in the adhesive.
5. Set anchors to manufacturer's recommended torque, using a torque wrench.
6. Install zinc-coated steel anchors for interior and stainless-steel anchors for exterior applications.

3.4. ACCOMODATION OF DIFFERENTIAL SEISMIC MOTION

- A. Install flexible connections in piping where they cross seismic joints, where adjacent sections or branches are supported by different structural elements, and where the connections terminate with connection to equipment that is anchored to a different structural element from the one supporting the connections as they approach equipment. Comply with requirements in Section 232113 for piping flexible connections.

3.5. FIELD QUALITY CONTROL

A. Perform tests and inspections:

1. Provide evidence of recent calibration of test equipment by a testing agency acceptable to authorities having jurisdiction.
2. Schedule test with Owner, through Architect, before connecting anchorage device to restrained component (unless post-connection testing has been approved), and with at least seven days' advance notice.
3. Obtain Architect's approval before transmitting test loads to structure. Provide temporary load-spreading members.
4. Test at least four of each type and size of installed anchors and fasteners selected by Engineer.
5. Test to 90 percent of rated proof load of device.
6. Measure isolator restraint clearance.
7. Measure isolator deflection.
8. Verify snubber minimum clearances.

B. Remove and replace malfunctioning units and retest as specified above.

C. Prepare test and inspection reports.

3.6. ADJUSTING

A. Adjust isolators after piping system is at operating weight.

B. Adjust limit stops on restrained-spring isolators to mount equipment at normal operating height. After equipment installation is complete, adjust limit stops so they are out of contact during normal operation.

END OF SECTION 230548

SECTION 260526 - GROUNDING AND BONDING

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes methods and materials for grounding systems and equipment.

1.3 SUBMITTALS

- A. Product Data: For each type of product indicated.
- B. Field quality-control test reports.

1.4 QUALITY ASSURANCE

- A. Electrical Components, Devices, and Accessories: Listed and labeled as defined in NFPA 70, Article 100, by a testing agency acceptable to authorities having jurisdiction, and marked for intended use.
- B. Comply with UL 467 for grounding and bonding materials and equipment.

PART 2 - PRODUCTS

2.1 CONDUCTORS

- A. Insulated Conductors: Copper wire or cable insulated for 600 V unless otherwise required by applicable Code or authorities having jurisdiction.
- B. Bare Copper Conductors:
 - 1. Solid Conductors: ASTM B 3.
 - 2. Stranded Conductors: ASTM B 8.
 - 3. Bonding Cable: stranded conductor sized per NEC 250 requirements.
 - 4. Bonding Conductor: stranded conductor sized per NEC 250 requirements.
 - 5. Bonding Jumper: Copper tape, braided conductors, terminated with copper ferrules; sized per NEC 250 requirements.

- C. Grounding Bus: Rectangular bars of annealed copper, 1/4 by 2 inches (6 by 50 mm) in cross section, unless otherwise indicated; with insulators and stand-off brackets.

2.2 CONNECTORS

- A. Listed and labeled by a nationally recognized testing laboratory acceptable to authorities having jurisdiction for applications in which used, and for specific types, sizes, and combinations of conductors and other items connected.
- B. Bolted Connectors for Conductors and Pipes: Copper or copper alloy, bolted pressure-type, with at least two bolts.
 - 1. Pipe Connectors: Clamp type, sized for pipe.
- C. Welded Connectors: Exothermic-welding kits of types recommended by kit manufacturer for materials being joined and installation conditions.

2.3 GROUNDING ELECTRODES

- A. Ground Rods: Copper-clad steel; 3/4 inch by 10 feet (19 mm by 3 m) in diameter.

PART 3 - EXECUTION

3.1 APPLICATIONS

- A. Conductors: Install solid conductor for No. 10 AWG and smaller, and stranded conductors for No. 8 AWG and larger, unless otherwise indicated.
- B. Underground Grounding Conductors: Install bare copper conductor, No. 3/0 AWG minimum. Bury at least 24 inches (600 mm) below grade.
- C. Conductor Terminations and Connections:
 - 1. Pipe and Equipment Grounding Conductor Terminations: Bolted connectors.
 - 2. Underground Connections: Welded connectors.
 - 3. Connections to Structural Steel: Welded connectors.

3.2 EQUIPMENT GROUNDING

- A. Install insulated equipment grounding conductors with all feeders and branch circuits. The raceway shall not be relied on for ground continuity.

3.3 INSTALLATION

- A. Grounding Conductors: Route along shortest and straightest paths possible, unless otherwise indicated or required by Code. Avoid obstructing access or placing conductors where they may be subjected to strain, impact, or damage.
- B. Ground Rods: Drive rods until tops are 6 inches (50 mm) below finished floor or final grade, unless otherwise indicated.
 - 1. Interconnect ground rods with grounding electrode conductor below grade and as otherwise indicated. Make connections without exposing steel or damaging coating, if any.
 - 2. Use exothermic welds for all below-grade connections.
- C. Bonding Straps and Jumpers: Install in locations accessible for inspection and maintenance, except where routed through short lengths of conduit.
 - 1. Bonding to Structure: Bond straps directly to basic structure, taking care not to penetrate any adjacent parts.
 - 2. Bonding to Equipment Mounted on Vibration Isolation Hangers and Supports: Install so vibration is not transmitted to rigidly mounted equipment.
 - 3. Provide exothermic-welded connection to building structural steel.
 - 4. Use exothermic-welded connectors for outdoor locations, but if a disconnect-type connection is required, use a bolted clamp.
- D. Grounding Bushings and Jumpers: Boxes provided with concentric, eccentric or over-sized knockouts shall be provided with bonding bushings and jumpers lugged to box.

3.4 FIELD QUALITY CONTROL

- A. Perform the following tests and inspections and prepare test reports:
 - 1. After installing grounding system but before permanent electrical circuits have been energized, test for compliance with requirements.
- B. Testing Technician
 - 1. The testing technicians shall be trained in all the methods of correctly and safely conducting the required test. The technician shall have regular experience conducting the required tests and they must have the knowledge to determine the serviceability of a specific piece of equipment.
- C. Physical Inspection and Testing
 - 1. Inspect grounding system to verify that it complies with the requirements in the drawings and specifications, as well as, NFPA 70 *National Electric Code Article 250*.
 - 2. Inspect the physical and mechanical condition and verify that it complies with manufacturer's standards. All portions of the grounding system shall be free of corrosion.
 - 3. Confirm bolted electrical connections are provided with low impedance using one of the following means:


- a. Measure the resistance with a low-resistance ohmmeter. Bolted electrical connection resistances shall be compared to resistances measured on similar connections. Any similar resistance values that deviate more than 50 percent should be investigated.
 - b. Inspect the bolted connection and verify that it is at the manufacturer's rated torque using a calibrated torque wrench.
4. Verify that adequate anchorage is in place for the grounding system.
- D. Electrical Inspection and Testing
 1. Conduct tests for fall of potential as defined by ANSI/IEEE 81 on the grounding system.
 2. Determine the resistance to ground throughout grounding system including equipment frames, systems neutral, and equipment grounding bars. Measure ground resistance not less than two full days after last trace of precipitation and without soil being moistened by any means other than natural drainage or seepage and without chemical treatment or other artificial means of reducing natural ground resistance. Perform ground resistance in all of, but not limited to, the areas listed below:
 - a. Main electrical distribution ground bar: 15 ohms
 - b. Main telecommunications ground bar: 15 ohms
 - c. Secondary telecommunications ground bars: 15 ohms
 - ~~d. Lightning protection path to ground: 5 ohms~~
- E. Excessive Ground Resistance: If resistance to ground exceeds specified values, notify Engineer promptly and include recommendations to reduce ground resistance.
 1. Retest required to show compliance with above value.
- F. Remove and replace malfunctioning units and retest as specified above.
- G. Test Reports: Prepare a written report to record the following:
 1. Test procedures used.
 2. Test results that comply with requirements.
 3. Test results that do not comply with requirements and corrective action taken to achieve compliance with requirements.

END OF SECTION 260526

System No. C-AJ-5061

March 14, 2017

ANSI/UL1479 (ASTM E814)	CAN/ULC S115
F Rating — 3 Hr	F Rating — 3 Hr
T Rating — 1/2Hr	FT Rating — 1/2 Hr
	FH Rating — 3 Hr
	FTH Rating — 1/2 Hr



1. **Floor or Wall Assembly** — Min 4-1/2 in. (114 mm) thick reinforced lightweight or normal weight (100-150 pcf or 1600-2400 kg/m³) concrete. Wall may also be constructed of any UL Classified **Concrete Blocks***. Max diam of opening is 30 in. (762 mm). See **Concrete Blocks** (CAZT) category in the Fire Resistance Directory for names of manufacturers.

2. **Metallic Sleeve** — (Optional) — Nom 30 in. (762 mm) diam (or smaller) Schedule 10 (or heavier) steel pipe, conduit or EMT cast or grouted into floor or wall assembly, flush with floor or wall surfaces.

3. **Through Penetrants** — One metallic pipe or tubing to be either concentrically or eccentrically within the firestop system. Pipe or tube to be rigidly supported on both sides of floor or wall assembly. The following types and sizes of metallic pipes or tubing may be used:

A. **Steel Pipe** — Nom 20 in. (508 mm) diam (or smaller) Schedule 10 (or heavier) steel pipe.

B. **Iron Pipe** — Nom 20 in. (508 mm) diam (or smaller) cast or ductile iron pipe.

C. **Copper Tubing** — Nom 6 in. (152 mm) diam (or smaller) Type L (or heavier) copper tubing.

D. **Copper Pipe** — Nom 6 in. (152 mm) diam (or smaller) Regular (or heavier) copper pipe.

4. **Pipe Covering** — Max 3 in. (76 mm) thick hollow cylindrical heavy density (min 3.5 pcf or 56 kg/m³) glass fiber units jacketed on the outside with an all service jacket. Longitudinal joints sealed with metal fasteners or factory-applied self-sealing lap tape. Transverse joints secured with metal fasteners or with butt tape supplied with the product. Pipe covering to terminate 6 in. (152 mm) from each side of floor or wall assembly.

See **Pipe and Equipment Covering — Materials** (BRGU) category in the Building Materials Directory for names of manufacturers. Any pipe covering material meeting the above specifications and bearing the UL Classification Marking with a Flame Spread Index of 25 or less and a Smoke Developed Index of 50 or less may be used.

5. **Firestop System** — The firestop system shall consist of the following:

A. **Pipe Covering Materials*** — Nom 3 in. (76 mm) thick unfaced mineral fiber pipe insulation having a nom density of 5 pcf (80 kg/m³) (or heavier) sized to the outside diam of pipe or tube and extending min 6 in. (152 mm) beyond each surface of floor or wall. Pipe insulation secured with min 18 AWG steel wire 3 in. (76 mm) beyond each surface of floor or wall. The annular space shall be min 1/4 in. (6 mm) to max of 3 in. (76 mm), or when steel sleeve is used, min 1 in. (25 mm) to max 2-1/4 in. (57 mm).

See **Pipe and Equipment Covering — Materials** (BRGU) category in the Building Materials Directory for names of manufacturers. Any pipe covering material meeting the above specification and bearing the UL Classification Marking with a Flame Spread Index of 25 or less and a Smoke Developed Index of 50 or less may be used.

B. **Sheathing Material*** — All service jacket material shall be wrapped around the outer circumference of the pipe covering material (Item 5A) with kraft facing exposed. Longitudinal joints sealed with metal fasteners.

See **Sheathing Material** (BVDV) category in the Building Materials Directory for names of manufacturers. Any sheathing material meeting the above specifications and bearing the UL Classification Marking with a Flame Spread Index of 25 or less and a Smoke Developed Index of 50 or less may be used.

C. **Packing Material** — Min 3 in. (76 mm) thickness of min 4 pcf (64 kg/m³) mineral wool batt insulation firmly packed into opening as a permanent form. Packing material to be recessed from top surface of floor or from both surfaces of wall as required to accommodate the required thickness of fill material.

D. **Fill, Void or Cavity Material* — Sealant** — Min 3/4 in. (19 mm) thickness of fill material applied within the annulus, flush with top surface of floor or with both surfaces of wall.

HILTI CONSTRUCTION CHEMICALS, DIV OF HILTI INC — FS-One Sealant or FS-ONE MAX Intumescent Sealant


*** Indicates such products shall bear the UL or cUL Certification Mark for jurisdictions employing the UL or cUL Certification (such as Canada), respectively.**

Last Updated on 2017-03-14

System No. W-L-1164

January 22, 2015

ANSI/UL1479 (ASTM E814)	CAN/ULC S115
F Ratings — 1 and 2 Hr (See Item 1 and 4)	F Ratings — 1 and 2 Hr (See Items 1 and 4)
T Rating — 0 Hr	FT Rating — 0 Hr
	FH Ratings — 1 and 2 Hr (See Items 1 and 4)
	FTH Rating — 0 Hr



1. Wall Assembly — The 1 or 2 hr fire-rated gypsum wallboard/stud wall assembly shall be constructed of the materials and in the manner described in the individual U300, U400, V400 or W400 Series Wall or Partition Design in the UL Fire Resistance Directory and shall include the following construction features:

A. Studs — Wall framing may consist of either wood studs or steel channel studs. Wood studs to consist of nom 2 by 4 in. (51 by 102 mm) lumber spaced 16 in. (406 mm) OC. Steel studs to be min 2-1/2 in. (64 mm) wide and spaced max 24 in. (610 mm) OC. When steel studs are used and the diam of opening exceeds the width of stud cavity, the opening shall be framed on all sides using lengths of steel stud installed between the vertical studs and screw-attached to the steel studs at each end. The framed opening in the wall shall be 4 to 6 in. (102 to 152 mm) wider and 4 to 6 in. (102 to 152 mm) higher than the diam of the penetrating item such that, when the penetrating item is installed in the opening, a 2 to 3 in. (51 to 76 mm) clearance is present between the penetrating item and the framing on all four sides.

B. Gypsum Board* — The gypsum wallboard type, thickness, number of layers, fastener type and sheet orientation shall be as specified in the individual Wall and Partition Design. Max diam of opening in steel stud walls is 32 in. (813 mm). Max diam of openings in wood stud walls is 14-1/2 in. (368 mm).

The hourly F, FH Ratings of the firestop system are equal to the hourly fire rating of the wall assembly in which it is installed.

2. **Steel Sleeve** — Nom 32 in. (813 mm) diam (or smaller) Schedule 40 (or heavier) steel pipe sleeve friction fit in nom 32 in. (813 mm) diam circular opening cut through gypsum board layers. Length of steel sleeve to be equal to thickness of wall.

3. **Through-Penetrant** — One metallic pipe, conduit or tubing installed either concentrically or eccentrically within the firestop system. The annular space between pipe, conduit or tubing and the steel sleeve shall be min of 0 in. (point contact) to max 1-7/8 in. (48 mm) Pipe, conduit or tubing to be rigidly supported on both sides of wall assembly. The following types and sizes of metallic pipes, conduits or tubing may be used:

A. **Steel Pipe** — Nom 30 in. (762 mm) diam (or smaller) Schedule 10 (or heavier) steel pipe.

B. **Iron Pipe** — Nom 30 in. (762 mm) diam (or smaller) service weight (or heavier) cast iron soil pipe or Class 50 (or heavier) ductile iron pressure pipe.

C. **Conduit** — Nom 4 in. (102 mm) diam (or smaller) steel electrical metallic tubing.

D. **Copper Tubing** — Nom 6 in. (152 mm) diam (or smaller) Type L (or heavier) copper tubing.

E. **Copper Pipe** — Nom 6 in. (152 mm) diam (or smaller) Regular (or heavier) copper pipe.

4. **Fill, Void or Cavity Material*-Sealant** — Min 5/8 in. (16 mm) and 1-1/4 in. (32 mm) thickness of fill material applied within annulus, flush with both surfaces of wall assembly for 1 or 2 hr rated walls, respectively. Min 1/2 in. (13 mm) diam bead of caulk applied to the penetrant/gypsumboard interface at the point contact location on both sides of wall.

HILTI CONSTRUCTION CHEMICALS, DIV OF HILTI INC — FS-ONE Sealant or FS-ONE MAX Intumescent Sealant


*** Indicates such products shall bear the UL or cUL Certification Mark for jurisdictions employing the UL or cUL Certification (such as Canada), respectively.**

Last Updated on 2015-01-22

System No. W-L-5046

December 21, 2017

ANSI/UL1479 (ASTM E814)	CAN/ULC S115
F Rating — 1 & 2 Hr (See Item 6)	F Rating — 1 & 2 Hr (See Item 6)
T Rating — 0 & 1 Hr (See Item 4)	FT Rating — 0 & 1 Hr (See Item 4)
	FH Rating — 1 & 2 Hr (See Item 6)
	FTH Rating — 0 & 1 Hr (See Item 4)



1. **Wall Assembly** — The fire-rated gypsum wallboard/stud wall assembly shall be constructed of the materials and in the manner specified in the individual U300, U400, V400 or W400 Series Wall and Partition Designs in the UL Fire Resistance Directory and shall include the following construction features:

A. **Studs** — Wall framing may consist of either wood studs or steel channel studs. Wood studs to consist of nom 2 by 4 in. (51 by 102 mm) lumber spaced 16 in. (406 mm) OC. Steel studs to be min 2-1/2 in. (64 mm) wide and spaced max 24 in. (610 mm) OC.

B. **Gypsum Board*** — Nom 5/8 in. (16 mm) thick gypsum wallboard, as specified in the individual Wall and Partition Design. Max diam of opening is 14-1/2 in. (368 mm) for wood stud walls and 22 in. (559 mm) for steel stud walls.

2. **Metallic Sleeve** — Nom 22 in. (559 mm) diam (or smaller) Schedule 40 (or thinner) steel pipe cast into wall assembly with joint compound and installed flush with wall surfaces.

3. **Through Penetrants** — One metallic pipe or tubing to be positioned within the firestop system. Pipe or tubing to be rigidly supported on both sides of wall assembly. The annular space shall be min 3/4 in. (19 mm) to max 3 in. (76 mm). The following types and sizes of metallic pipes or tubing may be used:

A. **Steel Pipe** — Nom 12 in. (305 mm) diam (or smaller) Schedule 40 (or heavier) steel pipe.

B. **Copper Tubing** — Nom 6 in. (152 mm) diam (or smaller) Type L (or heavier) copper tubing.

C. **Copper Pipe** — Nom 6 in. (152 mm) diam (or smaller) Regular (or heavier) copper pipe.

4. **Pipe Covering Materials* — Cellular Glass Insulation** — Nom 1-1/2 in. (38 mm) or 3 in. (76 mm) thick cellular glass pipe insulation sized to the outside diam of the steel pipe or tube and installed in accordance with the manufacturer's instructions. T Rating is 0 hr when nom 1-1/2 in. (38 mm) thick pipe insulation is used in 1 hr and 2 hr fire-rated wall assembly. T Rating is 0 hr when nom 3 in. (76 mm) thick pipe insulation is used in 1 hr fire-rated wall assembly. T Rating is 1 hr when nom 3 in. (76 mm) thick pipe insulation is used in 2 hr fire-rated wall assembly.

5. **Metal Jacket (Optional)** — Min 12 in. (305 mm) long jacket formed of min 0.010 in. (.254 mm) thick steel or aluminum sheet cut to wrap tightly around the pipe insulation with a min 2 in. (51 mm) lap. Jacket secured with min 1/2 in. (13 mm) wide stainless steel hose clamps or bands located within 2 in. (51 mm) of each end of the jacket and spaced a max of 10 in. (254 mm) OC. Jacket to be installed with abutting surface of sealant (Item 6B) on both surfaces of wall. Metal jacket to be used in addition to any other jacketing material which may be required or desired on the pipe insulation.

6. **Firestop System** — Installed symmetrically on both sides of the wall. **The hourly F Rating of the firestop system is equal to the hourly fire rating of the wall assembly in which it is installed.**

A. **Packing Material** — Min 2-1/4 or 3-1/2 in. (57 to 89 mm) thickness of min 4.0 pcf (64 kg/m³) mineral wool batt insulation firmly packed into opening as a permanent form for 1 or 2 hr walls, respectively. Packing material to be recessed from both surfaces of wall as required to accommodate the required thickness of fill material.

B. **Fill, Void or Cavity Material* — Sealant** — Min 3/4 in. (19 mm) thickness of fill material applied within the annulus, flush with both surfaces of the wall.

HILTI CONSTRUCTION CHEMICALS, DIV OF HILTI INC — FS-ONE MAX Intumescent Sealant

*** Indicates such products shall bear the UL or cUL Certification Mark for jurisdictions employing the UL or cUL Certification (such as Canada), respectively.**

Last Updated on 2017-12-21