STRUCTURES, FACILITIES AND EQUIPMENT DURING CONSTRUCTION.

4. DRAWINGS ARE DIAGRAMMATIC; THEREFORE, DETERMINE EXACT LOCATIONS OF SYSTEMS AND COMPONENTS IN THE

5. ALL NEW BUILDING PENETRATIONS SHALL BE FLASHED AND SEALED PER THE SPECIFICATION REQUIREMENTS. 6. LOCATE ALL EQUIPMENT TO ENSURE ACCESS TO FILTERS, CONTROL PANEL CABINETS AND MAINTENANCE

CLEARANCES AS INDICATED BY MANUFACTURER. 7. THIS CONTRACTOR IS RESPONSIBLE FOR LOCATION AND COORDINATION OF ALL APPLICABLE BELOW AND ABOVE

GROUND UTILITIES, PIPING AND EQUIPMENT. 8. THIS CONTRACTOR IS RESPONSIBLE FOR THE PROTECTION AND CLEANLINESS OF EXISTING AND ADJACENT

9. MAINTAINING DESIRED SYSTEM OPERATION IS TOP PRIORITY THROUGH ALL PHASES. SYSTEM SHUT-DOWNS FOR NEW PIPING, ELECTRICAL AND EQUIPMENT CONNECTIONS MUST BE COORDINATED AND APPROVED BY THE BUILDING OWNER. STRICT ADHERENCE IS REQUIRED FOR ALL TIMELINES AND DEADLINES SET BY OWNER AND CONSTRUCTION ADMINISTRATOR.

10. ALL WORK SHALL BE PERFORMED IN A NEAT, PROFESSIONAL AND SAFE MANNER, AND SHALL COMPLY WITH LOCAL, STATE AND NATIONAL CODES.

11. DURING CONSTRUCTION, ALL PIPING SHALL BE SEALED ON THE ENDS TO PREVENT DUST AND DEBRIS FROM ENTERING THE PIPING BETWEEN PHASES. SEALING SHALL INVOLVE A PLASTIC FILM COVERING WITH AN ELASTIC BAND TO

12. CONTRACTOR IS RESPONSIBLE FOR COORDINATING THE INSTALLATION OF ALL NEW EQUIPMENT, DUCTWORK AND PIPING REQUIRED PRIOR TO THE DEMOLITION AND REMOVAL OF EXISTING.

13. AT ALL TIMES, THIS CONTRACTOR SHALL BE SOLELY RESPONSIBLE FOR THE CONDITIONS OF THE JOBSITE, INCLUDING MEANS AND METHODS OF CONSTRUCTION AND SAFETY OF PERSONS AND PROPERTY. GENERAL HOUSEKEEPING OF ALL JOB SITE AREAS SHALL BE PERFORMED DAILY.

14. REFER TO CONTRACT SCOPE DOCUMENTS FOR ADDITIONAL INFORMATION AND SCOPE DEFINITION. PRIME CONTRACTOR'S BID SHALL PROVIDE COMPLETE AND WORKABLE SYSTEM.

15. NEW DUCTWORK THAT IS TO BE TIED INTO EXISTING DUCTWORK SHALL BE OF THE SAME SIZE AS THE EXISTING DUCT IN WHICH IT IS BEING CONNECTED. UNLESS NOTED OTHERWISE.

GENERAL DEMOLITION NOTES

1. ALL PIPING, FITTINGS, HANGERS, EQUIPMENT, APPURTENANCES, AND SUPPORTS MADE OBSOLETE BY THIS PROJECT SHALL BE REMOVED AND LEGALLY DISCARDED OFF SITE. THIS CONTRACTOR IS RESPONSIBLE FOR PROVIDING THE MEANS OF DISPOSAL – ALL METAL SHALL BE SEPARATED AND RECYCLED.

2. THIS CONTRACTOR SHALL BE RESONSIBLE FOR ALL REMOVALS REQUIRED FOR THE INSTALLATION OF NEW WORK, WHETHER OR NOT IT IS SPECIFICALLY INDICATED OR NOTED IN THESE DOCUMENTS.

3. ON DEMOLITION DRAWINGS, ALL EQUIPMENT AND PIPING SHOWN BOLD, DASHED, HATCHED OR MARKED WITH AN "X" SHALL BE REMOVED. REFER TO SPECIFIC DEMOLITION NOTES FOR ADDITIONAL DETAILS.

4. ALL DUCTWORK, FITTINGS, HANGERS, EQUIPMENT, APPURTENANCES, SUPPORTS AND CONCRETE PADS MADE OBSOLETE BY THIS PROJECT SHALL BE REMOVED AND LEGALLY DISCARDED OFF SITE.

5. GENERAL TRADES CONTRACTOR IS RESPONSIBLE FOR PATCHING AND SEALING ALL FLOOR AND EXTERIOR WALL

PENETRATIONS ABANDONED DUE TO DEMOLITION OF DUCT, PIPE OR EQUIPMENT. 6. REFER TO ARCHITECTURAL, ELECTRICAL AND STRUCTURAL DRAWINGS FOR ADDITIONAL INFORMATION RELATED TO

7. EVACUATE AND DISPOSE OF ALL REFRIGERANTS PER LOCAL, STATE AND FEDERAL CODES AND PROCEDURES PRIOR TO DEMOLITION OF ANY EQUIPMENT CONTAINING REFRIGERANTS.

GENERAL MECHANICAL NOTES

MECHANICAL AND PLUMBING EQUIPMENT DEMOLITION.

ALL DUCTWORK, PIPING AND EQUIPMENT SHALL BE IDENTIFIED PER THE SPECIFICATIONS.

2. CONTRACTOR SHALL COORDINATE WORK WITH ALL OTHER TRADES. LOCATE ALL DUCTWORK, PIPING, AND EQUIPMENT AS TO MAINTAIN ACCESS TO FILTERS, CONTROL CABINETS AND MECHANICAL EQUIPMENT.

3. SEE ARCHITECTURAL DRAWINGS FOR GRAPHIC SYMBOL EXPLANATION OF FIRE RATINGS. PROVIDE THROUGH PENETRATION FIRE STOP SYSTEMS FOR RATED WALL PENETRATIONS. SEE SPECIFICATIONS SECTION 078413 FOR

4. REFER TO ARCHITECTURAL REFLECTED CEILING PLAN FOR FINAL DIFFUSER LOCATIONS. COORDINATE ANY CONFLICTS WITH THE ARCHITECT.

5. FURNISH CEILING AND WALL ACCESS PANELS FOR ACCESS TO ALL CONCEALED DEVICES FOR INSTALLATION BY THE GENERAL TRADES CONTRACTOR.

6. WORK SCOPE INCLUDES BALANCING OF ALL AIR SYSTEM TO CFM'S INDICATED ON THE PLANS.

7. WORK SCOPE INCLUDES BALANCING OF ALL WATER SYSTEMS TO GPM'S INDICATED ON THE PLANS.

8. COORDINATE LOCATIONS OF TEMPERATURE SENSORS AND/OR THERMOSTATS WITH ALL ELECTRICAL SWITCHES AND OCCUPANCY SENSORS. MOUNT ALL SENSORS AND/OR THERMOSTATS AT 48" AFF. MOUNTING HEIGHT IS TO CENTERLINE.

GENERAL HVAC NOTES

AMBIENT OA TEMP, RH, PRESSURE AND CO2 SENSOR LOCATIONS SHALL BE APPROVED BY ENGINEER.

COORDINATE LOCATIONS OF THERMOSTATS OR TEMPERATURE SENSORS WITH OCCUPANCY SENSORS. WORK SCOPE INCLUDES PROVIDING EXTERNAL INSULATION FOR ALL SUPPLY, RETURN, OUTDOOR.

TRANSFER AND RELIEF AIR DUCTS. REFER TO SPECIFICATIONS FOR INSULATION REQUIREMENTS.

PROVIDE FIRE DAMPERS AT ALL PENETRATIONS OF 2-HOUR RATED ASSEMBLIES AND FIRE DAMPERS FOR TRANSFER OPENINGS ONLY THRU 1 HOUR RATED ASSEMBLIES.

FITTINGS NOT ACCEPTABLE. SEE DETAILS.

HIGH-EFFICIENCY BRANCH CONNECTIONS TO VAV AND FPB TERMINAL UNITS ARE REQUIRED. SPIN-IN

PROVIDE INTERNALLY LINED DUCTWORK AS NOTED ON PLANS. SEAL AND SECURE ALL EDGES OF LINER EXPOSED TO AIR STREAM. DIMENSIONS SHOWN ARE INSIDE CLEAR DIMENSIONS, ADJUST CONSTRUCTED SHEETMETAL DIMENSIONS ACCORDINGLY.

7. NO NEW EQUIPMENT, DUCTWORK, PIPING, ACCESSORIES, OR WIRING SHALL BE INSTALLED AND SUPPORTED BY OR HUNG FROM ANY COMPONENTS OF THE FIRE PROTECTION SYSTEM.

ALL DUCTWORK TERMINATING WITHIN A SPACE, NOT INDICATED TO HAVE A GRILLE OR TO BE CAPPED, SHALL BE TERMINATED WITH A METAL FRAME AND 1/2" x 1/2" WIRE MESH APPROVED BY ENGINEER.

PROVIDE DUCT MOUNTED MANUAL VOLUME DAMPER FOR EACH DIFFUSER (U.N.O.). LOCATE DAMPER AS FAR FROM DIFFUSER AS POSSIBLE WHILE ENSURING DAMPER ACCESSIBILITY. DAMPERS NOT REQUIRED FOR DIFFUSERS SERVED BY DEDICATED VAV BOXES.

WHEN ORDERING DIFFUSERS, REGISTERS AND GRILLES, REFER TO THE ARCHITECTURAL DRAWINGS TO

OBTAIN THE APPROPRIATE FRAMES. 11. INSTALL DUCT SMOKE DETECTORS FURNISHED BY DIVISION 26.

ALL PUBLIC SPACE THERMOSTATS AND CO2 SENSORS SHALL BE PROVIDED WITH A CLEAR, LOCKABLE

PROVIDE ACCOUSTICAL SEALANT ON ALL DUCTS, PIPES, ETC. THAT PENETRATE ACCOUSTICALLY RATED

GENERAL PIPING NOTES

WORK SCOPE INCLUDES BALANCING ALL WATER SYSTEMS TO THE GPM VALUES INDICATED ON THE PLANS.

WORK SCOPE INCLUDES PROVIDING INSULATION FOR ALL CHILLED WATER AND HEATING WATER ABOVEGROUND AND UNDERGROUND PIPING. REFER TO SPECIFICATIONS FOR INSULATION REQUIREMENTS.

ALL EXTERIOR CONDENSER WATER SUPPLY, RETURN AND EQUALIZER PIPING SHALL BE PROVIDED WITH HEAT TRACE AND INSULATION. REFER TO SPECIFICATIONS FOR DETAILS.

REFRIGERANT PIPING SHALL BE TYPE "ACR" COPPER WITH BRAZED JOINTS OR PRE-MANUFACTURED, PRE-

INSULATED COPPER TUBE REFRIGERANT LINESETS WITH BRAZED JOINTS OR BRASS FITTINGS. SIZE, ROUTE AND INSTALL ALL REFRIGERANT PIPING PER THE MANUFACTURER'S WRITTEN RECOMMENDATIONS AND REQUIREMENTS.

ALL REFRIGERANT PIPING SHALL BE INSULATED WITH ELASTOMERIC FOAM INSULATION - SEE SPECIFICATIONS. OUTDOOR, EXPOSED, ELASTOMERIC REFRIGERANT PIPING INSULATION SHALL HAVE TWO COATS OF UV-PROTECTANT COATING APPLIED.

CONDENSATE DRAIN PIPING

REFRIGERANT PIPING

ALL CONDENSATE DRAIN PIPING SHALL BE TYPE DWV COPPER PITCHED AT MIN. 1%.

TRAP ALL AIR HANDLING UNIT CONDENSATE PIPING AS SHOWN IN THE MECHANICAL DETAILS.

EXISTING CEILING NOTES

1. SOME CEILINGS ARE EXISTING; WORK SHALL BE PERFORMED THROUGH EXISTING CEILING.

2. REMOVE EXISTING LAY-IN CEILING TILES AS REQUIRED TO PERFORM WORK, STORE TILES IN MANAGED LOCATION AND REPLACE TILES IN SAME LOCATION. MARK BACK SIDE OF TILES AS NECESSARY FOR REPLACEMENT.

3. DISCONNECT AND REMOVE EXISTING LIGHTS AS REQUIRED TO PERFORM WORK, STORE LIGHTS IN MANAGED LOCATION AND REPLACE LIGHTS IN SAME LOCATION. MARK BACK OF LIGHTS AS NECESSARY

4. CONTRACTOR IS RESPONSIBLE FOR REPLACING ANY DAMAGED CEILING TILES WITH PRODUCT TO MATCH

5. CONTRACTOR IS RESPONSIBLE FOR REMOVING AND REPLACING EXISTING CEILING GRID IF REMOVAL OF CEILING GRID IS NECESSARY TO PERFORM WORK. REPLACE ANY REMOVED CEILING GRID WITH PRODUCT TO MATCH EXISTING.

DUCT SYMBOLS LEGEND

DUCT SIZE, FIRST FIGURE IS SIDE SHOWN EXISTING DUCTWORK TO REMAIN EXISTING DUCTWORK TO BE REMOVED CHANGE OF ELEVATION, INCLINED FLEXIBLE DUCT

CONCENTRIC TRANSITION ECCENTRIC TRANSITION

INTERNALLY LINED DUCTWORK //32x16/// SUPPLY DIFFUSER RETURN GRILLE


EXHAUST GRILLE SQUARE THROAT ELBOW WITH

TURNING VANES

RADIUS ELBOW

RECTANGULAR/ROUND BRANCH TAKE-OFF OR ROUND/ROUND BRANCH TAKE-OFF

STANDARD TEE




MOTOR OPERATED DAMPER




CEILING RETURN


CEILING EXHAUST




AD - ACCESS DOORS, VERTICAL OR HORIZONTAL



FLEXIBLE CONNECTION



CHANGE IN ELEVATION, VERTICAL



100 CFM DIFFUSER/GRILLE AIRFLOW

AIR TERMINAL / DIFFUSER TAG

NOTE: SOME SYMBOLS SHOWN ON THIS LEGEND MAY NOT PERTAIN TO THIS PROJECT

HVAC SYMBOLS LEGEND TEMPERATURE GAUGE BALL VALVE BYPASS MODULATING CONTROL VALVE 2-POSITION ISOLATION VALVE PRESSURE GAUGE UNION FLEX CONNECTION PRESSURE REDUCING VALVE AUTOMATIC AIR VENT STRAINER PRESSURE & TEMPERATURE PORT CHECK VALVE BFV - BUTTERFLY VALVE TEMPERATURE SENSOR FIRE DAMPER THERMOSTAT +48" AFF (UNLESS NOTED OTHERWISE) THERMOSTAT FOR RADIANT CEILING PANEL (RCP) **SENSOR**

HUMIDISTAT CARBON DIOXIDE DETECTOR CARBON MONOXIDE DETECTOR

1 HOUR FIRE RATED WALL ASSEMBLY 2 HOUR FIRE RATED WALL ASSEMBLY PARTITION TO RESIST THE PASSAGE OF SMOKE

EQUIPMENT ON ROOF ABOVE FINISHED FLOOR AIR HANDLING UNIT AIR FLOW MONITORING STATION

BALANCING DAMPER BYPASS DAMPER CARBON DIOXIDE

DOWN DEDICATED OUTDOOR AIR SYSTEM

DOOR GRILLE EXHAUST FAN **EXHAUST**

EXISTING WHEN USED AS PREFIX FAN COIL UNIT


INTAKE HOOD INDOOR UNIT, OUTDOOR UNIT #1-INDOOR UNIT #9 KITCHEN EXHAUST FAN

KITCHEN SUPPLY FAN LOUVER MOTOR OPERATED DAMPER OUTSIDE AIR OUTDOOR UNIT - UNIT NUMBER

RELIEF HOOD RETURN AIR RELIEF AIR REHEAT COIL PACKAGED ROOFTOP UNIT

SUPPLY AIR TOP OF DUCT TRANSFER AIR VARIABLE FREQUENCY DRIVER WIRE MESH SCREEN

NOTE: SOME SYMBOLS SHOWN ON THIS LEGEND MAY NOT PERTAIN TO THIS PROJECT



OVAL/ROUND

RADIUS ELBOW

SMOOTH OR 5 GORE (MINIMUM)

R/W = 1.5 (MINIMUM)

RECTANGULAR

MITERED ELBOW

TYPE RE6

OFFSETS ABOVE 30° SHALL BE TYPE RE

3. DEFAULT ELBOW SHALL BE "RE1".


1. BEAD, CROSSBREAK, AND REINFORCE FLAT SURFACES AS IN STRAIGHT DUCT.


4. ELBOW TYPES SHALL BE INSTALLED AS SHOWN AND NOT BE SUBSTITUTED WITHOUT PERMISSION. EXCEPTION: RE1 OR RE3 MAY BE SUBSTITUTED FOR RE2.


2. REFER TO SPECIFICATIONS FOR ADDITIONAL INFORMATION.


USE ONLY AS POINT OF OFFSETS

AND TRANSITIONS PER FIGURE 4-7 TYPE 2 OR AS SHOWN ON DRAWING










WITHOUT VANES

TYPE RE4

NOT ALLOWED





RECTANGULAR


RADIUS ELBOW WITH VANES

TYPE RE3

REFER TO SMACNA HVAC SYSTEMS DUCT DESIGN

MANUAL. FOURTH EDITION, SECTION 5.14 "SPLITTER VANES" AND SMACNA HVAC DUCT CONSTRUCTION

CHARTS 4-1 AND 4-1M. ELBOW SHALL HAVE THREE SPLITTER VANES AND r/W = 0.10 (R/W = 0.60) UNLESS




2 ELBOW CONSTRUCTION


RECTANGULAR

MITERED ELBOW

WITH VANES TYPE RE2







ELBOW-NO EXCEPTIONS

BRANCH ENTRY-WELDING EXHAUST-NO EXCEPTIONS

BRANCH ENTRY-DUST COLLECTION-NO EXCEPTIONS

C.L.R.

PIPING SYMBOLS LEGEND

AIR COOLED CHILLER

CENTER LINE (PIPE)

EXPANSION TANK

HOT WATER SUPPLY

HOT WATER RETURN

WATER PUMP

ELBOW UP

TEE UP

TEE DOWN

PIPE REDUCER

GAS REGULATOR

GAS METER

BALL VALVE

CO - CLEAN OUT

TIE INTO EXISTING

NOTE: SOME SYMBOLS SHOWN ON THIS LEGEND MAY NOT PERTAIN TO THIS PROJECT

POINT OF DISCONNECT

ELBOW DOWN

 $\overline{}$

 \longrightarrow

—<u>C</u>—

 \rightarrow

MOTORIZED CONTROL VALVE

UNIT HEATER (HOT WATER)

CHILLED WATER SUPPLY

CHILLED WATER RETURN

DIFFERENTIAL PRESSURE SENSOR

AIR SEPARATOR

BOILER

CHILLER

CHILLER


BALL VALVE





REDUCING STRAIGHT LATERAL

TAPERED BODY LATERAL









(c) by ZMM, INC. **HVAC SYMBOLS, LEGEND AND GENERAL NOTES**

> CHECKED 07/07/2023 COMM. NO.



2022088

AREA 'A'


KEY PLAN

NOT TO SCALE

- DISCONNECT AND REMOVE EXISTING FAN COIL UNIT AND PORTIONS OF DUCTWORK AS INDICATED. COORDINATE WITH E.C.
 REMOVE PORTIONS OF DUCTWORK AS INDICATED BACK TO ROOF MOUNTED EQUIPMENT.
- 3 SUPPORT EXISTING AIR DEVICE TO BE REINSTALLED IN NEW CEILING GRID.

222 Lee Street, West Charleston, West Virginia 25302 Phone: 304.342.0159 Fax: 304.345.8144


www.zmm.com




FIRST FLOOR PLAN AREA 'A' -**HVAC DUCT DEMOLITION**

07/07/2023

COMM. NO. **2022088** M111a








- DISCONNECT AND REMOVE EXISTING FAN COIL UNIT AND PORTIONS OF DUCTWORK AS INDICATED. COORDINATE WITH E.C.
 REMOVE PORTIONS OF DUCTWORK AS INDICATED BACK TO ROOF MOUNTED EQUIPMENT.
- 3 SUPPORT EXISTING AIR DEVICE TO BE REINSTALLED IN NEW CEILING GRID.

KEY PLAN

NOT TO SCALE



www.zmm.com



	DATE						
REVISIONS	DESCRIPTION						

FIRST FLOOR

PLAN AREA 'B' -**HVAC DUCT DEMOLITION**

07/07/2023 2022088

M111b

- 1 DISCONNECT AND REMOVE EXISTING FAN COIL UNIT AND PORTIONS OF DUCTWORK AS INDICATED. COORDINATE WITH E.C.
- 2 DISCONNECT AND REMOVE EXISTING FAN COIL UNIT AND ALL ASSOCIATED DUCTWORK, AIR DEVICES, AND ACCESSORIES AS INDICATED. COORDINATE WITH
- 3 REMOVE PORTIONS OF DUCTWORK AS INDICATED BACK TO ROOF MOUNTED EQUIPMENT.
- 4 REMOVE EXISTING DUCTWORK, AIR DEVICES, AND ACCESSORIES.
- 5 SUPPORT EXISTING AIR DEVICE TO BE REINSTALLED IN NEW CEILING GRID.

222 Lee Street, West Charleston, West Virginia 25302 Phone: 304.342.0159 Fax: 304.345.8144

www.zmm.com

	DATE					
NS NS	NO					
REVISIONS	DESCRIPTION					
	٥					
	Ñ.					


© by ZMM, INC.

FIRST FLOOR PLAN AREA 'C' -**HVAC DUCT DEMOLITION**

07/07/2023


COMM. NO. 2022088 M111c






FIRST FLOOR PLAN AREA 'C' - HVAC DUCTWORK DEMOLITION

1/8" = 1'-0"






FIRST FLOOR PLAN AREA 'D' - HVAC DUCTWORK DEMOLITION

KEYED NOTES

- 1 DISCONNECT AND REMOVE EXISTING FAN COIL UNIT AND ALL ASSOCIATED DUCTWORK AS INDICATED. COORDINATE WITH E.C.
- 2 DISCONNECT AND REMOVE EXISTING FAN COIL UNIT AND ALL ASSOCIATED DUCTWORK, AIR DEVICES, AND ACCESSORIES AS INDICATED. COORDINATE WITH
- 3 REMOVE DUCTWORK AS INDICATED BACK TO ROOF MOUNTED EQUIPMENT.
- REMOVE EXISTING DUCTWORK, AIR DEVICES, AND ACCESSORIES. REMOVE PORTIONS OF DUCTWORK AS INDICATED BACK TO ROOF MOUNTED
- 6 SUPPORT EXISTING AIR DEVICE TO BE REINSTALLED IN NEW CEILING GRID.

222 Lee Street, West Charleston, West Virginia 25302 Phone: 304.342.0159 Fax: 304.345.8144

www.zmm.com




	DATE						
6	z						
REVISIONS	DESCRIPTION						
	DE						
	Ö.						

FIRST FLOOR PLAN AREA 'D' -**HVAC DUCT DEMOLITION**

07/07/2023 COMM. NO. 2022088

M111d



- 1 DISCONNECT AND REMOVE EXISTING FAN COIL UNIT AND PORTIONS OF DUCTWORK AS INDICATED. COORDINATE WITH E.C.
- 2 REMOVE PORTIONS OF DUCTWORK AS INDICATED BACK TO ROOF MOUNTED EQUIPMENT.
- 3 SUPPORT EXISTING AIR DEVICE TO BE REINSTALLED IN NEW CEILING GRID.



www.zmm.com



	DATE						
S	NO						
REVISIONS	DESCRIPTION						
	Ö.						


SECOND FLOOR PLAN - HVAC DUCT **DEMOLITION**

SAO

07/07/2023 COMM. NO. 2022088

M112

	AREA 'B'		
AREA 'A'		AREA 'C'	
	AREA 'D'		
EY PLAN			
OT TO SCALE			




SECOND FLOOR PLAN - HVAC DUCTWORK DEMOLITION

1/8" = 1'-0"

- 1 REMOVE EXISTING ROOF MOUNTED HEAT EXCHANGER. COORDINATE WITH E.C. 2 REMOVE EXISTING PACKAGED ROOFTOP UNIT, AND PORTIONS OF GAS PIPING
- FOR INSTALLATION OF NEW UNIT. COORDINATE WITH E.C. AND P.C.
- 3 REMOVE EXISTING ROOF MOUNTED AIR COOLED CONDENSER. COORDINATE WITH



222 Lee Street, West Charleston, West Virginia 25302 Phone: 304.342.0159 Fax: 304.345.8144 www.zmm.com




	DATE			
SNOI	NOIL			
REVISIONS	DESCRIPTION			

ROOF PLAN -HVAC DEMOLITION

07/07/2023 COMM. NO. 2022088

M113



AREA 'A'

KEY PLAN

NOT TO SCALE

1 DISCONNECT AND REMOVE FAN COIL UNIT, PORTIONS OF HYDRONIC PIPING AND PORTIONS OF CONDENSATE PIPING AS INDICATED, AND ASSOCIATED CONTROLS. COORDINATE WITH E.C.


222 Lee Street, West Charleston, West Virginia 25302 Phone: 304.342.0159 Fax: 304.345.8144




FIRST FLOOR PLAN AREA 'A' -**HVAC PIPING DEMOLITION**

07/07/2023 COMM. NO. **2022088**

M121a







KEY PLAN

NOT TO SCALE

DISCONNECT AND REMOVE FAN COIL UNIT, PORTIONS OF HYDRONIC PIPING AND PORTIONS OF CONDENSATE PIPING AS INDICATED, AND ASSOCIATED CONTROLS. COORDINATE WITH E.C.



www.zmm.com



	DATE					
REVISIONS	PTION					
REVIS	DESCRIPTION					
	ON					

FIRST FLOOR PLAN AREA 'B' -**HVAC PIPING DEMOLITION**

2022088

07/07/2023

M121b

KEY PLAN

NOT TO SCALE

1 DISCONNECT AND REMOVE FAN COIL UNIT, PORTIONS OF HYDRONIC PIPING AND PORTIONS OF CONDENSATE PIPING AS INDICATED, AND ASSOCIATED CONTROLS. COORDINATE WITH E.C.




www.zmm.com

FIRST FLOOR PLAN AREA 'C' -**HVAC PIPING DEMOLITION**

07/07/2023 COMM. NO. 2022088

M121c





FIRST FLOOR PLAN AREA 'C' - HVAC PIPING DEMOLITION

1/8" = 1'-0"



KEY PLAN

NOT TO SCALE

1 DISCONNECT AND REMOVE FAN COIL UNIT, PORTIONS OF HYDRONIC PIPING AND PORTIONS OF CONDENSATE PIPING AS INDICATED, AND ASSOCIATED CONTROLS. COORDINATE WITH E.C.




www.zmm.com

FIRST FLOOR PLAN AREA 'D' -**HVAC PIPING DEMOLITION**

COMM. NO. **2022088**

07/07/2023

M121d



1 DISCONNECT AND REMOVE FAN COIL UNIT, PORTIONS OF HYDRONIC PIPING AND PORTIONS OF CONDENSATE PIPING AS INDICATED, AND ASSOCIATED CONTROLS. COORDINATE WITH E.C.



www.zmm.com

	DATE						
SNC	NOI						
REVISIONS	DESCRIPTION						
	Ö.						

SCHOOL


SECOND FLOOR PLAN - HVAC **PIPING**

DEMOLITION

SAO 07/07/2023 COMM. NO. 2022088


M122





SECOND FLOOR PLAN - HVAC PIPING DEMOLITION

1/8" = 1'-0"



AREA 'A'


KEY PLAN


NOT TO SCALE

- REALIGN AIR DEVICE INTO NEW CEILING GRID.
 24" X 14" OA DUCT UP TO DOAS-5 ON ROOF. TRANSITION DUCT AS REQUIRED AT CONNECTION TO UNIT.
 28" X 16" EA DUCT UP TO DOAS-5 ON ROOF. TRANSITION DUCT AS REQUIRED AT CONNECTION TO UNIT.



www.zmm.com






FIRST FLOOR PLAN - AREA 'A' -**HVAC DUCTWORK**

COMM. NO. **2022088**

M131a

07/07/2023



FIRST FLOOR PLAN AREA 'B' - HVAC DUCTWORK





- 1 REALIGN AIR DEVICE INTO NEW CEILING GRID.
- 2 16" X 14" OA DUCT UP TO DOAS-1 ON ROOF. TRANSITION DUCT AS REQUIRED AT CONNECTION TO UNIT.
- 3 14" X 12" EA DUCT UP TO DOAS-1 ON ROOF. TRANSITION DUCT AS REQUIRED AT CONNECTION TO UNIT.
- CONNECTION TO UNIT.

 32" X 14" OA DUCT UP TO DOAS-2 ON ROOF. TRANSITION DUCT AS REQUIRED AT
- CONNECTION TO UNIT.

 28" X 16" EA DUCT UP TO DOAS-2 ON ROOF. TRANSITION DUCT AS REQUIRED AT CONNECTION TO UNIT.
- 6 32" X 14" OA DUCT UP TO DOAS-3 ON ROOF. TRANSITION DUCT AS REQUIRED AT CONNECTION TO UNIT.
- 28" X 12" EA DUCT UP TO DOAS-3 ON ROOF. TRANSITION DUCT AS REQUIRED AT CONNECTION TO UNIT.
 26" X 14" OA DUCT UP TO DOAS-4 ON ROOF. TRANSITION DUCT AS REQUIRED AT
- CONNECTION TO UNIT.

 9 28" X 16" EA DUCT UP TO DOAS-4 ON ROOF. TRANSITION DUCT AS REQUIRED AT
- CONNECTION TO UNIT.

 10 24" X 12" SA DUCT UP TO RTU-1 ON ROOF. TRANSITION DUCT AS REQUIRED AT
- CONNECTION TO UNIT.
- 11 26" X 14" EA DUCT UP TO RTU-1 ON ROOF. TRANSITION DUCT AS REQUIRED AT CONNECTION TO UNIT.



222 Lee Street, West Charleston, West Virginia 25302 Phone: 304.342.0159 Fax: 304.345.8144

www.zmm.com



	DATE			
REVISIONS	DESCRIPTION			
	Ö			

/MIDDLE SCHOOL HOOLS IA

RISBURG, VIRGINIA

PEARISBURG

FIRST FLOOR
PLAN - AREA 'B' HVAC
DUCTWORK

DRAWN
SAO

CHECKED

JAP


DATE

07/07/2023

M131b

Z


2022088



AREA 'A'

KEY PLAN

NOT TO SCALE



FIRST FLOOR PLAN AREA 'C' - HVAC DUCTWORK

1/8" = 1'-0"



1 REALIGN AIR DEVICE INTO NEW CEILING GRID.

AREA 'A'

KEY PLAN


NOT TO SCALE

- 2 24" X 16" OA DUCT UP TO DOAS-8 ON ROOF. TRANSITION DUCT AS REQUIRED AT CONNECTION TO UNIT.
- 3 28" X 16" EA DUCT UP TO DOAS-8 ON ROOF. TRANSITION DUCT AS REQUIRED AT CONNECTION TO UNIT.
- 4 42" X 14" SA DUCT UP TO RTU-2 ON ROOF. TRANSITION DUCT AS REQUIRED AT CONNECTION TO UNIT.
- 5 46" X 14" RA DUCT UP TO RTU-2 ON ROOF. TRANSITION DUCT AS REQUIRED AT CONNECTION TO UNIT.
- 6 22" X 14" SA DUCT UP TO RTU-4 ON ROOF. TRANSITION DUCT AS REQUIRED AT
- CONNECTION TO UNIT. 7 26" X 14" RA DUCT UP TO RTU-4 ON ROOF. TRANSITION DUCT AS REQUIRED AT CONNECTION TO UNIT.



222 Lee Street, West Charleston, West Virginia 25302 Phone: 304.342.0159 Fax: 304.345.8144 www.zmm.com






c by ZMM, INC. FIRST FLOOR PLAN - AREA 'C' -**HVAC DUCTWORK**

SAO 07/07/2023

COMM. NO. 2022088 M131c





FIRST FLOOR PLAN AREA 'D' - HVAC DUCTWORK

KEYED NOTES

- 1 REALIGN AIR DEVICE INTO NEW CEILING GRID.
- 2 20" X 10" SA DUCT UP TO DOAS-9 ON ROOF. TRANSITION DUCT AS REQUIRED AT CONNECTION TO UNIT.
- 3 28" X 8" EA DUCT UP TO DOAS-9 ON ROOF. TRANSITION DUCT AS REQUIRED AT CONNECTION TO UNIT.
- 4 CONNECTION POINT OF FABRIC DUCT TO METAL DUCT. REFER TO DETAIL ON SHEET M511.
- 5 FABRIC DUCT WITHOUT AIR OPENINGS. 6 FABRIC DUCT (BASIS OF DESIGN: COMBI 70 FABRIC WITH ORIFLOW OPENINGS FROM FABRICAIR). PROVIDE AIR OPENINGS AT THE 6 O'CLOCK & 7 O'CLOCK POSITION FOR 2,000 CFM WITH 25 FT THROW, ISOTHERMAL AIR, TO 50 FPM. OPENINGS SHALL BE EQUALLY DISTRIBUTED ALONG THE LENGTH OF FABRIC
- DUCT. CENTERLINE OF DUCT SHALL BE 20'-0" AFF. REFER TO DETAILS ON SHEET 7 FABRIC DUCT (BASIS OF DESIGN: COMBI 70 FABRIC WITH ORIFLOW OPENINGS FROM FABRICÀIR). PROVIDE AIR OPENINGS AT THE 5 O'CLOCK & 6 O'CLOCK POSITION FOR 2,000 CFM WITH 25 FT THROW, ISOTHERMAL AIR, TO 50 FPM. OPENINGS SHALL BE EQUALLY DISTRIBUTED ALONG THE LENGTH OF FABRIC DUCT. CENTERLINE OF DUCT SHALL BE 20'-0" AFF. REFER TO DETAILS ON SHEET
- 8 28" X 16" LINED SUPPLY DUCT UP TO RTU-3A/3B ON ROOF. TRANSITION DUCT AS
- REQUIRED AT CONNECTION TO UNIT. 9 32" X 16" LINED RETURN DUCT UP TO RTU-3A/3B ON ROOF. TRANSITION DUCT AS REQUIRED AT CONNECTION TO UNIT.



222 Lee Street, West Charleston, West Virginia 25302 Phone: 304.342.0159 Fax: 304.345.8144

www.zmm.com



	DATE			
REVISIONS	DESCRIPTION			
	NO.			

FIRST FLOOR PLAN - AREA 'D' -**HVAC DUCTWORK**

07/07/2023 COMM. NO. 2022088

M131d

AREA 'A' **KEY PLAN** NOT TO SCALE



- 1 REALIGN AIR DEVICE INTO NEW CEILING GRID.
 2 28" X 16" OA DUCT UP TO DOAS-6 ON ROOF. TRANSITION DUCT AS REQUIRED AT CONNECTION TO UNIT.
- 3 20" X 24" EA DUCT UP TO DOAS-6 ON ROOF. TRANSITION DUCT AS REQUIRED AT CONNECTION TO UNIT.
- 4 26" X 20" OA DUCT UP TO DOAS-7 ON ROOF. TRANSITION DUCT AS REQUIRED AT CONNECTION TO UNIT.
- 5 24" X 22" EA DUCT UP TO DOAS-7 ON ROOF. TRANSITION DUCT AS REQUIRED AT CONNECTION TO UNIT.
- TIE NEW 16" X 12" OA DUCT INTO EXISTING 16" X 12" OA DUCT GOING DOWN TO FLOOR BELOW.



www.zmm.com


	REVISIONS	
<u>.</u>	DESCRIPTION	DATE

SECOND FLOOR PLAN - HVAC DUCTWORK

SAO 07/07/2023 COMM. NO. 2022088


M132






SECOND FLOOR PLAN - HVAC DUCTWORK

1/8" = 1'-0"








- 1 CHILLER AIR COOLED CONDENSING UNIT. SEE DWG M141b FOR REMOTE
- EVAPORATOR LOCATION. 2 REFRIGERANT PIPING THRU ROOF. ROUTE REFRIGERANT PIPING IN ACCORDANCE WITH MANUFACTURER'S INSTALLATION INSTRUCTIONS. SUPPORT REFRIGERANT
- PIPING EVER 10'-0" ON CENTER, AND AT EVERY CHANGING IN DIRECTION. 3 8" BOILER FLUE PIPING THRU ROOF. LOCATE FLUE PIPING TO MAINTAIN MINIMUM 15'-0" CLEARANCE FROM FRESH AIR INTAKES. TERMINATE A MINIMUM OF 2'-0" ABOVE ROOF PARAPET.
- 4 NEW RTU-1 LOCATION. COORDINATE FINAL LOCATION WITH STRUCTURAL. EXTEND GAS PIPING TO NEW RTU AND CONNECT, SEE DETAIL.



222 Lee Street, West Charleston, West Virginia 25302 Phone: 304.342.0159 Fax: 304.345.8144

www.zmm.com



	DATE					
REVISIONS	DESCRIPTION					
	O					

RENOVATIONS

MACY MCLAUGHERTY ELEMENTARY/MIDDLE SCHOOL

GILES COUNTY PUBLIC SCHOOLS

PEARISBURG, VIRGINIA

ROOF PLAN -HVAC

DRAWN	CHECKED
SAO	JAP
	DATE
	07/07/2023
	COMM. NO.
	2022088

M133



KEY PLAN

NOT TO SCALE

1 EXTEND NEW CHILLED AND HEATING WATER PIPING FROM MAIN TO FAN COIL UNIT.
TIE NEW CONDENSATE DRAIN PIPING INTO EXISTING CONDENSATE DRAIN
SYSTEM. DRAIN PIPING SIZE SHALL NOT BE SMALLER THAN MANUFACTURER'S
FACTORY DRAIN CONNECTION.



www.zmm.com



IO. DESCRIPTION DATE

ON ...

RG, VIRGINIA

ILES COUNTY PUBLIC SCHO PEARISBURG, VIRGINIA

© by ZMM, IN

FIRST FLOOR PLAN AREA 'A' -HVAC PIPING

DRAWN
SAO


SAO


DATE


07/07/2023

COMM. NO.
2022088

M141a







1 EXTEND NEW CHILLED AND HEATING WATER PIPING FROM MAIN TO FAN COIL UNIT.
TIE NEW CONDENSATE DRAIN PIPING INTO EXISTING CONDENSATE DRAIN
SYSTEM. DRAIN PIPING SIZE SHALL NOT BE SMALLER THAN MANUFACTURER'S
FACTORY DRAIN CONNECTION.



www.zmm.com



NO. DESCRIPTION DATE

DLE SCHOOL

ES COUNTY PUBLIC SCHOOLS
PEARISBURG, VIRGINIA

AREA 'B'

AREA 'A'

KEY PLAN

NOT TO SCALE

FIRST FLOOR PLAN AREA 'B' -HVAC PIPING

DRAWN
SAO

DATE
07/07/2023

COMM. NO.
2022088

M141b




KEY PLAN

NOT TO SCALE

1 EXTEND NEW CHILLED AND HEATING WATER PIPING FROM MAIN TO FAN COIL UNIT. TIE NEW CONDENSATE DRAIN PIPIING INTO EXISTING CONDENSATE DRAIN SYSTEM. DRAIN PIPING SIZE SHALL NOT BE SMALLER THAN MANUFACTURER'S FACTORY DRAIN CONNECTION. 2 FREEZER/COOLER SENSOR SHALL BE LOCATED IN NEW WALK-IN UNITS.



www.zmm.com




	REVISIONS	
NO.	DESCRIPTION	DATE

FIRST FLOOR PLAN AREA 'C' -**HVAC PIPING**

CHECKED 07/07/2023 COMM. NO. **2022088**

M141c





FIRST FLOOR PLAN AREA 'C' - HVAC PIPING
1/8" = 1'-0"

MATCH LINE AREA 'A'
MATCH LINE AREA 'C'

102D

__1 1/4" C

1 1/2" C—

MATCH LINE AREA 'A'
MATCH LINE AREA 'D'

KEYED NOTES

MATCH LINE AREA 'C'
MATCH LINE AREA 'D'

1 EXTEND NEW CHILLED AND HEATING WATER PIPING FROM MAIN TO FAN COIL UNIT. TIE NEW CONDENSATE DRAIN PIPIING INTO EXISTING CONDENSATE DRAIN SYSTEM. DRAIN PIPING SIZE SHALL NOT BE SMALLER THAN MANUFACTURER'S FACTORY DRAIN CONNECTION.



www.zmm.com

© by ZMM, INC.

FIRST FLOOR PLAN AREA 'D' -**HVAC PIPING**

CHECKED 07/07/2023 COMM. NO. **2022088**


M141d

AREA 'A' **KEY PLAN** NOT TO SCALE

1 EXTEND NEW CHILLED AND HEATING WATER PIPING FROM MAIN TO FAN COIL UNIT. TIE NEW CONDENSATE DRAIN PIPIING INTO EXISTING CONDENSATE DRAIN SYSTEM. DRAIN PIPING SIZE SHALL NOT BE SMALLER THAN MANUFACTURER'S FACTORY DRAIN CONNECTION.



www.zmm.com




SCHOOL

SECOND FLOOR PLAN - HVAC PIPING


CHECKED SAO 07/07/2023 COMM. NO. 2022088


M142





SECOND FLOOR PLAN - HVAC PIPING
1/8" = 1'-0"






FIRST FLOOR PLAN AREA 'B' - ENLARGED PIPING DEMOLITION 1/4" = 1'-0"

KEYED NOTES

INDICATED. COORDINATE WITH E.C.

- 1 DISCONNECT AND REMOVE EXISTING NATURAL GAS BOILER, FLUE PIPING, PORTIONS OF HYDRONIC PIPING AND PORTIONS OF NATURAL GAS PIPING AS
- 2 DISCONNECT AND REMOVE EXISTING REMOTE EVAPORATOR, REFRIGERANT PIPING, AND PORTIONS OF HYDRONIC PIPING AS INDICATED. COORDINATE WITH
- 3 DISCONNECT AND REMOVE EXISTING PUMP AND PORTIONS OF HYDRONIC PIPING AS INDICATED. COORDINATE WITH E.C.
- 4 DISCONNECT AND REMOVE FAN COIL UNIT, PORTIONS OF HYDRONIC PIPING AND PORTIONS OF CONDENSATE PIPING AS INDICATED, AND ASSOCIATED CONTROLS. COORDINATE WITH E.C.



FIRST FLOOR PLAN AREA 'B' - ENLARGED PIPING 1/4" = 1'-0"


KEYED NOTES


CONNECTION SIZE.

- 1 REFRIGERANT PIPING THRU ROOF. ROUTE REFRIGERANT PIPING IN ACCORDANCE WITH MANUFACTURER'S INSTALLATION INSTRUCTIONS.
- 2 8" BOILER FLUE PIPING THRU ROOF. 3 INTERLOCK EXISTING COMBUSTION AIR LOUVERS WITH NEW BOILER CONTROLS.
- PROVIDE BOILERS WITH ROOM AIR COMBUSTION KITS.
- 4 PROVIDE CONDENSATE NEUTRALIZATION KIT. ROUTE BOILER CONDENSATE DRAIN PIPING TO NEAREST FLOOR DRAIN. CONDESATE PIPING SIZE SHALL MATCH THE MANUFACTURER'S DISCHARGE CONNECTION SIZE.

5 ROUTE CHILLER CONDENSATE DRAIN PIPING TO NEAREST FLOOR DRAIN. CONDESATE PIPING SIZE SHALL MATCH THE MANUFACTURER'S DISCHARGE







ENLARGED MECHANICAL VIEWS


c by ZMM, INC.

07/07/2023 COMM. NO. 2022088

M310







REFRIGERANT PIPING

(OTHER PIPE BEYOND)-

ALUMINUM JACKET ON


BOTH REFRIGERANT LINES-


PIPE PORTAL WITH

TO PORTALS PLUS


ALUMI-FLASH SYSTEM-

ALUMINUM BASE EQUAL







FOR TWO ROW CABLE SUSPENSION SYSTEMS - TO BEST FIT WHERE ELBOWS OR OTHER FITTINGS ARE INCLUDED IN THE SYSTEM



8 FABRIC DUCT INLET ATTACHMENT









3x1 SUSPENSION, CABLE AT 12 O'CLOCK HANGER SUPPORTS DUCTSOX AT 10 & 2 O'CLOCK

11 FABRIC DUCT SUSPENSION
NO SCALE





INSULATED DUCT MANUAL VOLUME

3 DAMPER DETAIL

4 SUPPLY AIR DIFFUSER




FOR POWER

WIRING (BY


[∟]POWER


WIRING





TRUNK DUCT \





TYPICAL GAS PIPING AND REGULATOR



—AFD ADJUSTMENT CLIP

"CUT-AWAY" VIEW

-DARK GREY TAB IF AFD AT ZIPPER LOCATION

IF ADJUSTMENT NEEDED

OPEN ZIPPER AT


BOTTOM

ADJUSTABLE FLOW DEVICE, BALANCED

DOUBLE ZIPPER CONNECTION —

FROM FACTORY-






COORDINATE MOUNTING/CURB HEIGHT AS REQUIRED

-RIGID ROOF

INSULATION

ROOF FRAMING -SEE STRUCTURAL


TO PROVIDE PROPER CONDENSATE DRAINAGE.



INSTALLED AT ZIPPER LOCATION AT INLET OR AS SPECIFIED IN OTHER LOCAITONS. ZIPPER TO ZIPPER CONNECTION AS SHOWN. EXTERNAL LABEL IDENTIFIES LOCATION

RETURN OPENING IN TOP OF DUCT WITH 1" FLANGE. COVER OPENING WITH 1" GALVANIZED STEEL MESH.--INTERIOR LINED RA DUCT

DRAWINGS 1. ROOF OPENING LARGE ENOUGH TO ACCOMODATE SUPPLY AND RETURN DUCTWORK 2. CAULK THE SPACE BETWEEN DUCTWORK AND OPENINGS AIR TIGHT



13 TYPICAL GAS DETAIL

NO SCALE

9 FABRIC DUCT ADJUSTABLE FLOW DEVICE
NO SCALE




ROOFTOP UNIT CURB

RIGID ROOF

INSULATION BELOW UNIT

222 Lee Street, West Charleston, West Virginia 25302
Phone: 304.342.0159
Fax: 304.345.8144 www.zmm.com





DETAILS

(c) by ZMM, INC.

DRAWN CHECKED SAO 07/07/2023 COMM. NO. 2022088

M510

	D	IFFUSE	ER SCHEDULE
MARK	DIFFUSER TYPE	MODEL	DESCRIPTION
R1	RETURN	TITUS 33RL	HEAVY DUTY SURFACE MOUNTED GRILLE
S1	SUPPLY	TITUS OMNI	24x24 PLAQUE DIFFUSER

0	DOAS-2 HEAT WHEEL PERFORMANCE
SUMMER	SUMMER
79.1 DB°F/65.0 WB°F SA — OA	79.3 DB°F/65.1 WB°F 88.3 DB°F/70.6 WB°F SA ———————————————————————————————————
1,075 CFM	2,000 CFM
75.0 DB°F/62.0 WB°F	75.0 DB°F/62.0 WB°F
825 CFM 957 CFM	1,550 CFM 1,717 CFM
TOTAL CAPACITY: 20.8 MBH SENSIBLE CAPACITY: 10.3 MBH	TOTAL CAPACITY: 37.6 MBH SENSIBLE CAPACITY: 18.7 MBH
WINTER	WINTER
44.8 DB°F/36.1 WB°F 0.0 DB°F/0.0 WB°F	43.9 DB°F/35.4 WB°F 0.0 DB°F/0.0 WB°F
1,075 CFM	SA 2,000 CFM
1,075 CFM 日本 1,207 CFM 日本 1,20	2,000 CFM
825 CFM 957 CFM	1,550 CFM 1,717 CFM
TOTAL CAPACITY: 63.3 MBH	TOTAL CAPACITY: 147.8 MBH
SENSIBLE CAPACITY: 54.0 MBH	SENSIBLE CAPACITY: 98.0 MBH
DOAS-3 HEAT WHEEL PERFORMANCE	DOAS-4 HEAT WHEEL PERFORMANCE
SUMMER	SUMMER
79.7 DB°F/65.4 WB°F 88.3 DB°F/70.6 WB°F	79.5 DB°F/65.3 WB°F 88.3 DB°F/70.6 WB°F
SA 1,830 CFM	SA 2,310 CFM ☐ 2,480 CFM ☐
1,830 CFM	2,310 CFM
1,425 CFM 1,567 CFM	1,800 CFM 1,970 CFM
TOTAL CAPACITY: 32.9 MBH	TOTAL CAPACITY: 42.6 MBH
SENSIBLE CAPACITY: 16.4 MBH	SENSIBLE CAPACITY: 21.2 MBH
WINTER	WINTER
42.0 DB°F/34.1 WB°F 0.0 DB°F/0.0 WB°F	43.0 DB°F/34.8 WB°F 0.0 DB°F/0.0 WB°F
SA 1,830 CFM	SA 2,310 CFM 型 2,480 CFM
1,830 CFM	2,310 CFM
1,425 CFM 1,567 CFM	1,800 CFM 1,970 CFM
TOTAL CAPACITY: 100.9 MBH SENSIBLE CAPACITY: 86.3 MBH	TOTAL CAPACITY: 130.1 MBH SENSIBLE CAPACITY: 111.2 MBH
DOAS-5 HEAT WHEEL PERFORMANCE	DOAS-6 HEAT WHEEL PERFORMANCE
SUMMER	SUMMER
79.3 DB°F/65.1 WB°F 88.3 DB°F/70.6 WB°F	79.6 DB°F/65.3 WB°F 88.3 DB°F/70.6 WB°F
SA OA 1,935 CFM	SA
1,935 CFM	3,625 CFM
1,500 CFM 1,666 CFM	2,800 CFM 3,003 CFM
TOTAL CAPACITY: 36.6 MBH	TOTAL CAPACITY: 65.8 MBH
SENSIBLE CAPACITY: 18.1 MBH	SENSIBLE CAPACITY: 32.7 MBH
WINTER	WINTER
44.1 DB°F/35.6 WB°F	42.6 DB°F/34.6 WB°F
1,935 CFM	3,625 CFM
	68.0 DB°F/50.0 WB°F RA ———————————————————————————————————
RA — EA	

DOAS-7 HEAT WHEEL PERFORMANCE

79.4 DB°F/65.2 WB°F 88.3 DB°F/70.6 WB°F

TOTAL CAPACITY: 57.0 MBH

SENSIBLE CAPACITY: 28.3 MBH

43.7 DB°F/35.3 WB°F 0.0 DB°F/0.0 WB°F

TOTAL CAPACITY: 173.9 MBH

SENSIBLE CAPACITY: 148.5 MBH

2,549 CFM

3,259 CFM

3,060 CFM ☐ ☐ ☐

DOAS-8 HEAT WHEEL PERFORMANCE

78.8 DB°F/64.8 WB°F 88.3 DB°F/70.6 WB°F

625 CFM 758 CFM

46.6 DB°F/37.2 WB°F 0.0 DB°F/0.0 WB°F

68.0 DB°F/50.0 WB°F ☐ 6.5 DB°F/6.4 WB°F

625 CFM 758 CFM

TOTAL CAPACITY: 49.0 MBH

SENSIBLE CAPACITY: 41.8 MBH

TOTAL CAPACITY: 16.2 MBH

SENSIBLE CAPACITY: 8.0 MBH

805 CFM

										FOL	JR PIPE	FAN CC	IL UNIT	SCHED	JLE										
			APPROX.				CW CC	OLING COIL	. DATA					HW HE	ATING COIL	_ DATA			FAN DATA			ELECTRIC	CAL DATA		
			WEIGHT	TOTAL SA	TOTAL	SENSIBLE	EAT DB	EAT WB	LAT DB	LAT WB	FLOW	RUNOUT	TOTAL	EAT DB	LAT DB	FLOW	RUNOUT	ESP (IN	DESIGN]
MARK	MFR	MODEL	(LBS)	(CFM)	(MBH)	(MBH)	(°F)	(°F)	(°F)	(°F)	(GPM)	SIZE	(MBH)	(°F)	(°F)	(GPM)	SIZE	H2O)	RPM	SIZE (HP)	VOLTS	PHASE	MCA	MOCP	REMARKS
FCU-1	TRANE	BCHE054	220	1400	49.6	34.4	78	66	55.7	54.4	8.5	1"	54.6	66	102.1	5.5	1"	0.5	1302	1	115	1	16.63	25	
FCU-2 FCU-3	TRANE TRANE	FCCB100 FCCB100	200	1000 1000	41.7 42.2	28.4	78 78	66 66	53.9 53.7	53.2 53.0	8.5	1"	35.1 36.8	66 66	98.4 99.9	4	3/4"	0.5 0.5	1755 1755	1@0.13 1@0.22 1@0.13 1@0.22	115 115	1	6.08 6.08	15 15	+
FCU-4	TRANE	BCHE036	190	1200	49.3	32.1		66	53.7	52.3	9	1"	46.5	66	101.9	4.5	3/4"	0.5	1708	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	115	1	16.63	25	+
FCU-5	TRANE	BCHE054	220	1200	49.3	32.1	78	66	53.7	52.3	9	1"	46.5	66	101.9	4.5	3/4"	0.5	1708	1	115	1	16.63	25	
FCU-6	TRANE	BCHE054	220	1200	49.3	32.1	78	66	53.7	52.3	9	1"	46.5	66	101.9	4.5	3/4"	0.5	1708	1	115	1	16.63	25	
FCU-7	TRANE	BCHE036	190	1200	49.3	32.1	78	66 66	53.7	52.3	9	1"	46.5 46.5	66 66	101.9	4.5	3/4"	0.5	1708	1	115 115	1	16.63	25	
FCU-8 FCU-9	TRANE TRANE	BCHE036 BCHE054	190 220	1200 1200	49.3 49.3	32.1 32.1		66	53.7 53.7	52.3 52.3	9	1"	46.5	66	101.9 101.9	4.5 4.5	3/4" 3/4"	0.5 0.5	1708 1708	1	115	1	16.63 16.63	25 25	+
FCU-10	TRANE	BCHE054	220	1200	49.3	32.1	78	66	53.7	52.3	9	1"	46.5	66	101.9	4.5	3/4"	0.5	1708	1	115	1	16.63	25	+
FCU-11	TRANE	BCHE054	220	1400	49.6	34.4	78	66	55.7	54.4	8.5	1"	54.6	66	102.1	5.5	1"	0.5	1302	1	115	1	16.63	25	
FCU-12	TRANE	FCCB020	85	160	4.8	3.5	78	66	60.2	57.6	1	3/4"	5.7	66	99.0	0.5	3/4"	0.5	1291	0.13	115	1	2.75	15	<i></i>
FCU-13	TRANE TRANE	BCHE054 BCHE054	220 220	1600	53.7	37.8	78	66 66	56.6 57.7	55.1 55.9	9.5	1" 1-1/4"	60.0 69.8	66 66	100.7 101.9	6	1"	0.5	1408	1	115 115	1	16.63 16.63	25	
FCU-14 FCU-15	TRANE	FCCB100	200	1800 725	62.4 19.9	44.2 15.6	76 78	66	60.3	58.3	12.5 3.5	3/4"	23.1	66	95.3	1	3/4"	0.5 0.5	1494 1438	0.13	115	1	6.08	25 15	+
FCU-16	TRANE	BCHE054	220	1600	53.7	37.8	78	66	56.6	55.1	9.5	1"	60.0	66	100.7	6	1"	0.5	1408	1	115	1	16.63	25	
FCU-17	TRANE	FCCB100	200	1100	35.2	26.3	78	66	58.1	56.7	7	1"	37.5	66	97.4	5	1"	0.5	1807	0.13	115	1	6.08	15	
FCU-18	TRANE	BCHE054	220	1600	53.7	37.8	78	66	56.6	55.1	9.5	1"	60.0	66	100.7	6	1"	0.5	1408	1	115	1	16.63	25	
FCU-19	TRANE	BCHE036	190	1200	49.3	32.1	78	66	53.7	52.3	9	1"	46.5	66	101.9	4.5	3/4"	0.5	1708	1	115	1	16.63	25	
FCU-20 FCU-21	TRANE TRANE	BCHE054 BCHE054	220 220	1500 1400	51.7 49.6	36.1 34.4	78 78	66 66	56.1 55.7	54.4 54.4	8.5	1"	57.3 54.6	66	101.3 102.1	5.5 5.5	1"	0.5 0.5	1355 1302	1	115 115	1	16.63 16.63	25 25	+
FCU-22	TRANE	BCHE054	220	1400	49.6	34.4		66	55.7	54.4	8.5	1"	54.6	66	102.0	5.5	1"	0.5	1302	1	115	1	16.63	25	+
FCU-23	TRANE	BCHE054	220	1400	49.6	34.4	78	66	55.7	54.4	8.5	1"	54.6	66	102.0	5.5	1"	0.5	1302	1	115	1	16.63	25	
FCU-24	TRANE	BCHE036	190	1200	49.3	32.1	78	66	53.7	52.3	9	1"	46.5	66	101.9	4.5	3/4"	0.5	1708	1	115	1	16.63	25	
FCU-25	TRANE	FCCB040	110	325	11.7	8.4	78	66	56.3	55.3	2.5	3/4"	11.2	66	97.7	1.5	3/4"	0.5	1617	0.13	115	1	2.75	15	
FCU-26 FCU-27	TRANE TRANE	FCCB100 FCCB100	200	1050 1050	41.5 41.5	28.9	/8 78	66 66	54.8 54.8	54.0 54.0	7.5 7.5	1"	36.4 36.4	66 66	97.9 97.9	4.5 4.5	3/4"	0.5 0.5	1798 1798	1@0.13 1@0.22 1@0.13 1@0.22	115 115	1	6.08 6.08	15 15	+
FCU-28	TRANE	FCCB100	200	1050	41.5	28.9		66	54.8	54.0	7.5	1"	36.4	66	97.9	4.5	3/4"	0.5	1798	1@0.13 1@0.22	115	1	6.08	15	+
FCU-29	TRANE	FCCB100	200	1050	41.5	28.9	78	66	54.8	54.0	7.5	1"	36.4	66	97.9	4.5	3/4"	0.5	1798	1@0.13 1@0.22	115	1	6.08	15	
FCU-30	TRANE	FCCB100	200	1050	41.5	28.9	78	66	54.8	54.0	7.5	1"	36.4	66	97.9	4.5	3/4"	0.5	1798	1@0.13 1@0.22	115	1	6.08	15	
FCU-31	TRANE	BCHE090	275	2200	80.5	55.5	78	66	55.1	54.0	14	1-1/4"	87.5	66	102.8	8.5	1"	0.5	885	1	115	1	16.63	25	
FCU-32 FCU-33	TRANE TRANE	FCCB030 FCCB020	85 85	250 250	5.8 6.7	4.6 5.0	78 	66	63.1 61.8	59.8 58.6	1.5	3/4"	6.5 6.5	66 66	90.1	0.5	3/4"	0.5 0.5	1526 1536	0.13	115 115	1	2.75 2.75	15 15	+
FCU-34	TRANE	FCCB020	150	650	23.0	16.6		66	56.5	55.5	4	3/4"	21.6	66	96.6	0.5	3/4"	0.5	1672	0.13	115	1	3.88	15	+
FCU-35	TRANE	FCCB040	110	240	8.4	6.1	78	66	56.5	55.7	1.5	3/4"	9.3	66	101.6	1	3/4"	0.5	1399	0.13	115	1	2.75	15	+
FCU-36	TRANE	FCCB100	200	800	23.9	17.9	78	66	59.5	57.5	5	1"	32.1	66	103.0	4	3/4"	0.5	1503	1@0.13 1@0.22	115	1	6.08	15	
FCU-37	TRANE	FCCB060	140	460	12.8	9.8	78	66	60.5	58.2	2.5	3/4"	14.3	66	94.6	1	3/4"	0.5	1465	0.22	115	1	3.88	15	
FCU-38 FCU-39	TRANE TRANE	FCCB040 FCCB100	200	310 950	10.6 31.2	7.8	78 78	66	57.0 57.7	56.0 56.5	6	3/4"	10.1 31.9	66 66	96.1 97.0	2.5	3/4"	0.5 0.5	1575 1670	0.13 1@0.13 1@0.22	115 115	1	2.75 6.08	15 15	+
FCU-40	TRANE	BCHE090	275	2100	78.1	53.7		66	54.8	53.8	13.5	1-1/4"	84.7	66	103.3	8.5	1"	0.5	864	1 1	115	1	16.63	25	+
FCU-41	TRANE	FCCB020	85	150	4.6	3.3	78	66	59.9	57.2	1	3/4"	5.6	66	100.5	0.5	3/4"	0.5	1267	0.13	115	1	2.75	15	
FCU-42	TRANE	BCHE120	340	3200	129.0	86.7	78	66	53.4	52.6	22	1-1/2"	123.5	66	101.7	12	1-1/4"	0.5	1004	1.5	208	3	9.5	15	
FCU-43	TRANE	BCHE054	220	1500	51.7	36.1	78	66	56.1	54.7	9	1"	57.3	66	101.3	5.5	1"	0.5	1355	11	115	1	16.63	25	
FCU-44	TRANE TRANE	BCHE120 BCHE036	340	2500	106.2	70.7	78 78	66	52.3	51.7	18	1-1/2"	103.8	66	104.3	10	1-1/4"	0.5	867	1.5	208	3	9.5	15 25	
FCU-45 FCU-46	TRANE	FCCB020	190 85	1200 150	49.3 4.6	32.1	78 78	66	53.7 59.9	52.3 57.2	1	3/4"	46.5 5.6	66 66	101.9 100.5	4.5 0.5	3/4"	0.5 0.5	1708 1267	0.13	115 115	1	16.63 2.75	15	+
FCU-47	TRANE	BCHE054	230	1600	53.7	37.8	78	66	56.6	55.1	9.5	1"	60.0	66	100.7	5.75	1"	0.5	1408	1	115	1	16.63	25	+
FCU-48	TRANE	BCHE054	220	1400	49.6	34.4	78	66	55.7	54.4	8.5	1"	54.6	66	102.0	5.5	1"	0.5	1302	1	115	1	16.63	25	
FCU-49	TRANE	BCHE054	220	1400	49.6	34.4	78	66	55.7	54.4	8.5	1"	54.6	66	102.1	5.5	1"	0.5	1302	1	115	1	16.63	25	
FCU-50	TRANE	BCHE054	220	1400	49.6	34.4	78	66	55.7	54.4	8.5	1"	54.6	66	102.0	5.5	1"	0.5	1302	1	115	1	16.63	25	+
FCU-51 FCU-52	TRANE TRANE	BCHE054 BCHE054	220 220	1400 1400	49.6 49.6	34.4 34.4	78 	66	55.7 55.7	54.4 54.4	8.5 8.5	1"	54.6 54.6	66 66	102.1 102.0	5.5 5.5	1"	0.5 0.5	1302 1302	1	115 115	1 1	16.63 16.63	25 25	+
FCU-53	TRANE	BCHE054	220	1400	49.6	34.4	78	66	55.7	54.4	8.5	1"	54.6	66	102.1	5.5	1"	0.5	1302	1	115	1	16.63	25	+
FCU-54	TRANE	BCHE054	220	1400	49.6	34.4	78	66	55.7	54.4	8.5	1"	54.6	66	102.0	5.5	1"	0.5	1302	1	115	1	16.63	25	
FCU-55	TRANE	BCHE054	220	1800	62.4	44.2	78	66	55.7	55.9	12.5	1-1/4"	69.8	66	101.9	5	1"	0.5	1494	1	115	1	16.63	25	
FCU-56	TRANE	BCHE054	230	1600	53.7	37.8	78	66	56.6	55.1	9.5	1"	60.0	66	100.7	5.75	1"	0.5	1408	1	115	1	16.63	25	

									DE	DICATE	D OUTD	OOR AIF	R SYSTE	M UNIT	SCHEDI	JLE									
			APPROX.			(CW COOLIN	G COIL DATA	4		NA ⁻	TURAL GAS	HEATING D	ATA	SU	PPLY FAN [DATA	EXH	AUST FAN	DATA		ELECTRIC	AL DATA		
			WEIGHT	TOTAL SA	TOTAL	SENSIBLE	EAT DB	EAT WB	LAT DB	LAT WB	INPUT	OUTPUT	EAT DB	LAT DB	ESP (IN	DESIGN		ESP (IN	DESIGN						
MARK	MFR	MODEL	(LBS)	(CFM)	(MBH)	(MBH)	(°F)	(°F)	(°F)	(°F)	(MBH)	(MBH)	(°F)	(°F)	H2O)	RPM	SIZE (HP)	H2O)	RPM	SIZE (HP)	VOLTS	PHASE	MCA	MOCP	REMARKS
DOAS-1	TRANE	OABD036	2200	1075	41.4	30.8	79.1	65.0	51.4	51.4	100	80	44.8	113.4	1.5	2279	1	1.0	1641	1	208	3	28.3	40	
DOAS-2	TRANE	OABD036	2300	2000	43.6	43.3	79.3	65.2	57.6	57.6	200	160	43.9	117.7	1.5	2495	3	1.0	2044	1	208	3	32.3	40	
DOAS-3	TRANE	OABD036	2200	1830	44.5	43.6	79.7	65.4	57.1	57.1	200	160	42.0	122.6	1.5	2442	3	1.0	2020	1	208	3	32.3	40	
DOAS-4	TRANE	OABD072	2300	2310	72.4	59.0	79.5	65.3	54.2	54.2	200	160	43.0	106.9	1.5	2701	3	1.0	2219	1.5	208	3	44.8	60	
DOAS-5	TRANE	OABD036	2300	1935	43.5	42.7	79.3	65.1	57.2	57.2	200	160	44.1	120.3	1.5	2442	3	1.0	2009	1	208	3	32.3	40	
DOAS-6	TRANE	OAKD180	5300	3625	180.5	121.9	79.6	65.3	47.1	47.1	350	280	42.6	113.8	1.5	1801	3	1.0	1460	2	208	3	84.9	100	
DOAS-7	TRANE	OAKD144	5200	3060	140.7	98.1	79.4	65.2	48.6	48.6	300	240	43.7	116.0	1.5	1681	3	1.0	1380	2	208	3	74.2	90	
DOAS-8	TRANE	OABD036	2200	805	39.2	26.6	78.8	64.8	47.0	47.0	75	60	46.6	115.3	1.5	2951	2	1.0	2640	2	208	3	33.1	40	
DOAS-9	TRANF	OABD048	2200	1540	50.3	40.2	79 1	65.0	53.5	53.5	125	100	45.2	105.1	1.5	2252	15	1.0	1926	1	208	3	35.4	50	

NOTES:

1. BASIS OF DESIGN: TRANE. SEE SPECIFICATIONS FOR ALTERNATE MANUFACTURERS.
2. CAPACITIES SHOWN ARE MINIMUM.

EXTERNAL STATIC PRESSURE DOES NOT INCLUDE DIRTY FILTER ALLOWANCE OR SUPPLY EXIT LOSS.
 UNIT SHALL BE PROVIDED WITH FACTORY INSTALLED AND WIRED TERMINAL STRIP FOR DDC INTEGRATION.

SEE SPECIFICATION FOR ADDITIONAL INFORMATION ON EQUIPMENT REQUIREMENTS.
 SEE CONTROLS SCHEMATICS FOR ADDITIONAL ACCESSORIES AND APPURTENANCES.

0.	SEE CONTROLS SCHEWATICS FOR ADDITIONAL ACCESSORIES AND AFFORT ENANCES.
7.	 ANY UNIT EXCEEDING THE DIMENSIONS OR WEIGHTS SHALL BE SUBMITTED FOR REVIEW AND APPROVED BY THE ENGINEER.

											ROOF	TOP UN	IT SCHE	DULE											
			APPROX.			C	CW COOLIN	G COIL DAT	A		NA	TURAL GAS	HEATING D	ATA	SUI	PPLY FAN D	ATA	EXH	AUST FAN I	DATA		ELECTRIC	AL DATA		
				TOTAL SA	TOTAL	SENSIBLE	EAT DB	EAT WB	LAT DB	LAT WB	INPUT	OUTPUT	EAT DB	LAT DB	ESP (IN	DESIGN		ESP (IN	DESIGN						
MARK	MFR	MODEL	(LBS)	(CFM)	(MBH)	(MBH)	(°F)	(°F)	(°F)	(°F)	(MBH)	(MBH)	(°F)	(°F)	H2O)	RPM	SIZE (HP)	H2O)	RPM	SIZE (HP)	VOLTS	PHASE	MCA	MOCP	REMARKS
RTU-1	TRANE	OABD096A3	2,200	2,000	89.1	60.5	82.0	68.0	53.4	53.2	100	80	60.0	96.9	1.25	2,262	1.5	0.5	1,704	1.0	208	3	44.6	60	
RTU-2	TRANE	OADG020C1	3,800	5,000	244.4	151.0	82.0	69.0	53.4	52.9	300	243	50.0	94.8	1.5	1,562	5.0	0.5	1,708	1.5	208	3	91.7	110	
RTU-3A	TRANE	OADG020C1	3,500	4,000	188.2	115.3	80.0	68.0	52.6	52.2	250	202.5	50.0	96.7	1.5	1,718	3.0	0.5	1,414	1.0	208	3	77.3	100	
RTU-3B	TRANE	OADG020C1	3,500	4,000	188.2	115.3	80.0	68.0	52.6	52.2	250	202.5	50.0	96.7	1.5	1,718	3.0	0.5	1,414	1.0	208	3	77.3	100	
DTIL 4	TDANE	040000001	2 500	2.450	100 6	70.0	90.0	67.0	E0.0	40.7	150	120	50.0	05.2	1.0	1 602	1.5	0.5	1 107	1.0	200	2	EO 4	70	

NOTES:

1. BASIS OF DESIGN: TRANE. SEE SPECIFICATIONS FOR ALTERNATE MANUFACTURERS.
2. CAPACITIES SHOWN ARE MINIMUM.

DOAS-9 HEAT WHEEL PERFORMANCE

79.1 DB°F/65.0 WB°F 88.3 DB°F/70.6 WB°F

1,290 CFM 1,430 CFM

45.2 DB°F/36.3 WB°F 0.0 DB°F/0.0 WB°F

TOTAL CAPACITY: 91.3 MBH

SENSIBLE CAPACITY: 77.9 MBH

1,290 CFM 1,430 CFM

TOTAL CAPACITY: 29.9 MBH

SENSIBLE CAPACITY: 14.8 MBH

938 CFM 1,540 CFM

1,680 CFM

EXTERNAL STATIC PRESSURE DOES NOT INCLUDE DIRTY FILTER ALLOWANCE OR SUPPLY EXIT LOSS.
 UNIT SHALL BE PROVIDED WITH FACTORY INSTALLED AND WIRED TERMINAL STRIP FOR DDC INTEGRATION.

SEE SPECIFICATION FOR ADDITIONAL INFORMATION ON EQUIPMENT REQUIREMENTS.
 SEE CONTROLS SCHEMATICS FOR ADDITIONAL ACCESSORIES AND ARRIVED FOR ADDITIONAL ACCESSORIES AND ADDITIONAL ACCESSORIES AND ADDITIONAL ACCESSORIES AND ACCESSORIES ADDITIONAL ACCESSORIES AND ACCESSORIES ADDITIONAL ACCESSORIES ADDITIONAL ACCESSORIES ADDITIONAL ACCESSORIES ADDITIONAL ACCESSORIES AD

6. SEE CONTROLS SCHEMATICS FOR ADDITIONAL ACCESSORIES AND APPURTENANCES.7. ANY UNIT EXCEEDING THE DIMENSIONS OR WEIGHTS SHALL BE SUBMITTED FOR REVIEW AND APPROVED BY THE ENGINEER.

							AIR C	OOLED (CHILLEF	R SCHEI	DULE							
					CONE	DENSER		REMOTE	EVAPORAT	OR DATA		REFRIGE	RANT DATA		ELECTRIC	CAL DATA		
				APPROX. WEIGHT	NOMINAL				DESIGN FLOW	MIN. FLOW	DIFF. PRESS.		#					
MARK	MFR	MODEL	LOCATION	(LBS)	TONNAGE	IPLV (EER)	EWT (°F)	LWT (°F)	(GPM)	(GPM)	(FT H2O)	TYPE	CIRCUITS	VOLTAGE	PHASE	MCA	MOCP	REMARKS
CHL-1	TRANE	ACS-160	ROOF	8,000	160	16.243	54	44	289	240	7.32	R-410A	2	208	3	696	800	
CHL-2	TRANE	ACS-160	ROOF	8,000	160	16.243	54	44	289	240	7.32	R-410A	2	208	3	696	800	

NOTES:

1. BASIS OF DESIGN: TRANE - SEE SPECIFICATIONS FOR ALTERNATE MANUFACTURERS.
2. PROVIDE HAIL GUARDS AND SOUND BLANKETS.

					C	ONDEN	SING BO	DILER SO	CHEDUL	.E					
	APPROX CONNECTIONS ELECTRICAL DATA WEIGHT INPUT OUTPUT														
MARK	MFR	MODEL	(LBS)	(MBH)	(MBH)	EWT (°F)	LWT (°F)	HWR (IN.)	HWS (IN.)	FLUE (IN.)	AIR (IN.)	GAS (IN.)	VOLTS	PHASE	REMARKS
B-1	BRYAN	FF2000	4,800	2,000	1,900	110	130	3"	3"	8"	8"	2"	208	3	
B-2	BRYAN	FF2000	4,800	2,000	1,900	110	130	3"	3"	8"	8"	2"	208	3	

NOTES:

1. BASIS OF DESIGN: BRYAN - SEE SPECIFICATIONS FOR ALTERNATE MANUFACTURERS.
2. PROVIDE NEUTRALIZATION KIT.
3. PROVIDE BOILER FLUE AND VENTS PER MANUFACTURER'S INSTALLATION INSTRUCTIONS.

	HYDRONIC PUMP SCHEDULE														
	FLOW EFFICIENCY SUCTION DISCHARGE ELECTRICAL DATA														
MARK	MFR.	MODEL	SERVICE	TYPE	(GPM)	HEAD (FT)	(%)	SIZE (IN)	SIZE (IN)	HP	RPM	VOLTS	PHASE	REMARKS	
P-1A	BELL & GOSSETT	1531-5BD	CHILLED WATER	END SUCTION	720	80	76.9	6	5	25	1,800	208	3		
P-1B	BELL & GOSSETT	1531-5BD	CHILLED WATER	END SUCTION	720	80	76.9	6	5	25	1,800	208	3		
P-2A	BELL & GOSSETT	1531-3BD	HEATING WATER	END SUCTION	330	65	78.0	4	3	10	1,800	208	3		
P-2B	BELL & GOSSETT	1531-3BD	HEATING WATER	END SUCTION	330	65	78.0	4	3	10	1,800	208	3		

ARCHITECTS
ENGINEERS

222 Lee Street, West
Charleston, West Virginia 25302
Phone: 304.342.0159
Fax: 304.345.8144

WWW.zmm.com

	DATE					
REVISIONS	DESCRIPTION					
	O					

RG, VIRGINIA

GILES COUNTY PUBI PEARISBURG, \


(c) by ZMM, INC.

SCHEDULES


WN CHECKED
JAP
DATE
07/07/2023
COMM. NO.

M520

2022088



222 Lee Street, West Charleston, West Virginia 25302 Phone: 304.342.0159 Fax: 304.345.8144 www.zmm.com



HVAC CONTROLS **DIAGRAMS**

CHECKED SAO 07/07/2023 COMM. NO. 2022088

M620