GENERAL NOTES

- 1. THE COMPLETED INSTALLATION SHALL CONFORM TO ALL APPLICABLE CODES, ORDINANCES AND REGULATIONS.
- 2. THE CONTRACTOR SHALL PROVIDE ALL REQUIRED MATERIAL, LABOR, TOOLS, EQUIPMENT AND SUPERVISION FOR A COMPLETE INSTALLATION.
- 3. INSTALL ALL EQUIPMENT AND MATERIALS ACCORDING TO MANUFACTURERS INSTRUCTIONS UNLESS OTHERWISE INDICATED.
- 4. CONTRACTOR TO FIELD VERIFY ALL PIPING AND EQUIPMENT LOCATIONS.
- 5. THESE DRAWINGS ARE SCHEMATIC IN NATURE AND INDICATE THE GENERAL AND APPROXIMATE LOCATION OF EQUIPMENT AND PIPING. DO NOT SCALE DRAWINGS. FIELD VERIFY ALL DIMENSIONS PRIOR TO CONSTRUCTION AND FABRICATING PIPING.
- 6. THE CONTRACTOR SHALL COORDINATE THE INSTALLATION OF WORK AND THE WORK OF OTHER TRADES. MINOR DEVIATIONS FROM THE PLANS MAY BE MADE TO AVOID MINOR CONFLICTS. WHEN MAJOR CONFLICTS ARE APPARENT, THE OWNER SHALL BE ADVISED IMMEDIATELY, AND THE AFFECTED WORK SHALL NOT BE INSTALLED UNTIL THE CONFLICT HAS BEEN RESOLVED.
- 7. ALL NECESSARY ALLOWANCES AND PROVISIONS SHALL BE MADE BY THE CONTRACTOR FOR BEAMS, COLUMNS TO OTHER OBSTRUCTIONS OF THE BUILDING OR THE WORK OF OTHER CONTRACTORS WHETHER OR NOT SAME IS INDICATED, WHERE NECESSARY TO AVOID OBSTRUCTIONS.
- 8. THE CONTRACTOR SHALL THOROUGHLY CLEAN THE WORK AREA DAILY. CONTRACTOR SHALL ALSO REMOVE ALL OF THE TRASH AND DEBRIS AFTER COMPLETION OF THE WORK.
- 9. EXCESSIVE CUTTING AND SIMILAR OPERATIONS LIKELY TO WEAKEN A BUILDING STRUCTURE TO FACILITATE THE PIPING INSTALLATION WILL NOT BE PERMITTED. IMPLEMENT SUITABLE MEASURES THROUGHOUT THE CONSTRUCTION PERIOD TO PREVENT TRASH AND DIRT FROM ENTERING PIPES, BEFORE, DURING AND AFTER INSTALLATION. UNLESS OTHERWISE INDICATED, RUN PIPING PARALLEL TO THE WALLS OF THE BUILDING. ERECT VERTICAL PIPING STRAIGHT AND PLUMB. WHERE PIPE IS TO BE INSULATED, PROVIDE A CLEARANCE EQUAL TO THE INSULATION PLUS A MINIMUM OF 1 INCH ALL AROUND.
- 10. THE INTERIOR SURFACES OF PIPING SHALL BE SMOOTH AND ENTIRELY FREE FROM OBSTRUCTIONS TO FLOW. CLEAN AND FLUSH THE SYSTEMS BEFORE CONNECTING TO EQUIPMENT. VERIFY THAT ALL FOREIGN MATERIAL HAS BEEN REMOVED BEFORE PLACING IN SERVICE.
- 11. LABEL PIPING AND EQUIPMENT PER THE SPECIFICATIONS.
- 12. SUPPORT PIPING AND EQUIPMENT PER THE SPECIFICATIONS AND MANUFACTURERS INSTRUCTIONS.
- 13. PROVIDE DIELECTRIC UNIONS/FITTINGS IN PIPING AT CONNECTIONS OF DISSIMILAR METAL PIPING AND TUBING.
- 14. PRIOR TO PIPING WORK, CAREFULLY INSPECT THE INSTALLED WORK AND EXCAVATION AND VERIFY THAT ALL SUCH WORK IS COMPLETE TO THE POINT WHERE THE PIPING MAY BE INSTALLED IN ACCORDANCE WITH THESE DOCUMENTS. FOLLOW THE DRAWINGS IN LAYING OUT WORK AND CHECK DRAWINGS OF OTHER TRADES TO VERIFY SUFFICIENT SPACE TO INSTALL PIPING. UNDIMENSIONED DRAWINGS ARE INTENDED TO INDICATE THE GENERAL ARRANGEMENT OF PIPING SYSTEMS AND ARE NOT INTENDED TO CONVEY PRECISE LOCATIONAL INFORMATION. COORDINATE WITH OTHER TRADES TO PERMIT ALL PHASES OF THE WORK TO BE INSTALLED. OFFSETS, FITTINGS AND EXTRA PIPE, NECESSARY TO AVOID INTERFERENCE OR PROVIDE MAXIMUM HEADROOM AND SPACE, SHALL BE FURNISHED AND INSTALLED WITHOUT ADDITIONAL EXPENSE TO THE OWNER. IF THE PIPING IS INSTALLED WITHOUT COORDINATING WITH OTHER PHASES OF THE WORK SO AS TO CAUSE INTERFERENCE, THE NECESSARY CHANGES SHALL BE MADE AT NO EXTRA CHARGE.

- 15. MAKE CHANGES IN DIRECTION IN DRAINAGE PIPING BY THE APPROPRIATE USE OF 45 DEGREE WYES; ONE-HALF WYES; LONG SWEEP QUARTER BENDS; SIXTH, EIGHTH OR SIXTEENTH BENDS; OR A COMBINATION OF THESE FITTINGS. NO CHANGES IN DIRECTION GREATER THAN 90 DEGREES SHALL BE MADE IN DRAINAGE PIPING. WHERE DIFFERENT SIZES OF DRAINAGE PIPES OR PIPES AND FITTINGS ARE TO BE CONNECTED, USE CORRECTLY SIZED STANDARD INCREASERS OR REDUCERS. DRILLING AND TAPPING OF DRAINS AND THE USE OF SADDLE HUBS AND BENDS ARE PROHIBITED.
- 16. EXAMINE ROUGHING-IN OF DRAINAGE PIPING SYSTEMS TO VERIFY ACTUAL LOCATIONS OF PIPING CONNECTIONS BEFORE PLUMBING SPECIALTIES ARE INSTALLED. EXAMINE FLOORS AND WALLS FOR SUITABLE LOCATIONS.


13

17. SEAL JOINTS BETWEEN PLUMBING SPECIALTIES AND WALLS USING MILDEW-RESISTANT SILICONE SEALANT.

10


- 18. EXCAVATE AND SHAPE TRENCH BOTTOMS TO PROVIDE UNIFORM BEARING AND SUPPORT OF PIPES. SHAPE SUBGRADE TO PROVIDE CONTINUOUS SUPPORT FOR BELLS, JOINTS AND BARRELS OF PIPES. REMOVE PROJECTING STONES AND SHARP OBJECTS ALONG TRENCH SUBGRADE. EXCAVATE TRENCHES 6 INCHES DEEPER THAN ELEVATION REQUIRED IN ROCK OR OTHER UNYIELDING BEARING MATERIAL, 4 INCHES DEEPER ELSEWHERE, TO ALLOW FOR BEDDING COURSE.
- 19. PLACE BACKFILL ON SUBGRADES FREE OF MUD, FROST, SNOW OR ICE. PLACE AND COMPACT BEDDING COURSE ON TRENCH BOTTOMS. SHAPE BEDDING COURSE TO PROVIDE CONTINUOUS SUPPORT FOR BELLS, JOINTS AND BARRELS OF PIPES.
- 20. BACKFILL TRENCHES EXCAVATED AND WITHIN 18 INCHES OF BOTTOM OF FOOTINGS WITH SATISFACTORY SOIL; FILL WITH CONCRETE TO ELEVATION OF BOTTOM OF FOOTINGS.
- 21. PLACE AND COMPACT INITIAL BACKFILL OF SUB-BASE MATERIAL, FREE OF PARTICLES LARGER THAN 1 INCH IN ANY DIMENSION, TO A HEIGHT OF 12 INCHES OVER THE PIPE. CAREFULLY COMPACT THE INITIAL BACKFILL UNDER PIPE HAUNCHES AND COMPACT EVENLY UP ON BOTH SIDES AND ALONG THE FULL LENGTH OF UTILITY PIPING. PLACE AND COMPACT FINAL BACKFILL OF SATISFACTORY SOIL TO FINAL SUBGRADE ELECTRORY SOIL TO FINAL SUBGRADE ELECTRORY SOIL TO FINAL SUBGRADE S
- 22. INSTALL HOSE-BIBBS AND WALL HYDRANTS 18 INCHES ABOVE FINISHED FLOOR OR GRADE UNLESS OTHERWISE NOTED.
- 23. COORDINATE PLUMBING EQUIPMENT AND MATERIAL LOCATIONS WITH ELECTRICAL, HVAC, FIRE SUPPRESSION, STRUCTURAL AND ARCHITECTURAL PLANS TO AVOID CONFLICTS.
- 24. ALL PLUMBING EQUIPMENT SHALL BE INSTALLED IN SUCH A MANNER SO THAT ALL VALVES, ETC., ARE COMPLETELY ACCESSIBLE AND SERVICEABLE, INCLUDING ACCESS DOORS IF REQUIRED.
- 25. WHERE PIPING PASSES THROUGH FIRE AND/OR SMOKE RATED WALLS OR CEILINGS, OPENINGS SHALL BE FIRE AND/OR SMOKE STOPPED PER THE APPROPRIATE UL DETAIL.


EGEND A	AND ABBREVIATIONS		T		T		
— SAN — —	SANITARY SOIL & WASTE (BELOW FLOOR)	————— НВ	HOSE BIBB	DN	DOWN	=	SHOCK ABSORBER (PLUMBING AND DRAINAGE INSTITUTE
— SAN ——	SANITARY SOIL & WASTE (ABOVE FLOOR)	—————————————————————————————————————	WALL HYDRANT	DWG	DRAWING EXISTING	PDI="0" PH	SIZING) PHASE
	SANITARY VENT	FD-"0"	FLOOR DRAIN WITH TRAP	(E) EL	ELEVATION	RD	ROOF DRAIN (COMBINATION)
	DOMESTIC COLD WATER			ERL	EMERGENCY RAIN LEADER	RECIRC	RECIRCULATING
	DOMESTIC HOT WATER		PIPE TURNING UP	F	(SECONDARY) FAHRENHEIT	RL RPZ	RAIN LEADER (PRIMARY) REDUCED PRESSURE ZONE
_ 		——————————————————————————————————————	PIPE TURNING DOWN	FCO	FLOOR CLEANOUT	SAN	BACKFLOW PREVENTER SANITARY
	DOMESTIC HOT WATER RECIRCULATING	ADA	AMERICANS WITH DISABILITIES ACT	FD	FLOOR DRAIN	SS	STAINLESS STEEL
_	BALL VALVE	AFF Q	ABOVE FINISHED FLOOR CENTER LINE	GPF	GALLONS PER FLUSH	ST	STORM
-	CHECK VALVE	CLG	CEILING	GPH	GALLONS PER HOUR	T&P	TEMPERATURE & PRESSURE
	DIDECTION OF FLOW IN DIDE	СО	CLEANOUT	GPM	GALLONS PER MINUTE	TYP	TYPICAL
-	DIRECTION OF FLOW IN PIPE	CW	DOMESTIC COLD WATER	HET	HIGH EFFICIENCY TOILET	V	VENT
	T & P RELIEF VALVE	DCW	DOMESTIC COLD WATER	HEU	HIGH EFFICIENCY URINAL	VTR	VENT THRU ROOF
.1.		DHW	DOMESTIC HOT WATER	HP	HORSEPOWER	W	WASTE
	PIPE UNION OR FLANGE	DHWR	DOMESTIC HOT WATER RECIRC	INV EL	INVERT ELEVATION	WCO	WALL CLEANOUT
FCO WCO → —	PIPE CLEANOUT (F = FLOOR, W = WALL)	DEG	DEGREES	MAX	MAXIMUM		
				MIN	MINIMUM		



ITED STATES ARMY RESERVE CENTER, SALEM, VA
TRAINING CENTER RENOVATION & ADDITION
P2 #: 499678
ID, ABBREVIATIONS AND GENERAL NOT


SHEET ID







US Army Corps of Engineers ®


PD102











13___

12

10



GENERAL SHEET NOTES

17


- 1 FOR LEGEND, ABBREVIATIONS AND GENERAL NOTES, SEE DRAWING P-001.
- VERIFY LOCATION AND SIZE OF SANITARY, VENT AND DOMESTIC WATER PIPING AND COORDINATE WITH NEW WORK DRAWINGS.
- 3 COORDINATE WITH CIVIL DRAWINGS FOR UTILITY LOCATIONS AND PIPING INVERT ELEVATIONS.

DEMOLITION KEYNOTES


S ARMY CORPS OF ENGINE
LOUISVILLE DISTRICT
LOUISVILLE, KY
JOHN C. GRIMBERG CO.
ROCKVILLE, MD
WILEYIWILSON
ALEXANDIRA, VA

US Army Corps of Engineers ®


SHEET ID VMS PD121



ENLARGED SANITARY PLAN - FIRST FLOOR WOMEN'S - DEMOLITION SCALE: 1/4" = 1'-0"



ENLARGED SANITARY PLAN - FIRST FLOOR MEN'S - DEMOLITION SCALE: 1/4" = 1'-0"



ENLARGED SANITARY PLAN - SECOND FLOOR MEN'S - DEMOLITION SCALE: 1/4" = 1'-0"

GENERAL SHEET NOTES

17


- 1 FOR LEGEND, ABBREVIATIONS AND GENERAL NOTES, SEE DRAWING P-001.
- 2 VERIFY LOCATION AND SIZE OF SANITARY, VENT AND DOMESTIC WATER PIPING AND COORDINATE WITH NEW WORK DRAWINGS.
- 3 COORDINATE WITH CIVIL DRAWINGS FOR UTILITY LOCATIONS AND PIPING INVERT ELEVATIONS.

DEMOLITION KEYNOTES

US Army Corps of Engineers ®

SHEET ID

PD401



SEE HEATING WATER 1 1/4" DCW DIAGRAM ON TO SHED -DWG M-501 — 1 1/4" DCW -115 GAL DHW STORAGE TANK REMOVE NATURAL GAS FIRED DOMESTIC SEE "DOMESTC WATER HEATER DEMOLITION DIAGRAM" ON DWG P-502 WATER HEATER — 1 1/2" DHW — 🗕 11- 2" DCW **BOILER ROOM** 102 1" DHW — CAPPED 3/4" DCW __ 2 1/2" DCW - 3" DCW, 1 1/2" DHW CORRIDOR SEE DWG PD104 126 DHW DCW SERVICE BELOW FIN FL —

12

13

10

GENERAL SHEET NOTES

17

16

- 1 FOR LEGEND, ABBREVIATIONS AND GENERAL NOTES, SEE DRAWING P-001.
- 2 VERIFY LOCATION AND SIZE OF SANITARY, VENT AND DOMESTIC WATER PIPING AND COORDINATE WITH NEW WORK DRAWINGS.


18

3 COORDINATE WITH CIVIL DRAWINGS FOR UTILITY LOCATIONS AND PIPING INVERT ELEVATIONS.

DEMOLITION KEYNOTES

ENLARGED DOMESTIC WATER PLAN - FIRST FLOOR WOMEN'S - DEMOLITION SCALE: 1/4" = 1'-0"

ENLARGED DOMESTIC WATER PLAN - FIRST FLOOR MECH ROOM - DEMOLITION SCALE: 1/4" = 1'-0"



— 1/2" DCW, 1/2" DHW TO SHOWER (TYP OF 4) FR BEL-OFFICE 207C FR BEL STO 207D - 1 1/4" DCW TO MEN'S URINAL (TYP OF 5) 205 1/2" DCW AND 1/2" DHW TO LAV (TYP OF 6) --<u>WC</u> <u>WC</u> <u>WC</u> 1" DHW FR BEL-

2" CW FR BEL-

2 1/2" DCW

ENLARGED DOMESTIC WATER PLAN - SECOND FLOOR MEN'S - DEMOLITION SCALE: 1/4" = 1'-0"

-2" DCW, 1 1/4" DCW

DN TO WC (TYP OF 5)


ENLARGED DOMESTIC WATER PLAN - FIRST FLOOR MEN'S - DEMOLITION B1 SCALE: 1/4" = 1'-0"

SHEET ID


SUBMISSION INTERIM DESIGN

JOHN C. GRIMBERG CO.
ROCKVILLE, MD
WILEY|WILSON
ALEXANDIRA, VA

US Army Corps of Engineers ®







13

10





GENERAL SHEET NOTES

18

17

16


- 1 FOR LEGEND, ABBREVIATIONS AND GENERAL NOTES, SEE DRAWING P-001. 2 VERIFY LOCATION AND SIZE OF SANITARY, VENT AND DOMESTIC WATER PIPING AND COORDINATE WITH NEW WORK DRAWINGS.
- 3 COORDINATE WITH CIVIL DRAWINGS FOR UTILITY LOCATIONS AND PIPING INVERT ELEVATIONS.


DEMOLITION KEYNOTES

US Army Corps of Engineers ®


IED STATES ARMY RESERVE CENTER, SALEM, TRAINING CENTER RENOVATION & ADDITION P2 #: 499678

INTERIM DESIGN SUBMISSION SHEET ID PD421







INTERIM DESIGN SUBMISSION SHEET ID P-102



INTERIM DESIGN SUBMISSION







INTERIM DESIGN SUBMISSION

P-105

17

18





13

10



17


- 1 FOR LEGEND, ABBREVIATIONS AND GENERAL NOTES, SEE DRAWING P-001.
- 2 FOR PLUMBING FIXTURE SCHEDULES, SEE DRAWING P-601.
- WERIFY LOCATION AND SIZE OF SANITARY, VENT AND DOMESTIC WATER PIPING AND COORDINATE WITH DEMOLITION DRAWINGS PRIOR TO FABRICATIONS.
- 4 COORDINATE WITH CIVIL DRAWINGS FOR UTILITY LOCATIONS AND PIPING INVERT ELEVATIONS.
- 5 REFER TO ARCHITECTURAL DRAWINGS FOR ROOM NAMES AND NUMBERS.

SHEET KEYNOTES


S ARMY CORPS OF ENGINE
LOUISVILLE DISTRICT
LOUISVILLE, KY
JOHN C. GRIMBERG CO.
ROCKVILLE, MD
WILEY|WILSON
ALEXANDIRA, VA

US Army Corps of Engineers ®

SHEET ID








B1 ENLARGED SANITARY PLAN - FIRST FLOOR MEN'S - NEW WORK

SCALE: 1/4" = 1'-0"

0' 2' 4' 8'



13

ENLARGED SANITARY PLAN - SECOND FLOOR - NEW WORK

SCALE: 1/4" = 1'-0"

0' 2' 4' 8'



GENERAL SHEET NOTES

17

- 1 FOR LEGEND, ABBREVIATIONS AND GENERAL NOTES, SEE DRAWING P-001.
- 2 FOR PLUMBING FIXTURE SCHEDULES, SEE DRAWING P-601.
- WERIFY LOCATION AND SIZE OF SANITARY, VENT AND DOMESTIC WATER PIPING AND COORDINATE WITH DEMOLITION DRAWINGS PRIOR TO FABRICATIONS.
- 4 COORDINATE WITH CIVIL DRAWINGS FOR UTILITY LOCATIONS AND PIPING INVERT ELEVATIONS.
- 5 REFER TO ARCHITECTURAL DRAWINGS FOR ROOM NAMES AND NUMBERS.

SHEET KEYNOTES

MY CORPS OF ENGINEERS

JEC

LOUISVILLE DISTRICT

LOUISVILLE, KY

LOUISVILLE, KY

LOUISVILLE, KY

JFC

CHECKED BY:

KEL

SOLICITATION NO.:

W912QR22R0040

CHECKED BY:

W912QR22R0040

SUBMITTED BY:

WILEYIWILSON


ALEXANDIRA, VA


MARR

MARR

D STATES ARMY RESERVE CENTER, SALEM, VA
RAINING CENTER RENOVATION & ADDITION
P2 #: 499678
ARGED SANITARY PLANS - NEW WORK

SHEET ID TC **P-401**





13

10

GENERAL SHEET NOTES

17

- 1 FOR LEGEND, ABBREVIATIONS AND GENERAL NOTES, SEE DRAWING P-001.
- 2 FOR PLUMBING FIXTURE SCHEDULES, SEE DRAWING P-601.
- 3 VERIFY LOCATION AND SIZE OF SANITARY, VENT AND DOMESTIC WATER PIPING AND COORDINATE WITH DEMOLITION DRAWINGS PRIOR TO FABRICATIONS.
- 4 COORDINATE WITH CIVIL DRAWINGS FOR UTILITY LOCATIONS AND PIPING INVERT ELEVATIONS.
- 5 REFER TO ARCHITECTURAL DRAWINGS FOR ROOM NAMES AND NUMBERS.

SHEET KEYNOTES

ENLARGED DOMESTIC WATER PLAN - FIRST FLOOR WOMEN'S - NEW WORK


SCALE: 1/4" = 1'-0"


0' 2' 4' 8'

9 ENLARGED DOMESTIC WATER PLAN - FIRST FLOOR MECH ROOM - NEW WORK

SCALE: 1/4" = 1'-0"

0' 2' 4' 8'





B1 ENLARGED DOMESTIC WATER PLAN - FIRST FLOOR MEN'S - NEW WORK

SCALE: 1/4" = 1'-0"

0' 2' 4' 8'

ENLARGED DOMESTIC WATER PLAN - SECOND FLOOR TOILETS - NEW WORK

SCALE: 1/4" = 1'-0"


O 2' 4' 8'

UNITED STATES ARMY RESERVE CENTER, SALI
TRAINING CENTER RENOVATION & ADDITIC
P2 #: 499678

TC ENLARGED DOMESTIC WATER PLANS -

US Army Corps of Engineers ®

SHEET ID TC P-402



10

11

12

13

14

15

16

17

1 FOR LEGEND, ABBREVIATIONS AND GENERAL NOTES, SEE DRAWING P-001.

2 FOR PLUMBING FIXTURE SCHEDULES, SEE DRAWING P-601.

18

3 VERIFY LOCATION AND SIZE OF SANITARY, VENT AND DOMESTIC WATER PIPING AND COORDINATE WITH DEMOLITION DRAWINGS PRIOR TO FABRICATIONS.

5 REFER TO ARCHITECTURAL DRAWINGS FOR ROOM NAMES AND NUMBERS.


JOHN C. GRIMBERG CO.
ROCKVILLE, MD
WILEY|WILSON
ALEXANDIRA, VA


US Army Corps

of Engineers ®


SHEET ID VMS P-421

INTERIM DESIGN SUBMISSION





	JMBING FI			1			1				1
AG	FIXTURE	APPLICABLE STANDARD	MATERIAL	MOUNTING AND OUTLET	DIMENSIONS (IN.)	RIM HEIGHT (IN.)	SIZE	CONNE (IN.)	CTION	FAUCETS, FITTINGS, AND ACCESSORIES	BASIS
		STANDARD		OUTLET	(114.)	(114.)	TRAP	CW	HW		
<u>/C-1</u>	WALL-MOUNTED ELONGATED WATER CLOSET	ASME A112.19.2 ADA	VITREOUS CHINA	FLOOR MOUNTED BOTTOM-OUTLET	26-3/4"x17-1/2"x14-1/4"	ADA 17" SEE ARCH ELEVATIONS	4"	1"		 SEATS: ELONGATED OPEN-FRONT TOILET SEAT WITH SELF-SUSTAINING STAINLESS STEEL CHECK HINGE. SUPPLY: MANUAL FLUSH VALVE SIPHON JET FLUSHING 	DESIGN CONSUMPTION: 1.1/1.28 GPF COLOR: WHITE BOLT CAPS
<u>/C-2</u>	WALL-MOUNTED ELONGATED WATER CLOSET	ASME A112.19.2 ADA	VITREOUS CHINA	FLOOR MOUNTED BOTTOM-OUTLET	26-3/4"x17-1/2"x14-1/4"	SEE ARCH ELEVATIONS	4"	1"		SEATS: ELONGATED OPEN-FRONT TOILET SEAT WITH SELF-SUSTAINING STAINLESS STEEL CHECK HINGE. SUPPLY: MANUAL FLUSH VALVE SIPHON JET FLUSHING	DESIGN CONSUMPTION: 1.1/1.28GPF COLOR: WHITE BOLT CAPS
<u>\V-1</u>	LAVATORY	ASME A112.18.1 FAUCET ASME A112.18.1 ANSI A117.1	VITREOUS CHINA SINK; LEAD FREE BRASS FAUCET WITH CHROME FINISH	UNDERMOUNT COUNTERTOP	20-3/8"x17-3/8" x7-7/8"	ADA 34"	1-1/2"	1/2"	1/2"	 FAUCET: ADA MANUAL FAUCET, PADDLE HANDLES, GOOSENECK FAUCET WITH 0.5 GPM TAMPERPROOF AERATOR, CERAMIC DISC VALVE CARTRIDGE, AND INTEGRAL HOT LIMIT SAFETY STOP. PROVIDE MIXING VALVE AND BRAIDED FLEX SUPPLY HOSES WITH COMPRESSION CONNECTORS. ADA PROTECTION TRAP, STOP, AND SUPPLY PROTECTORS. 	DESIGN FLOW RATE: 0.5 GPM FRONT OVERFLOW COLOR: WHITE
AV-2	LAVATORY	ASME A112.19.2 FAUCET ASME A112.18.1 ANSI A117.1	VITREOUS CHINA SINK; LEAD FREE BRASS FAUCET WITH CHROME FINISH	UNDERMOUNT COUNTERTOP	20-3/8"x17-3/8" x7-7/8"	34"	1-1/2"	1/2"	1/2"	 FAUCET: ELECTRONIC SENSOR FAUCET WITH 0.5 GPM TAMPERPROOF AERATOR, CERAMIC DISC VALVE CARTRIDGE, AND INTEGRAL HOT LIMIT SAFETY STOP. PROVIDE MIXING VALVE AND BRAIDED FLEX SUPPLY HOSES WITH COMPRESSION CONNECTORS. ADA PROTECTION TRAP, STOP, AND SUPPLY PROTECTORS. 	DESIGN FLOW RATE: 0.5 GPM FRONT OVERFLOW COLOR: WHITE
<u>4V-3</u>	LAVATORY	ASME A112.19.2 FAUCET ASME A112.18.1 ANSI A117.1	VITREOUS CHINA SINK; LEAD FREE BRASS FAUCET WITH CHROME FINISH	WALL MOUNTED	20"x18 1/4"x5"	ADA 34"	1-1/2"	1/2"	1/2"	 FAUCET: ELECTRONIC SENSOR FAUCET WITH 0.5 GPM TAMPERPROOF AERATOR, CERAMIC DISC VALVE CARTRIDGE, AND INTEGRAL HOT LIMIT SAFETY STOP. PROVIDE MIXING VALVE AND BRAIDED FLEX SUPPLY HOSES WITH COMPRESSION CONNECTORS. ADA PROTECTION TRAP, STOP, AND SUPPLY PROTECTORS. ADA WALL MOUNTED VITREOUS CHINA SINK BASIN. 	DESIGN FLOW RATE: 0.5 GPM FRONT OVERFLOW COLOR: WHITE
<u>SK</u>	SINK	ASME A112.18.1 FAUCET ASME A112.18.1 ANSI A117.1	OVAL VITREOUS CHINA SINK; LEAD FREE BRASS FAUCET WITH CHROME FINISH	UNDERMOUNT COUNTERTOP	21-1/2"x17-3/8" x5-1/2"	ADA 34"	1-1/2"	1/2"	1/2"	 FAUCET: ADA MANUAL FAUCET, PADDLE HANDLES, GOOSENECK FAUCET WITH 0.5 GPM TAMPERPROOF AERATOR, CERAMIC DISC VALVE CARTRIDGE, AND INTEGRAL HOT LIMIT SAFETY STOP. PROVIDE MIXING VALVE AND BRAIDED FLEX SUPPLY HOSES WITH COMPRESSION CONNECTORS. ADA PROTECTION TRAP, STOP, AND SUPPLY PROTECTORS. 	DESIGN FLOW RATE: 0.5 GPM FRONT OVERFLOW COLOR: WHITE
<u>U</u>	URINAL	ASME A112.19.2 ADA	VITREOUS CHINA	WALL-MOUNTED BACK-OUTLET	17-1/4"x20-3/4" x14-1/4"	19" STANDARD; ADA 12" SEE ARCH ELEVATIONS	2"	3/4"		1. MANUAL FLUSH VALVE 2. SUPPLY: CHROME-PLATED, 3/4" TOP INLET SPUD 3. PROVIDE CONCEALED TYPE WALL CARRIER	DESIGN CONSUMPTION: 0.125 GPF COLOR: WHITE
<u>JS</u>	JANITOR SINK	ASME A112.18.1	CAST-BRASS FAUCET TERRAZZO BASIN	WALL-MOUNTED FAUCET FLOOR-MOUNTED BASIN	24"x24"x12"		3"	1/2"	1/2"	FAUCET: PROVIDE WITH TOP WALL BRACE, STOPS, VACUUM BREAKER, BUCKET HOOK, AND THREADED SPOUT. PROVIDE FLAT GRID STRAINER/DRAIN, STAINLESS STEEL THRESHOLD CAP	
<u>VC-1</u>	HI/LOW ELECTRIC WATER COOLER WITH BOTTLE FILLING STATION	NSF/ANSI 42-53 AND 61-372	COPPER PIPING, STAINLESS STEEL BASIN & CASING	WALL-MOUNTED	36 1/4"x18 5/8"X46 1/4"	32-5/16" WITH ADA 27" CLEAR BELOW	1-1/4"	3/8"		 PROVIDE 1-1/4" COPPER TRAP WITH CLEANOUT PLUG. PROVIDE ASME A112.6.1M CONCEALED WALL HANGERS WITH THRU-BOLTS AND BACK PLATES PROVIDE DIELECTRIC COUPLINGS ON BOTH SUPPLY AND WASTE CONNECTIONS PROVIDE INTEGRAL RECESSED CHILLER. 	CHILLER: 8.0 GPH AT 50 DEG F FLOW RATE 370 RATED WATTS (5.0 FLA). MOUNTS TO FACTOR' PROVIDED FRAME.
<u>VC-2</u>	SINGLE ELECTRIC WATER COOLER WITH BOTTLE FILLING STATION	NSF/ANSI 42-53 AND 61-372	COPPER PIPING, STAINLESS STEEL BASIN & CASING	WALL-MOUNTED	17 7/8"X18 1/2"X39 3/4"	32-5/16" WITH ADA 27" CLEAR BELOW	1-1/4"	3/8"		 PROVIDE 1-1/4" COPPER TRAP WITH CLEANOUT PLUG. PROVIDE ASME A112.6.1M CONCEALED WALL HANGERS WITH THRU-BOLTS AND BACK PLATES PROVIDE DIELECTRIC COUPLINGS ON BOTH SUPPLY AND WASTE CONNECTIONS PROVIDE INTEGRAL RECESSED CHILLER. 	CHILLER: 8.0 GPH AT 50 DEG F FLOW RATE 370 RATED WATTS (5.0 FLA). MOUNTS TO FACTOR PROVIDED FRAME.
	ADA SHOWER SYSTEM	ASME A112.18.1	CHROME PLATED METAL	WALL-MOUNTED		VALVE: 48" SLIDE BAR: 48" - 78"	2"	1/2"	1/2"	REMOVABLE HAND HELD SPRAY WITH SWIVEL CONNECTOR, 60" STAINLESS STEEL FLEX HOSE, 30" SLIDE BAR, HOSE WALL OUTLET, VACUUM BREAKER. PRESSURE BALANCED SHOWER VALVE W/ADJUSTABLE TEMP LIMIT STOP.	DESIGN FLOW RATE: 1.5 GPM
<u>H-2</u>	SHOWER SYSTEM	ASME A112.18.1	CHROME PLATED METAL	WALL-MOUNTED		VALVE: 48" SHOWER HEAD: 80"	2"	1/2"	1/2"	PIVOTING SHOWER HEAD WITH VACUUM BREAKER. PRESSURE BALANCED SHOWER VALVE W/ADJUSTABLE TEMPERATURE LIMIT STOP	DESIGN FLOW RATE: 1.5 GPM
<u>WF</u>	WASH FOUNTAIN	ASME A112 .19.3 ASME A112 .18.1	304 STAINLESS STEEL	FLOOR MOUNTED	36"X26"X44"	33 1/4"	1 1/2"	1/2"	1/2"	AIR VALVE FOOT CONTROL LOW-VOLTAGE PLUG-IN ADAPTER EACH OUTLET IS CONTROLLED BY A SEPARATE SLOW-CLOSING SOLENOID VALVE. INFRARED SENSOR MODULE. 4. THREE WASH STATIONS	DESIGN FLOW RATE: 1.5 GPM



TED STATES ARMY RESERVE CENTER, SALEM, VATRAINING CENTER RENOVATION & ADDITION P2 #: 499678

INTERIM DESIGN SUBMISSION

SHEET ID

P-601

PLU	MBING SPE	CIALITIE	ES SCHEDULE	S			
TAG	FIXTURE	APPLICABLE STANDARD	BODY MATERIAL	COLOR/FINISH	OUTLET CONNECTION	INLET CONNECTION	ACCESSORIES AND REMARKS
RPZ	DOMESTIC WATER BACKFLOW PREVENTER	AWWA C511-92	STAINLESS STEEL	STAINLESS STEEL	4"	4"	THE ASSEMBLY SHALL MEET THE REQUIREMENTS OF ASSE STD 1013; AWWA STD. C511; CSA B64.4 PROVIDE STRAINER
FCO	FLOOR CLEANOUT	ASME A112.36.2M	CAST-IRON	POLISHED BRONZE	AS INDICATED ON DRAWINGS		5-3/4" DIAMETER ROUND MEDIUM DUTY WITH TAPER THREAD SEAL, CLOSURE PLUG. HUB AND SPIGOT OR HUBLESS, TEE COMPATIBLE WITH PIPING, VANDAL PROOF TOP. NICKEL-BRONZE TOP IN FINISHED FLOORS, CAST IRON IN UNFINISHED FLOORS.
со	CLEANOUT	ASME A112.36.2M	EPOXY COATED CAST-IRON	BRONZE	AS INDICATED ON DRAWINGS		ROUND HEAVY DUTY WITH TAPER THREAD SEAL, CLOSURE PLUG. HUB AND SPIGOT OR HUBLESS, TEE COMPATIBLE WITH PIPING, VANDAL PROOF CAST IRON TOP.
wco	WALL CLEANOUT	ASME A112.36.2M	CAST-IRON	STAINLESS STEEL	AS INDICATED ON DRAWINGS		7-3/4" CHROME PLATED BRONZE SQUARE FRAME, CAST BRONZE TAPER THREAD PLUG. VANDAL PROOF SCREWS.
НВ	HOSE BIBB	ASME A112.21.3M	CAST BRONZE	STAINLESS STEEL	3/4"	3/4"	BRONZE INTERIOR HOSE BIBB WITH INTEGRAL VACUUM REAKER, REMOVABLE WHEEL HANDLE, AND 3/4" HOSE THREAD OUTLET
WH	WALL HYDRANT	ASME A112.21.3M	CAST BRONZE	STAINLESS STEEL	3/4"	3/4"	BRONZE QUARTER TURN NON-FREEZE AUTOMATIC DRAINING, STAINLESS STEEL FACE, 6" CORE DRILLED WALL-MOUNTED SINGLE-HOLE FAUCET WITH INTEGRAL VACUUM BREAKER AND DUAL CHECK VALVE, LOOSE KEY HANDLE, LOCK SHIELD CAP, AND 3/4" HOSE THREAD OUTLET
SS/EW	SAFETY SHOWER / EYE WASH	-	SCH 40 GALV WITH ORANGE PIPE COVER PLASTIC SHOWER HEAD AND STAINLESS STEEL BOWL	-	1 1/4"	1 1/4"	1 1/4" NPT FEMALE TOP OR SIDE INLET SUPPLY AT 20 GPM EMERGENCY THERMOSTATIC MIXING VALVE FLOOR MOUNTED SET MIXING VALVE AT 80 DEG F

FLOOR AND ROOF DRAIN SCHEDULE					
DESIGNATION	ITEM	BODY CONSTRUCTION	STRAINER CONSTRUCTION	CONNECTION	DESCRIPTION
FD	FLOOR DRAIN	COATED CAST-IRON	LIGHT DUTY NICKEL BRONZE	HUB OUTLET WITH GASKET	TWO-PIECE BODY WITH DOUBLE DRAINAGE FLANGE, FLASHING COLLAR, WEEPHOLES, BOTTOM OUTLET, ADJUSTABLE ROUND STRAINER. PROVIDE WITH ELASTOMERIC TRAP GUARD WITH CURL CLOSURE AT BOTTOM.
FFD	FUNNEL FLOOR DRAIN	COATED CAST-IRON	LIGHT DUTY NICKEL BRONZE WITH NICKEL BRONZE FUNNEL	HUB OUTLET WITH GASKET	TWO-PIECE BODY WITH DOUBLE DRAINAGE FLANGE, FLASHING COLLAR, WEEPHOLES, BOTTOM OUTLET, ADJUSTABLE ROUND STRAINER WITH FUNNEL. PROVIDE WITH ELASTOMERIC TRAP GUARD WITH CURL CLOSURE AT BOTTOM.

WATER HE	ATER SC	HEDULE					
DESIGNATION	BUILDING	TYPE	TANK CAPACITY (GALLONS)	RECOVERY CAPACITY (GALLONS PER HOUR)	TEMPERATURE RISE (DEGREES F)	INPUT BTU / HR	ELECTRICAL CHARACTERISTICS (VOLT/PH/Hz)
DWH-1	TC	NATURAL GAS STORAGE	90	175	100	150,000	120/1/60
DWH-2	VMS	NATURAL GAS STORAGE	110	328	100	285,000	120/1/60

DESIGNATION	DWH-1	DWH-2
LOCATION	TC BUILDING	VMS BUILDING
SERVICE	DOMESTIC HOT WATER	DOMESTIC HOT WATER
TANK SIZE (GALLONS)	10.3	10.3
FILL PRESSURE (PSI)	60	60
RELIEF VALVE PRESSURE SETTING (PSI)	120	120



MARK DESCRIPTION DATE

| DRAWN BY: SOLICITATION NO.: JFC | W912QR22R0040 | SUBMITTED BY: W912QR22R0040 | SUBMITTED BY: | SIZE: | ANSI D | SUBMITTED BY: | ANSI D | SUBMITTED BY: | SIZE: | ANSI D | SUBMITTED BY: | SIZE: | ANSI D | SUBMITTED BY: | SIZE: | SIZE: | SIZE: | SUBMITTED BY: | SIZE: | SUBMITTED BY: | SIZE: | SIZE: | SUBMITTED BY: | SUBMITTED BY: | SIZE: | SUBMITTED BY: | SUBMITTE

US ARMY CORPS OF ENGINEERS
LOUISVILLE DISTRICT
LOUISVILLE, KY
JOHN C. GRIMBERG CO.
ROCKVILLE, MD
WILEY|WILSON
ALEXANDIRA, VA

TED STATES ARMY RESERVE CENTER, SALEM, VA
TRAINING CENTER RENOVATION & ADDITION
P2 #: 499678
SCHEDULES II

INTERIM DESIGN SUBMISSION

SHEET ID

P-602